

1. Inspections of one- and two-family dwellings for which construction must cease until the inspection is made shall be limited to the following:

i. The bottom of footing trenches before placement of footings, except that in the case of pile foundations, inspections shall be made in accordance with the requirements of the building subcode;

ii. Foundations and all walls up to grade level prior to covering or back filling;

(1) For new construction, a foundation location survey showing all building corners of the foundation and the elevation of the top of the foundation wall shall be submitted to the construction official as soon as possible after the installation of the foundation wall. It is not necessary for work to cease for the preparation and submission of this survey. A land surveyor or professional engineer licensed in the State of New Jersey shall prepare the survey. The proposed foundation location and elevation as shown on the original plot plan shall also be shown on the foundation location survey.

(A) Exception: A foundation location survey shall not be required for additions, decks, swimming pools, sheds as described in N.J.A.C. 5:23-9.9 or similar structures.

(2) For new construction and additions, the foundation location survey for a building that is located in a flood plain shall include flood hazard certificates as required by section 1612.5 of the building subcode or section R301.2.4 of the one-and two-family dwelling subcode.

iii. Utility services, including septic;

iv. Mid-point inspections shall include the following:

(1) Building Subcode: All structural framing, connections, wall and roof sheathing, and insulation.

(A) The framing inspection shall take place after the rough electrical and plumbing inspections and after the installation of the heating, ventilation and/or air conditioning duct system.

(B) For buildings containing roof or other truss systems, a truss system and permanent truss bracing inspection shall be performed prior to the installation of any interior roof truss covering material. Where the truss design utilizes the interior finish as bracing for the bottom cord, that portion of the bracing shall be part of the final inspection and shall be in addition to the components of the final inspection in (d) below.

(C) The insulation inspection shall be performed after all other subcode rough inspections

and prior to the installation of any interior finish material.

(D) The inspector shall use a Department approved checklist.

(E) Prior to inspection, the responsible person in charge of work shall provide to the building inspector a signed framing checklist to be verified and initialed by the inspector and then made part of the permit file.

(2) Electrical Subcode: Rough wiring, panel and service installation.

(3) Plumbing Subcode: Rough piping.

2. Inspections for all subcodes of construction, other than one-and two-family dwellings, shall be limited to those required for one-and two-family dwellings and the following: fire suppression systems; heat producing devices; any special inspections required by any subcode of the regulations;

i. The mid-point inspection shall include a review for compliance with N.J.A.C. 5:23-7, the Barrier Free Subcode, for buildings required by N.J.A.C. 5:23-7.1 to be accessible.

3. Any additional inspections, as permitted by this chapter and as may be required by the municipality, shall be of the type and nature that construction may continue without interruption;

4. Additional inspection schedule: Where buildings proposed for construction exceed two stories in height or by their nature pose complex or unusual inspection problems, the construction official or appropriate subcode official may specify additional inspections to the applicant in writing prior to the issuance of a permit and during construction in the case of unforeseeable circumstances.

(c) Notice for inspection:

1. The owner or other responsible person in charge of work shall notify the enforcing agency when the work is ready for any required inspection specified herein or required by the construction official or appropriate subcode official. This notice shall be given at least 24 hours prior to the time the inspection is desired. This notice shall represent an attestation on the part of the owner, other than single-family owner-occupants performing their own work, or other responsible person in charge of work, that the work has been completed in conformance with the code and is ready for inspection.

2. Inspections shall be performed within three business days of the time for which it was requested. The work shall not proceed in a manner which will preclude the inspection until it has been made.

(d) Final inspection: Upon completion of the building or structure, and before the issuance of a certificate of use and

occupancy required herein, a final inspection shall be made, and any violations of the code shall be noted and the holder of the permit shall be notified of any discrepancies by the construction official. The final inspection shall include:

1. Building and Fire Subcode: Installation of all interior and exterior finish materials, sealing of exterior joints, mechanical system and any other required equipment.
2. Electrical Subcode: Wiring, devices and fixtures.
3. Plumbing Subcode: Piping, trim and fixtures.
4. Tests required by any provision of the adopted subcodes.
5. A review for compliance with N.J.A.C. 5:23-7, the Barrier Free Subcode, for all buildings required by N.J.A.C. 5:23-7.1 to be accessible.
6. Verification of compliance with N.J.A.C. 5:23-3.5, Posting structures.

(e) Inspections records: The enforcing agency shall make a written record of all inspections, including any discrepancies or violations noted and shall maintain those reports as a public record which shall be available for public inspection during normal business hours.

(f) Department inspections: At the request of an enforcing agency, the Department may assist the enforcing agency in the inspection of any construction, provided that the enforcing agency has submitted the plans and specifications for such construction to the Department.

(g) The construction official shall serve as an agent of the Bureau of Housing Inspection of the Department of Community Affairs for the purpose of inspecting newly constructed and altered hotels and multiple dwellings in order to enforce the provisions of the regulations for the maintenance of hotels and multiple dwellings (N.J.A.C. 5:10). Responsibility for inspection may be delegated to the appropriate subcode official(s).

(h) Periodic inspections: The building subcode official or fire protection subcode official may periodically inspect all existing buildings and structures, except one and two family dwellings, for compliance with the rules with respect to posting. Such inspection shall specify any violation of the rules with respect to the posting of floor load, occupancy load and use group of the building.

Amended by R.1981 d.182, effective June 4, 1981.
See: 13 N.J.R. 187(b), 13 N.J.R. 333(b).
Amended by R.1992 d.244, effective June 15, 1992.
See: 24 N.J.R. 1147(a), 24 N.J.R. 2243(a).

Class I inspections added to (b)Iiv.
Amended by R.1996 d.323, effective July 15, 1996 (operative January 1, 1997).
See: 28 N.J.R. 2112(a), 28 N.J.R. 3549(a).
Amended by R.1997 d.304, effective July 21, 1997.
See: 29 N.J.R. 2204(a), 29 N.J.R. 3248(a).
Added (b)lii(1) and (d)l.

Amended by R.2000 d.166, effective April 17, 2000.
See: 31 N.J.R. 4151(a), 32 N.J.R. 1376(a).

In (d), added 2; and added (h).
Amended by R.2003 d.187, effective May 5, 2003.
See: 34 N.J.R. 4248(a), 35 N.J.R. 1939(c).

In (b), rewrote Iiv.
Amended by R.2003 d.216, effective May 19, 2003.
See: 35 N.J.R. 16(a), 35 N.J.R. 2203(a).

Rewrote the section.
Administrative correction.
See: 35 N.J.R. 3298(a).
Amended by R.2006 d.75, effective February 21, 2006.
See: 37 N.J.R. 3110(a), 38 N.J.R. 1183(a).

Added (b)liv(1)(E).
Amended by R.2007 d.46, effective February 5, 2007.
See: 38 N.J.R. 872(a), 39 N.J.R. 370(b).

In (c)1, added new third sentence, and recodified former third sentence as new (c)2.

Administrative correction.
See: 39 N.J.R. 3914(a).
Amended by R.2008 d.192, effective July 21, 2008.
See: 39 N.J.R. 4985(a), 40 N.J.R. 4314(b).

In the introductory paragraph of (b)1, substituted "one- and" for "one-and"; and in the introductory paragraph of (b)lii(1), inserted "and the elevation of the top of the foundation wall", "or professional engineer" and "and elevation", and inserted the second sentence.

5:23-2.18A Utility load management device installation programs

(a) Whenever a public utility proposes to undertake a program of installing load management devices at the properties of a substantial number of service customers within a limited period of time, it may apply to the Department for permission to utilize the procedure set forth in this section.

(b) A utility with a program to install load management devices shall submit detailed information to the Department on the design of the device.

(c) The utility shall provide an educational program acceptable to the Department to acquaint any interested Department personnel and municipal subcode officials with the device and with installation and operating procedures.

(d) The utility shall insure that all devices to be installed are identical in design, listed and labeled or otherwise approved according to this chapter for their intended use.

(e) At least one month in advance of any installations, the utility shall submit to the Department, and to each affected municipality, notice of the anticipated number of installations to be performed in each municipality. A maximum and a minimum figure may be submitted where there is uncertainty about the number to be scheduled by customers. An approximate number of weeks for installations in that municipality shall be given along with an approximate number of installations per week.

1. Each week, in advance of installation, the utility shall notify the municipality of any change in the anticipated number of installations for that week. No weekly number of installations shall be so great that the cumulative number of installations in the municipality shall exceed the maximum anticipated number submitted.