

CHAPTER 29

NOISE CONTROL

Authority

N.J.S.A. 13:1D-1 et seq. and 13:1G-1 et seq.

Source and Effective Date

R.1990 d.262, effective May 21, 1990.
See: 22 N.J.R. 307(b), 22 N.J.R. 1576(a).

Executive Order No. 66(1978) Expiration Date

Chapter 29, Noise Control, expires on May 21, 1995.

Chapter Historical Note

Chapter 29, Noise Control, was originally adopted as R.1974 d.12, effective January 18, 1974. See: 5 N.J.R. 334(a), 6 N.J.R. 59(b).

Subchapter 2, Noise from Vessels and Watercraft, was adopted as R.1977 d.177, effective May 20, 1977. See: 9 N.J.R. 167(d), 9 N.J.R. 266(a). Subchapter 2 was repealed by R.1979 d.12 and new rules concerning watercraft noise control adopted at N.J.A.C. 7:6-6, effective March 1, 1979. See: 10 N.J.R. 475(a), 11 N.J.R. 63(d).

Pursuant to Executive Order No. 66(1978), Chapter 29 was readopted as R.1990 d.262. See: Source and Effective Date. A new Subchapter 2, Procedures for the Determination of Noise from Stationary Sources, originally adopted as Chapter 29B, was adopted as R.1993 d.301, effective June 21, 1993. See: 25 N.J.R. 1040(a), 25 N.J.R. 2721(a).

See section annotations for specific rulemaking activity.

CHAPTER TABLE OF CONTENTS

SUBCHAPTER 1. GENERAL PROVISIONS

- 7:29-1.1 Definitions
- 7:29-1.2 Industrial, commercial, public service, or community service facilities
- 7:29-1.3 Stationary emergency signaling devices
- 7:29-1.4 Exceptions
- 7:29-1.5 Performance test principle

SUBCHAPTER 2. PROCEDURES FOR THE DETERMINATION OF NOISE FROM STATIONARY SOURCES

- 7:29-2.1 Definitions
- 7:29-2.2 Acceptable test methods
- 7:29-2.3 Measurement principle
- 7:29-2.4 Operating conditions during the test
- 7:29-2.5 General requirements
- 7:29-2.6 Equipment
- 7:29-2.7 Reporting requirements
- 7:29-2.8 Preparation for testing
- 7:29-2.9 Procedure
- 7:29-2.10 Calculations
- 7:29-2.11 Qualifications of investigative personnel
- 7:29-2.12 Incorporation by reference

SUBCHAPTER 1. GENERAL PROVISIONS

7:29-1.1 Definitions

The following words and terms, when used in this subchapter, shall have the following meanings unless the context clearly indicates otherwise.

"Commercial facility" means any premises, property, or facility involving traffic in goods or furnishing of services for sale or profit including, but not limited to:

1. Banking and other financial institutions;
2. Dining establishments;
3. Establishments for providing retail services;
4. Establishments for providing wholesale services;
5. Establishments for recreation and entertainment;
6. Office buildings;
7. Transportation;
8. Warehouses.

"Community service facility" means any non-residential facility used to provide services to the public, including but not limited to:

1. Club meeting halls, offices and facilities;
2. Organization offices and facilities;
3. Facilities for the support and practice of religion;
4. Private and parochial schools.

"Continuous airborne sound" means sound that is measured by the slow response setting of a sound level meter in accordance with the provisions of N.J.A.C. 7:29-2.

"dBA" means the abbreviation designating the unit of sound level as measured by a sound level meter using the A-weighting.

"Decibel" means the practical unit of measurement for sound pressure level; the number of decibels of a measured sound is equal to 20 times the logarithm to the base 10 of the ratio of the sound pressure of the measured sound to the sound pressure of a standard sound (20 micropascals); abbreviated "dB".

"Emergency energy release device" means a device used specifically to release excess energy on a non-scheduled basis as necessary for purposes of safety.

"Frequency" means the number of sound pressure oscillations per second, expressed in hertz; abbreviated "Hz".

"Impulsive sound" means either a single pressure peak or a single burst (multiple pressure peaks) having a duration of less than one second.

"Industrial facility" means any activity and its related premises, property, facilities, or equipment involving the fabrication, manufacture, or production of durable or non-durable goods.

"Octave band sound pressure level" means the sound pressure level measured in decibels in standard octave bands with a sound level meter.

"Peak sound pressure level" means the maximum instantaneous sound pressure level measured by a sound level meter on the PEAK setting.

"Person" means any individual, public or private corporation, political subdivision, governmental agency, department or bureau of the State, municipality, industry, copartnership, or association.

"Public service facility" means any facility and its related premises, property, or equipment used to provide governmental services to the public including, but not limited to:

1. Maintenance centers;
2. Offices and buildings of agencies or instrumentalities of government;
3. Schools;
4. Waste collection centers;
5. Waste recycling centers; and
6. Water and sewage facilities.

"Residential property" means property used for human habitation including, but not limited to:

1. Private property used for human habitation;
2. Commercial living accommodations and commercial property used for human habitation;
3. Recreational and entertainment property used for human habitation;
4. Community service property used for human habitation.

"Sound level" means the sound pressure level measured in decibels with a sound level meter set for A-weighting; sound level is expressed in dBA.

"Sound level meter" means an instrument used in accordance with the provisions of N.J.A.C. 7:29-2 to measure sound pressure level, sound level, octave band sound pressure level, or peak sound pressure level, separately or in any combinations thereof.

"Sound pressure level" means the level of a sound measured in dB units with a sound level meter which has a uniform ("flat") response over the band of frequencies measured.

"Stationary emergency signaling device" means any device, excluding those attached to motor vehicles, used to alert persons engaged in emergency operations. These include, but are not limited to, fire-fighters, first aid squad members, and law enforcement officers, whether paid or volunteer.

Amended by R.1985 d.129, effective March 18, 1985.

See: 16 N.J.R. 1682(a), 17 N.J.R. 699(b).

Substantially amended.

Amended by R.1993 d.301, effective June 21, 1993.

See: 25 N.J.R. 1040(a), 25 N.J.R. 2721(a).

Case Notes

Since the Department of Environmental Protection has not adopted regulations specifying or limiting the volume of sound to be emitted by fire sirens, or their location, these areas are not preempted from local regulation. *Malhame v. Boro. of Demarest*, 162 N.J.Super. 248, 392 A.2d 652 (Law Div.1978) appeal dismissed 174 N.J.Super. 28, 415 A.2d 358.

7:29-1.2 Industrial, commercial, public service, or community service facilities

(a) No person shall cause, suffer, allow, or permit sound from any industrial, commercial, public service or community service facility that, when measured at any residential property line, is in excess of any of the following:

1. From 7:00 A.M. to 10:00 P.M.:

- i. Continuous airborne sound which has a sound level in excess of 65 dBA; or
- ii. Continuous airborne sound which has an octave band sound pressure level in decibels which exceeds the values listed below in one or more octave bands:

Octave Band Center Frequency (Hz)	Octave Band Sound Pressure Level (dB)
31.5	96
63	82
125	74
250	67
500	63
1000	60
2000	57
4000	55
8000	53

or,

- iii. Impulsive sound in air which has a peak sound pressure level in excess of 80 decibels.

2. From 10:00 P.M. to 7:00 A.M.:

- i. Continuous airborne sound which has a sound level in excess of 50 dBA; or

- ii. Continuous airborne sound which has an octave band sound pressure level in decibels which exceeds the value listed below in one or more octave bands:

Octave Band Center Frequency (Hz)	Octave Band Sound Pressure Level (dB)
31.5	86
63	71
125	61
250	53
500	48
1000	45
2000	42
4000	40
8000	38

or

- iii. Impulsive sound in air which has a peak sound pressure level in excess of 80 decibels.

(b) No person shall cause, suffer, allow, or permit sound from any industrial, commercial, public service, or community service facility that, when measured at the property line of any other commercial facility is in excess of any of the following:

1. Continuous airborne sound which has a sound level in excess of 65 dBA; or
2. Continuous airborne sound which has an octave band sound pressure level in decibels which exceeds the values listed below in one or more octave bands:

Octave Band Center Frequency (Hz)	Octave Band Sound Pressure Level (dB)
31.5	96
63	82
125	74
250	67
500	63
1000	60
2000	57
4000	55
8000	53

or

3. Impulsive sound in air which has a peak sound pressure level in excess of 80 decibels.

Amended by R.1985 d.129, effective March 18, 1985.
See: 16 N.J.R. 1682(a), 17 N.J.R. 699(b).

Substantially amended.

Amended by R.1993 d.301, effective June 21, 1993.
See: 25 N.J.R. 1040(a), 25 N.J.R. 2721(a).

7:29-1.3 Stationary emergency signaling devices

(a) Testing of only the electromechanical functioning of a stationary emergency signaling device shall occur at the same time each day that a test is performed, but not before 8:00 A.M. or after 8:00 P.M. Any such testing shall only use the minimum cycle test time. Except as provided for in (b) below, such test time shall not exceed ten seconds.

(b) Testing of the complete emergency signaling system including the electromechanical functioning of the signaling device and the personnel response to the signal shall not occur more than once in each calendar month. Such testing shall not occur before 8:00 A.M. or after 8:00 P.M. The ten second time limit on the electromechanical functioning of the signaling device shall not apply to such system testing.

(c) Stationary emergency signaling devices shall be used only for testing in compliance with applicable provisions of these regulations and for emergency purposes where personnel and equipment are mobilized.

Amended by R.1985 d.129, effective March 18, 1985.

See: 16 N.J.R. 1682(a), 17 N.J.R. 699(b).

Substantially amended.

Case Notes

Since the department has not adopted regulations specifying or limiting the volume of sound to be emitted by fire sirens, or their location, these areas are not preempted from local regulation. *Malhame v. Boro. of Demarest*, 162 N.J.Super. 248, 392 A.2d 652 (Law Div.1978) appeal dismissed 174 N.J.Super. 28, 415 A.2d 358.

7:29-1.4 Exceptions

(a) The operational performance standards established in this subchapter shall not apply to any of the following noise sources:

1. Agriculture;
2. Bells, chimes or carillons while being used in conjunction with religious services;
3. Emergency energy release devices;
4. Emergency work to provide electricity, water or other public utilities when public health or safety is involved;
5. Motor vehicle race tracks;
6. National Warning System (NAWAS): Systems used to warn the community of attack or imminent public danger such as flooding or explosion. These systems are controlled by the New Jersey Office of Emergency or Hazardous Spill Management, Division of State Police;
7. Noise of aircraft flight operations;
8. Public celebrations;
9. Public roadways;
10. Surface carriers engaged in commerce by railroad;
11. The unamplified human voice;
12. Use of explosive devices: These are regulated by the New Jersey Department of Labor under the 1960 Explosive Act (N.J.S.A. 21:1A-1 to 21:1A-144).

Amended by R.1985 d.129, effective March 18, 1985.

See: 16 N.J.R. 1682(a), 17 N.J.R. 699(b).

Substantially amended.

Petition for Rulemaking: Regulations governing noise control pertaining to motor vehicle race tracks.

See: 23 N.J.R. 3535(a).

Petition for Rulemaking: Noise control for racetracks; public hearing.

See: 24 N.J.R. 2299(a), 24 N.J.R. 3440(d).

7:29-1.5 Performance test principle

For the purposes of measuring sound in accordance with the applicable provisions of these regulations, test equipment methods and procedures shall conform to the provisions of N.J.A.C. 7:29B-1.

Amended by R.1985 d.129, effective March 18, 1985.

See: 16 N.J.R. 1682(a), 17 N.J.R. 699(b).

Deleted "standards as published by the Department or its approved equivalent" and substituted "the provisions of N.J.A.C. 7:29-2."

SUBCHAPTER 2. PROCEDURES FOR THE DETERMINATION OF NOISE FROM STATIONARY SOURCES

7:29-2.1 Definitions

The following words and terms, when used in this subchapter, shall have the following meanings, unless the context clearly indicates otherwise. Terms not defined in this section are intended to be used as defined in the New Jersey Noise Control Act, N.J.S.A. 13:1G, and in this chapter, or are used in their common engineering or scientific sense.

"A-weighted sound level" means the sound level in decibels, reported as measured by a sound level measuring instrument having an "A"-weighting network which discriminates against the lower frequencies according to a relationship approximating the auditory sensitivity of the human ear. The level so read is designated dBA.

"Department" means the Department of Environmental Protection and Energy.

"Duty cycle" means the period of time for one operating cycle for equipment which cycles periodically at a regular rate; e.g., five minutes on, 10 minutes off equals a 15 minute duty cycle.

"Extraneous sound" means a sound which is neither part of the neighborhood residual sound nor comes from the source under investigation.

"Facility" means land and/or buildings used for commercial or industrial operations which produce the sound under investigation.

"Neighborhood residual sound level" means that measured value which represents the summation of the sound from all of the discrete sources affecting a given site at a given time, exclusive of extraneous and transient sounds and the sound from the source of interest.

"Noise" means, for purposes of this procedure, any sound which is not in conformance with the provisions of this chapter.

"Octave" means any two frequencies whose ratio is exactly two to one.

"Octave band" means a spectrum of sound frequencies between band edge frequencies an octave apart. For purposes of this procedure, octave band frequencies are as specified in Table 1, Page 11, of ANSI S1.11-1966 (R-1976) "specifications for octave, half-octave and third-octave band filter sets" (see N.J.A.C. 7:29-2.12(a)1).

"Sound level meter" means an instrument approved by the Department for the measurement of noise and sound levels.

"Sound source" means any person, animal, device, operation, process, activity, or phenomenon which emits or causes sound.

"Sound spectrum" means the description of the resolution of a sound into its frequency and amplitude components.

"Steady state sound" means a sound whose level remains constant during measurement.

"Total sound level" means that measured level which represents the summation of the sounds from all of the sound sources affecting a given place at a given time.

"Transient sound" means a sound whose level does not remain constant during measurement.

"Wind screen" means a device recommended by the manufacturer as a microphone cover to reduce the effect of wind.

7:29-2.2 Acceptable test methods

Testing shall be conducted in accordance with methods set forth hereinafter. Alternative methods, procedures, or instruments may be used subject to approval and conditions prescribed by the Department. The Department may itself employ such alternatives when warranted by test conditions or other circumstances.

7:29-2.3 Measurement principle

For purposes of measuring noise in accordance with applicable provisions of the rules of the Department, sound levels shall be determined by a qualified investigator using instruments and procedures prescribed by the Department.

Case Notes

Noise measuring procedures cited in holding that occupational hearing loss may be proven without evidence of decibel levels in excess of statutorily permissible limits. *Bronico v. J.T. Baker Chemical Co.*, 209 N.J.Super. 220, 507 A.2d 279 (App.Div.1986).

7:29-2.4 Operating conditions during the test

Insofar as practicable, sound will be measured while the source under investigation is operating at normal, routine conditions and, as necessary, at other conditions including, but not limited to, design, maximum and fluctuating rates. For test purposes, these conditions will apply during the times from 7:00 A.M. to 10:00 P.M. and from 10:00 P.M. to 7:00 A.M.

7:29-2.5 General requirements

(a) All tests shall be conducted in accordance with the following procedures:

1. The investigator shall, to the extent practicable, identify all sources contributing sound to the point of measurement.
2. Measurements shall be taken at or within the property line of any affected person.
3. The measuring device must be calibrated before and after each series of readings and at least once every hour.
4. The measuring device must be recertified and the calibrator must be recalibrated at least once per year by the manufacturer or by a person that has been approved by the Department. A copy of written documentation of such recertification and recalibration, in a form approved by the Department, shall be kept with the equipment to which it refers.
5. No outdoor measurements shall be made:
 - i. During periods when the wind speed exceeds 12 miles per hour (including gusts).
 - ii. Without a wind screen properly attached to the measuring device.
 - iii. Under any condition which allows the measuring device to become wet, such as rain, snow, or condensation.
 - iv. When the ambient temperature is below 14 degrees F (-10 degrees C) or above 122 degrees F (50 degrees C).

7:29-2.6 Equipment

(a) Requirements for equipment are as follows:

1. Sound level meters:
 - i. Measurements of continuous sound shall be made either with a Type 1 (Precision) or a Type 2 (General Purpose) sound level meter manufactured to the requirements of ANSI S1.4-1971 "specification for sound level meters" (see N.J.A.C. 7:29-2.12(a)2) or its successor. These meters shall have a range which includes 30-130 decibels.
 - ii. Measurements of impulse sound shall be made with a Type 1 (Precision) or with a Type 2 (General

Purpose) sound level meter equipped for measuring peak values and manufactured to the requirements of IEC Publication 651 (1979) "Sound Level Meters" (see N.J.A.C. 7:29-2.12(a)3) or its successor.

- iii. Measurements of sound by octave bands shall be made with a sound level meter with octave band frequency filter set that conforms to the requirements of Class II as specified in ANSI S1.11-1966 (R-1976) "specification for octave, half-octave, and third-octave band filter sets" (see N.J.A.C. 7:29-2.12(a)1).

2. Calibrators used should be those recommended by the manufacturer of the sound level meter.

3. Other equipment:

- i. A wind screen, as recommended by the sound level meter manufacturer.
- ii. A wind speed measuring instrument including a range of five to 15 miles per hour (2.2 to 6.7 meters per second) with plus or minus two miles per hour (plus or minus 0.9 meters per second) accuracy.
- iii. A tape measure or an optical distance indicator for determining distance.
- iv. A compass for determining direction or, alternatively, a suitable map of the vicinity.
- v. A thermometer for determining ambient temperature.
- vi. Optional equipment including a flashlight or miner's lamp, a microphone extension cable, an extension pole with microphone holder, a headphone equipped with a plug to fit the sound level meter.

7:29-2.7 Reporting requirements

(a) Reports shall be provided on forms approved by the Department.

(b) The report for each test shall include:

1. The date and day of the week on which the test is made;
2. The time of measurements, clearly indicating A.M. or P.M.;
3. The times of calibration of the measuring devices while on site;
4. The weather conditions;
5. The temperature when the ambient is below 14 degrees F (-10 degrees C);
6. The wind speed;
7. The identification of all measurement equipment by manufacturer, model number, and serial number;

8. The date each piece of equipment was last recertified or recalibrated by the manufacturer or other approved person;

9. The duty cycle of source of interest;

10. The total sound level in dBA, or dB if in octave bands, or in dBA peak if measuring maximum instantaneous sound pressure level of impulse sound at the measurement point;

11. The neighborhood residual sound level in dBA, or dB if in octave bands, at the measurement point;

12. A sketch of the site, not necessarily to scale, orienting the facility of interest, the points of measurement, topographic features, and relevant distances, containing sufficient information for another investigator to repeat the measurements under similar conditions;

13. A description of the sound sources by character and location;

14. A description of the neighborhood residual sound by character and location, to the extent feasible.

7:29-2.8 Preparation for testing

(a) Survey: Prior to taking noise measurements the investigator shall explore the vicinity of the suspected source on foot to identify any other sound sources which could affect measurements, to establish the approximate location and character of the main sound source, and to select suitable points from which to measure the sound from the suspected source and the neighborhood residual sound.

(b) Nature of sound: While the sound source or sources are under observation the investigator shall ascertain whether the sound is steady state or transient. The duty cycle time, if any, shall be measured and noted.

(c) Wind speed measurement: The investigator shall measure the wind speed at the measurement site with an appropriate wind meter. If the wind speed does not exceed 12 miles per hour (5.4 meters per second), proceed using a sound level meter equipped with a wind screen. When the wind speed exceeds 12 miles per hour (5.4 meters per second), including gusts, sound level readings shall not be made, but shall be postponed until the wind speed decreases below 12 miles per hour (5.4 meters per second).

(d) Instrument selection: After determining the character of the sound to be measured, the investigator shall select the appropriate measuring equipment pursuant to the requirements of N.J.A.C. 7:29-2.6. If the sound is concentrated within a narrow band of frequencies, an instrument capable of octave band analysis shall be selected. If impulse sound is predominant, an instrument capable of impulse peak measurement shall be selected.

7:29-2.9 Procedure

(a) Calibration of Sound Measuring Equipment: When a meter zero adjust screw is accessible from outside the sound measuring equipment, then prior to making sound level measurements, the investigator shall zero adjust in accordance with the manufacturer's instructions. If the zero adjust screw of the equipment is not readily accessible, and if the investigator observes that the meter zero adjust is defective, the equipment shall be taken out of service until repaired. Before and after making a set of sound level measurements, the investigator shall check, and if warranted, adjust the sound level meter calibration at the level specified by the sound level calibrator used. When a multi-frequency calibrator is used, it shall be set for 1000 Hertz. The procedure below shall be followed before and after each set of measurements:

1. Turn on the sound level meter and allow it to warm-up as specified by the manufacturer—usually three to five minutes;

2. Check the condition of the sound level meter battery and replace if necessary;

3. Set the sound level meter range or attenuator setting to the appropriate level (most calibrators produce sound levels in the range of 94 to 124 dB);

4. Set the sound level meter for slow response and set the sound level meter weighting switch to the appropriate position in accordance with the manufacturer's instructions for the sound level calibrator to be used;

5. Test the calibrator batteries and replace them if necessary;

6. Allow the calibrator to warm-up if necessary as specified by the manufacturer;

7. Place the calibrator on the microphone gently to prevent damage to the microphone diaphragm;

8. Adjust the sound level meter using the calibration (sensitivity or amplifier gain) adjustment until the meter reads the calibrator output;

9. If the sound level meter being calibrated is to be used for measuring impulse sound, the following additional steps must be taken:

- i. Switch the detector characteristic setting from "Slow Response" to "Impulse" and note the meter reading. The change must be not more than 0.25 dB.

- ii. Switch the detector characteristic setting from "Impulse" to "Peak". The meter reading must increase by 3.0 plus or minus 0.5 dB.

- iii. If the requirements of either (a)9i or (a)9ii above are not met, no further measurements shall be made with that sound level meter. It shall be taken out of service for repair and recertification.

(b) Measurement: After calibrating the sound level meter, switch to the appropriate weighting position and place the wind screen over the microphone. The appropriate weighting position is "A" for measurement of continuous or impulse sound, and "flat" or "ext. Filter" for octave band measurements. The meter is now ready for measuring the sound level.

1. Total sound level is measured as follows:

i. Position the microphone at the point at which the sound is to be measured.

ii. During sound level measurements, the sound level meter microphone is to be mounted on a tripod or held at arm's length, at a minimum of three feet (0.9 meter) above ground level, and pointed at the proper angle to an imaginary line from the sound source to the microphone. The proper angle is specified by the manufacturer, according to the microphone characteristics.

iii. When measuring continuous sound, the measuring device shall be set for "A" weighting, "slow" meter response, and the range switch shall be set to that range in which the meter needle reads nearest to the maximum end of the scale. When the measured sound is variable, causing the meter needle to fluctuate, record both the minimum and maximum readings, e.g. 66-69 dBA, indicating that the reading was not less than 66 nor more than 69, during the measurement. When selecting the proper range setting for making the measurement, do not include extraneous sounds.

iv. When octave band measurements are made, the sound from the source must be constant in level and in character. Record the maximum and minimum readings in dB. Use "flat" response or "ext. Filter" setting as appropriate to the instrument. (Do not use "A" scale.) If level variations exceed plus or minus 2 dB in the bands containing the principal source frequencies, discontinue the measurement. The octave band level shall be used as a supplement to "A" weighted level measurements.

v. To measure impulse noise, the investigator shall set the meter for "A" weighting, peak hold, and the appropriate range for the needle to be on scale. After measuring an impulse peak, press the reset button to prepare for measurement of the next impulse. If the impulses follow each other rapidly as for example in a fusillade, it is not necessary to measure every impulse. In such a case, measure as many impulses as feasible, estimate the number of impulses occurring, and the time period during which they occur.

vi. While making sound level measurements, observe whether the meter reading is increased by extraneous sound sources such as passing vehicles, aircraft flying overhead, barking dogs, etc. In such cases, postpone the sound level measurement until the extraneous sound has abated. This shall not apply, however, if the

source of the extraneous sound is located on the facility under investigation.

vii. There are instances in which the sound propagation from a source is such that the sound level varies significantly with altitude. In such cases, connect the sound level meter to its microphone by a long cable and, after calibrating, elevate the microphone with a long pole or other means to measure the sound level at different altitudes.

viii. Continue the test over a period of time sufficient to ensure that the sound levels measured are typical of the source under observation but in no event should the duration of the test be less than 10 minutes.

ix. No less frequently than at one hour intervals during the investigation, and again at the conclusion of measurement, calibrate the sound level meter, check the condition of the batteries, measure the wind speed, and record the results for inclusion in the Noise Measurement Report. If the sound level meter has drifted more than 0.5 dB off calibration, or if the sound level meter battery check procedure indicates that the battery charge is too low, or if the wind speed has increased to greater than 12 miles per hour (5.4 meters per second), then measurements taken since the previous calibration check shall be considered invalid. Wind gusts over 12 miles per hour (5.4 meters per second) at this time shall not invalidate measurements since readings would not have been taken during previous gusts.

2. Neighborhood residual sound is measured as follows:

i. When the sound from the source under investigation can be discontinued, the neighborhood residual sound shall be measured at the same location at which the total sound was measured. When the sound under investigation cannot be reasonably discontinued, the neighborhood residual sound may be measured at an alternative location, in accordance with the following procedure:

(1) The alternative location should be as close as feasible to the original sound measurement location, but so located that the sound from the source has as little effect as possible on the neighborhood residual sound measurement. Even if the source sound is audible or is sufficient to raise the sound level above that which would be measured were it inaudible at the alternative location, the reading is sufficient for the purpose of this procedure.

(2) The alternative location chosen must be such that buildings in the vicinity are similar in size and distribution, the local topography is similar in character to the location of the affected property where the total sound was measured.

(3) Traffic conditions at the time of neighborhood residual sound measurement must be similar to those

at the location of the affected property where the total sound was measured.

7:29-2.10 Calculations

(a) Corrected source sound level: Correct the total sound level for the neighborhood residual sound in accordance with the procedure for using Table 1 to determine the sound level from the sound source of interest. If the difference between the total sound level and the neighborhood residual sound level is greater than 10 dB no correction is necessary.

TABLE 1

THE DETERMINATION OF SOURCE SOUND LEVEL FROM TOTAL AND NEIGHBORHOOD RESIDUAL SOUND MEASUREMENTS

A Sound Level Difference (Decibels)	B Correction Factor (Decibels)
0.5	9.6
1	7
2	4
3	3
4	1.8
5	1.6
6	1.2
7	1
8	0.75
9	0.6
10	0.5
Greater than 10	0.0

Procedure for Using Table 1

Step 1: Subtract the maximum measured level of the neighborhood residual sound from the minimum measured level of the total sound.

Step 2: In Column A, find the difference determined under Step 1 and its corresponding correction factor in Column B.

Step 3: Subtract the value obtained from Column B in Step 2 from the minimum measured total sound level (used in Step 1) to determine the sound level attributable to the sound source.

7:29-2.11 Qualifications of investigative personnel

(a) For the purposes of this procedure, persons shall be considered qualified to make noise measurements who have satisfactorily completed any of the following:

1. "Community noise—A Short Course" offered by the Department of Environmental Sciences of Cook College, Rutgers, the State University; or
2. A program of tutoring and on-the-job training offered by the Office of Noise Control to its employees; or
3. Education or experience or a combination thereof certified by the Department as equivalent to the provisions of (a)1 or (a)2 above.

7:29-2.12 Incorporation by reference

(a) Wherever referenced in this subchapter, the following sources are incorporated by reference as part of this subchapter:

1. ANSI:S1.11-1966 (R 1976) "specifications for octave, half-octave and third-octave filter sets" can be purchased from: American National Standards Institute, Inc., 1430 Broadway, New York, New York 10018. Cost: \$5.50.
2. ANSI:S1.4-1971 "specification for sound level meters" can be purchased from: American National Standards Institute, Inc., 1430 Broadway, New York, New York 10018. Cost: \$5.50.
3. "Sound Level Meters" IEC Publication 651 (1979) can be purchased from the Catalogue of International Electrotechnic Commission Publications—1980, 1, Rue de Varembe, Geneva, Switzerland. Approximate Cost: \$48.14.