

**7:27-15.5 Motor vehicle inspections**

(a) The owner of a motor vehicle subject to this section pursuant to N.J.A.C. 7:27-15.2 shall have the motor vehicle periodically inspected in accordance with this section.

(b) The motor vehicle shall be inspected at least once every two years. This biennial inspection shall be deemed an "on-cycle" inspection and shall include an initial inspection, together with any reinspections required pursuant to (h) below. In addition, in accordance with its procedures, the DMV may require the owner of a motor vehicle to have it inspected more frequently than every two years. Such more frequent inspections shall be deemed to be "off-cycle" inspections and shall also include an initial inspection together with any reinspections required pursuant to (h) below.

(c) Initial inspections and reinspections for an on-cycle or an off-cycle inspection shall be performed at either an official inspection facility or at a PIF.

(d) A motor vehicle inspection is not complete until:

1. The motor vehicle passes all of the tests and satisfies all of the requirements, as specified in (f) below, that constitute the emission inspection at an appropriate inspection facility, as specified in (c) above; or

2. The motor vehicle has been issued a waiver in accordance with N.J.A.C. 13:20-43.13.

(e) Initial inspections shall be performed without repair or adjustment, other than proper tightening of the gas cap, at the inspection facility, prior to the inspection.

(f) A motor vehicle inspection shall include the following:

1. A visible smoke test conducted in accordance with N.J.A.C. 7:27B-4.5(a);

2. Unless the motor vehicle is exempt pursuant to N.J.A.C. 7:27-15.6(e) or (f), an exhaust emission test utilizing motor vehicle emission testing equipment approved by the Department. The specific exhaust emission test to be used shall be determined in accordance with (g) below;

3. For all post-1974 model year LDGVs, LDGTs and HDGVs, an emission control apparatus compliance examination conducted in accordance with N.J.A.C. 7:27B-4.9;

4. Twelve months after the EPA's interim approval of the Enhanced I/M State Implementation Plan Revision, for all post-1980 model year LDGVs and LDGTs originally equipped with an evaporative emission control system, an evaporative pressure test utilizing motor vehicle emission testing equipment approved by the Department and conducted in accordance with N.J.A.C. 7:27B-4.10;

5. Twelve months after the EPA's interim approval of the Enhanced I/M State Implementation Plan Revision, for all post-1980 model year LDGVs and LDGTs originally equipped with an evaporative emission control system, an evaporative purge test utilizing motor vehicle emission testing equipment approved by the Department and conducted in accordance with N.J.A.C. 7:27B-4.11, except that those motor vehicles that, in accordance with (g) below, are subject to only the 2500 RPM test as their sole exhaust emission test, shall not be subject to an evaporative purge test;

6. For all LDGVs, LDGTs and HDGVs originally equipped with a sealed fuel filler cap (that is, not a directly vented fuel filler cap), not otherwise subject to an evaporative pressure test pursuant to (f)4, above, a fuel cap leak test utilizing motor vehicle emission testing equipment approved by the Department and conducted in accordance with N.J.A.C. 7:27B-4.13;

7. On and after January 1, 1998, for all post-1995 LDGVs and LDGTs, an on-board diagnostics test conducted in accordance with N.J.A.C. 7:27B-4.12; and

8. For any motor vehicle that is subject to a recall notice issued to the owner on or after January 1, 1995, pursuant to either a "Voluntary Emissions Recall" as defined at 40 C.F.R. section 85.1902(d) or to a remedial plan determination made pursuant to 42 U.S.C.A. section 7541(c), the provision by the owner of the motor vehicle of documentation that all applicable recall repairs have been completed; provided, however, for any recall notice received fewer than 60 days prior to inspection, provision of this documentation may, instead, be provided at the next scheduled vehicle inspection.

NEW JERSEY STATE LIBRARY

(g) The exhaust emission test to be used pursuant to (f)2 above shall be determined as follows:

1. Except as specified in (g)2 and 3 below, the exhaust emission test procedure to be used shall be as follows:

i. For model year 1980 and older motor vehicles, the exhaust emission test procedure to be used shall be the idle test set forth at N.J.A.C. 7:27B-4.5(b);

ii. For model year 1981 and newer motor vehicles, the exhaust emission test procedure to be used 12 months after the EPA's interim approval of the Enhanced I/M State Implementation Plan Revision shall be the ASM5015 test set forth at N.J.A.C. 7:27B-4.7, except that an inspection performed at a PIF may utilize the IM240 test set forth at N.J.A.C. 7:27B-4.8; and

iii. For model year 1981 and newer motor vehicles, the exhaust emission test procedure to be used until 12 months after the EPA's interim approval of the Enhanced I/M State Implementation Plan Revision shall be the idle test set forth at N.J.A.C. 7:27B-4.5(b).

2. Notwithstanding the provision of (g)1 above, if the motor vehicle has a GVWR in excess of 8,500 pounds, the exhaust emission test procedure to be used shall be the idle test set forth at N.J.A.C. 7:27B-4.5(b).

3. Notwithstanding the provision of (g)1 above, if the motor vehicle is any of the following types, the exhaust emission test procedure to be used 12 months after the EPA's interim approval of the Enhanced I/M State Implementation Plan Revision shall be the 2500 RPM test set forth at N.J.A.C. 7:27B-4.6:

i. Motor vehicles of model year 1981 and newer that employ full-time four-wheel drive; or

ii. Low mileage vehicles of model year 1981 and newer.

(h) The owner of a motor vehicle that fails to pass all of the tests that constitute a motor vehicle inspection pursuant to (f) above shall have it reinspected in accordance with every applicable element of (f) within 30 days. Operation of the motor vehicle upon the public roads, streets or highways of the State or any public or quasi-public property in the State shall be prohibited pursuant to N.J.A.C. 7:27-15.3(c) unless, by the 30-day deadline:

1. The motor vehicle passes all of the tests and meets all the requirements that constitute the inspection; or

2. A waiver is issued pursuant to N.J.A.C. 13:20-43.13.

(i) An on-road inspection conducted pursuant to N.J.A.C. 13:20-43.14 may include the following:

1. A visible smoke test conducted in accordance with N.J.A.C. 7:27B-4.5(a);

2. Unless the motor vehicle is exempt pursuant to N.J.A.C. 7:27-15.6(e) or (f), an idle test utilizing motor vehicle emission testing equipment approved by the Department and conducted in accordance with N.J.A.C. 7:27B-4.5(b);

3. For all post-1974 model year LDGVs, LDGTs and HDGVs, an emission control apparatus compliance examination conducted in accordance with N.J.A.C. 7:27B-4.9;

4. Twelve months after the EPA's interim approval of the Enhanced I/M State Implementation Plan Revision, for all post-1980 model year LDGVs and LDGTs originally equipped with an evaporative emission control system, unless the motor vehicle is exempt pursuant to N.J.A.C. 7:27-15.6(e) or (f), an evaporative pressure test utilizing motor vehicle emission testing equipment approved by the Department and conducted in accordance with N.J.A.C. 7:27B-4.10; and

5. Any other tests deemed appropriate by the Director of the DMV that are directed toward detecting acts of tampering with emission control apparatus specifically prohibited at N.J.A.C. 7:27-15.7(a)1 or toward identifying vehicles operated in violation of N.J.A.C. 7:27-15.3(d). Such tests may include visual or functional checks of emission control apparatus and elements of design.

(j) A motor vehicle inspection test using remote sensing techniques shall include the following:

(Reserved)

(k) Any motor vehicle that fails an on-road inspection conducted pursuant to (i) above or a remote sensing test conducted pursuant to (j) above shall be subject to an off-cycle inspection. An off-cycle inspection shall consist of all test procedures and requirements to which a motor vehicle would normally be subject in accordance with (f) above. If the motor vehicle fails the initial off-cycle inspection, the provisions of (h) above apply.

(l) Each year DMV shall conduct a program evaluation test which shall entail additional testing for at least 0.1 percent of those motor vehicles subject to inspection during that year. The motor vehicles subject to the program evaluation testing shall be selected by the DMV in accordance with its procedures. The program evaluation test shall consist of two IM240 tests performed in accordance with N.J.A.C. 7:27B-4.8. The program evaluation test shall be performed after, and in addition to, any other inspection procedures required pursuant to this section. The results of the program evaluation test shall not be used in determining whether a motor vehicle has passed or failed its motor vehicle inspection with regard to exhaust emissions.

Emergency New Rule, R.1995 d.409, effective June 29, 1995 (expires August 28, 1995).

See: 27 N.J.R. 2752(a).

Adopted Concurrent Proposal, R.1995 d.527, effective August 28, 1995, (operative October 27, 1995).

See: 27 N.J.R. 2752(a), 27 N.J.R. 3806(a).  
 Provisions of R.1995 d.409 readopted, with changes effective October 2, 1995.  
 Amended by R.1997 d.56, effective February 3, 1997 (operative March 8, 1997).  
 See: 28 N.J.R. 2298(b), 29 N.J.R. 498(a).  
 Updated model year references and inserted references to HDGVs and to twelve months after EPA interim approval of plan revisions throughout; substantially amended (c); inserted (f)6 and (f)7 and recodified former (f)6 as (f)8; inserted (g)1iii; and substantially amended (g)2.  
 Amended by R.1997 d.283, effective July 7, 1997 (operative August 11, 1997).  
 See: 29 N.J.R. 726(a), 29 N.J.R. 2826(b).  
 Inserted text in (f)7.

**Cross References**

Testing procedures for fuel cap leak test, see N.J.A.C. 7:27B-4.13.

**7:27-15.6 Motor vehicle inspection standards**

(a) Any light-duty gasoline-fueled vehicle, light-duty gasoline-fueled truck or heavy-duty gasoline-fueled vehicle shall not emit visible smoke in the exhaust emissions or in the crankcase emissions for a period in excess of three consecutive seconds when measured using the test procedure established at N.J.A.C. 7:27B-4.5.

(b) Any light-duty gasoline-fueled vehicle, light-duty gasoline-fueled truck or heavy-duty gasoline-fueled vehicle shall not emit carbon monoxide (CO), hydrocarbons (HC), or oxides of nitrogen (NO<sub>x</sub>) in the exhaust emissions in excess of the following standards:

1. If, pursuant to the provisions of N.J.A.C. 7:27-15.5(g), a motor vehicle is tested using the idle test, the motor vehicle shall be subject to the exhaust emission standards set forth in Table 1 below. Compliance with these standards shall be determined in accordance with the inspection test procedure at N.J.A.C. 7:27B-4.5;

**TABLE 1  
 EXHAUST EMISSION STANDARDS  
 FOR THE IDLE TEST  
 LDGVs and LDGTs Powered by Gasoline**

Model Year	CO (% by volume)	HC (ppm as hexane)
Pre-1968	8.5	1400
1968-1970	7.0	700
1971-1974	5.0	500
1975-1980	3.0	300
1981 & Later	1.2	220

LDGVs and LDGTs Powered by a  
 Fuel Other Than Gasoline  
 (Reserved)

HDGVs Powered by Gasoline

Model Year	CO (% by volume)	HC (ppm as hexane)
Pre-1968	8.5	1400
1968-1970	8.5	1200
1971-1974	6.0	700
1975-1978	4.0	500
1979 & Later	3.0	300

**HDGVs Powered by a Fuel Other Than Gasoline**

(Reserved)

2. If, pursuant to the provisions of N.J.A.C. 7:27-15.5(g), a motor vehicle is tested using the 2500 RPM test, the motor vehicle shall be subject to the applicable exhaust emission standards set forth in Table 2 below. Compliance with these standards shall be determined in accordance with the inspection test procedure at N.J.A.C. 7:27B-4.6;

3. If, pursuant to the provisions of N.J.A.C. 7:27-15.5(g), a motor vehicle is tested using the ASM5015 test, the motor vehicle shall be subject to the applicable exhaust emission standards set forth in Table 3 below. Compliance with these standards shall be determined in accordance with the inspection test procedure at N.J.A.C. 7:27B-4.7; or

4. If, pursuant to the provisions of N.J.A.C. 7:27-15.5(g), a motor vehicle is tested using the IM240 test, the motor vehicle shall be subject to the applicable exhaust emission standards set forth in Table 4 below. Compliance with these standards shall be determined in accordance with the inspection test procedure at N.J.A.C. 7:27B-4.8.

**TABLE 2  
 EXHAUST EMISSION STANDARDS  
 FOR THE 2500 RPM TEST  
 LDGVs and LDGTs Powered by Gasoline**

Model Year	CO (% by volume)	HC (ppm as hexane)
1981 & Later	0.5	100

LDGVs and LDGTs Powered by a  
 Fuel Other Than Gasoline  
 (Reserved)

**TABLE 3  
 EXHAUST EMISSION STANDARDS  
 FOR THE ASM5015 TEST  
 LDGVs Powered by Gasoline**

(Effective through December 31, 1999)

Model Years	HC <sup>†</sup>	CO <sup>†</sup>	NO <sub>x</sub> <sup>†</sup>
1981-1982	4	13	19
1983-1990	4	11	19
1991-1995	2	10	18
1994+ Tier 1	1	9	17

<sup>†</sup>The numbers given in this column refer to the appropriate column number in Table 5 below, which contains the actual exhaust emission standards.

**LDGVs Powered by a Fuel other than Gasoline**  
 (Effective through December 31, 1999)  
 (Reserved)

**LDGT1s Powered by Gasoline**  
 (Effective through December 31, 1999)

† The numbers given in this column refer to the appropriate column number in Table 5 below, which contains the actual exhaust emission standards.

<u>Model Years</u>	<u>HC<sup>†</sup></u>	<u>CO<sup>†</sup></u>	<u>NO<sub>x</sub><sup>†</sup></u>
1981-1983	8	16	24
1984-1987	6	15	24
1988-1990	6	15	20
1991-1995	5	13	19
1994+ Tier 1			
(≤3750 LVW)	1	9	17
(>3750 LVW)	2	10	18

LDGT1s Powered by a Fuel other than Gasoline  
(Effective through December 31, 1999)  
(Reserved)

LDGT2s Powered by Gasoline  
(Effective through December 31, 1999)

Model Years	HC†	CO†	NO <sub>x</sub> †
1981-1983	8	16	24
1984-1987	6	15	24
1988-1990	6	15	23
1991-1995	5	13	22
1994 + Tier 1			
(≤5750 LVW)	2	10	18
(>5750 LVW)	5	13	21

† The numbers given in this column refer to the appropriate column number in Table 5 below, which contains the actual exhaust emission standards.

LDGT2s Powered by a Fuel other than Gasoline  
(Effective through December 31, 1999)  
(Reserved)

LDGVs Powered by Gasoline  
(Effective January 1, 2000)

Model Years	HC†	CO†	NO <sub>x</sub> †
1981-1982	1	11	17
1983 +	1	9	17

† The numbers given in this column refer to the appropriate column number in Table 5 below, which contains the actual exhaust emission standards.

LDGVs Powered by a Fuel other than Gasoline  
(Effective January 1, 2000)  
(Reserved)

LDGT1s Powered by Gasoline  
(Effective January 1, 2000)

Model Years	HC†	CO†	NO <sub>x</sub> †
1981-1983	7	14	22
1984-1987	3	12	22
1988-1995	3	12	18
1994 + Tier 1	1	9	17

† The numbers given in this column refer to the appropriate column number in Table 5 below, which contains the actual exhaust emission standards.

LDGT1s Powered by a Fuel other than Gasoline  
(Effective January 1, 2000)  
(Reserved)

LDGT2s Powered by Gasoline  
(Effective January 1, 2000)

Model Years	HC†	CO†	NO <sub>x</sub> †
1981-1983	7	14	22
1984-1987	3	12	22
1988-1995	3	12	20
1994 + Tier 1	1	9	17

† The numbers given in this column refer to the appropriate column number in Table 5, below, which contains the actual exhaust emission standards.

TABLE 4  
EXHAUST EMISSION STANDARDS FOR THE IM240 TEST

LDGVs Powered by Gasoline  
(Effective through December 31, 1999)

Model Years	HC (g/ml)		CO (g/ml)		NO <sub>x</sub> (g/ml)	
	Composite	Phase 2	Composite	Phase 2	Composite	Phase 2
1968-1972	10.0	6.00	150	120	10.0	10.0
1973-1974	10.0	6.00	150	120	9.0	9.0
1975-1976	7.50	5.00	90.0	72.0	9.0	9.0
1977-1979	7.50	5.00	90.0	72.0	6.0	6.0
1980	2.00	1.25	60.0	48.0	6.0	6.0
1981-1982	2.00	1.25	60.0	48.0	3.0	3.0
1983-1990	2.00	1.25	30.0	24.0	3.0	3.0
1991-1995	1.20	0.75	20.0	16.0	2.5	2.5
1994 + Tier 1	0.80	0.50	15.0	12.0	2.0	2.0

LDGVs Powered by a Fuel other than Gasoline  
(Effective through December 31, 1999)  
(Reserved)

LDGT1s Powered by Gasoline  
(Effective through December 31, 1999)

Model Years	HC (g/ml)		CO (g/ml)		NO <sub>x</sub> (g/ml)	
	Composite	Phase 2	Composite	Phase 2	Composite	Phase 2
1968-1972	10.0	6.00	150	120	10.0	10.0
1973-1974	10.0	6.00	150	120	9.0	9.0

Model Years	HC (g/ml)		CO (g/ml)		NO <sub>x</sub> (g/ml)	
	Composite	Phase 2	Composite	Phase 2	Composite	Phase 2
1975-1978	8.00	5.00	120	96.0	9.0	9.0
1979-1983	7.50	5.00	100	80.0	7.0	7.0
1984-1987	3.20	2.00	80.0	64.0	7.0	7.0
1988-1990	3.20	2.00	80.0	64.0	3.5	3.5
1991-1995	2.40	1.50	60.0	48.0	3.0	3.0
1994+ Tier 1						
(LVW ≤ 3750)	0.80	0.50	15.0	12.0	2.0	2.0
(LVW > 3750)	1.00	0.63	20.0	16.0	2.5	2.5

## LDGT1s Powered by a Fuel other than Gasoline

(Effective through December 31, 1999)

(Reserved)

## LDGT2s Powered by Gasoline

(Effective through December 31, 1999)

Model Years	HC (g/ml)		CO (g/ml)		NO <sub>x</sub> (g/ml)	
	Composite	Phase 2	Composite	Phase 2	Composite	Phase 2
1968-1972	10.0	6.00	150	120	10.0	10.0
1973-1974	10.0	6.00	150	120	9.0	9.0
1975-1978	8.00	5.00	120	96.0	9.0	9.0
1979-1983	7.50	5.00	100	80.0	7.0	7.0
1984-1987	3.20	2.00	80.0	64.0	7.0	7.0
1988-1990	3.20	2.00	80.0	64.0	5.0	5.0
1991-1995	2.40	1.50	60.0	48.0	4.5	4.5
1994+ Tier 1						
(LVW ≤ 5750)	1.00	0.63	20.0	16.0	2.5	2.5
(LVW > 5750)	2.40	1.50	60.0	48.0	4.0	4.0

## LDGT2s Powered by a Fuel other than Gasoline

(Effective through December 31, 1999)

(Reserved)

## LDGVs Powered by Gasoline

(Effective January 1, 2000)

Model Years	HC (g/ml)		CO (g/ml)		NO <sub>x</sub> (g/ml)	
	Composite	Phase 2	Composite	Phase 2	Composite	Phase 2
1968-1972	7.00	4.50	120	96.0	7.0	7.0
1973-1974	7.00	4.50	120	96.0	6.0	6.0
1975-1976	3.00	2.00	65.0	52.0	6.0	6.0
1977-1979	3.00	2.00	65.0	52.0	4.0	4.0
1980	0.80	0.50	30.0	24.0	4.0	4.0
1981-1982	0.80	0.50	30.0	24.0	2.0	2.0
1983-1995	0.80	0.50	15.0	12.0	2.0	2.0
1994+ Tier 1	0.60	0.40	10.0	8.0	1.5	1.5

## LDGVs Powered by a Fuel other than Gasoline

(Effective January 1, 2000)

(Reserved)

## LDGT1s Powered by Gasoline

(Effective January 1, 2000)

Model Years	HC (g/ml)		CO (g/ml)		NO <sub>x</sub> (g/ml)	
	Composite	Phase 2	Composite	Phase 2	Composite	Phase 2
1968-1972	7.00	4.50	120	96.0	7.0	7.0
1973-1974	7.00	4.50	120	96.0	6.0	6.0

Model Years	HC (g/ml)		CO (g/ml)		NO <sub>x</sub> (g/ml)	
	Composite	Phase 2	Composite	Phase 2	Composite	Phase 2
1975-1978	4.00	2.50	80.0	64.0	6.0	6.0
1979-1983	3.40	2.00	70.0	56.0	4.5	4.5
1984-1987	1.60	1.00	40.0	32.0	4.5	4.5
1988-1995	1.60	1.00	40.0	32.0	2.5	2.5
1994+ Tier 1						
(LVW≤3750)	0.60	0.40	10.0	8.0	1.5	1.5
(LVW>3750)	0.80	0.50	13.0	10.0	1.8	1.8

LDGT1s Powered by a Fuel other than Gasoline

(Effective January 1, 2000)

(Reserved)

LDGT2s Powered by Gasoline

(Effective January 1, 2000)

Model Years	HC (g/ml)		CO (g/ml)		NO <sub>x</sub> (g/ml)	
	Composite	Phase 2	Composite	Phase 2	Composite	Phase 2
1968-1972	7.00	4.50	120	96.0	7.0	7.0
1973-1974	7.00	4.50	120	96.0	6.0	6.0
1975-1978	4.00	2.50	80.0	64.0	6.0	6.0
1979-1983	3.40	2.00	70.0	56.0	4.5	4.5
1984-1987	1.60	1.00	40.0	32.0	4.5	4.5
1988-1995	1.60	1.00	40.0	32.0	3.5	3.5
1994+ Title 1						
(LVW≤5750)	0.80	0.50	13.0	10.0	1.8	1.8
(LVW>5750)	0.80	0.50	15.0	12.0	2.0	2.0

LDGT2s Powered by a Fuel other than Gasoline

(Effective January 1, 2000)

(Reserved)

TABLE 5

Column numbers	Hydrocarbons (ppm)								Carbon monoxide (%)								Oxides of nitrogen (ppm)							
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
LVW†																								
1750	142	224	257	291	324	390	407	774	0.80	1.26	1.64	2.02	2.78	3.16	3.54	4.31	1212	1819	2272	2725	3178	3631	4084	4990
1875	134	212	243	275	306	368	384	729	0.75	1.19	1.55	1.91	2.63	2.98	3.34	4.06	1142	1713	2181	2649	3117	3586	4054	4990
2000	127	201	230	260	289	348	363	688	0.71	1.13	1.47	1.81	2.48	2.82	3.16	3.83	1077	1616	2058	2499	2941	3383	3824	4778
2125	121	191	219	246	274	329	343	650	0.68	1.07	1.39	1.71	2.35	2.67	2.99	3.63	1018	1527	1944	2360	2776	3192	3609	4578
2250	115	182	208	234	260	312	325	615	0.64	1.02	1.32	1.62	2.23	2.53	2.83	3.44	954	1446	1839	2232	2625	3018	3411	4395
2375	109	173	198	223	247	297	309	583	0.61	0.97	1.26	1.54	2.12	2.40	2.69	3.26	915	1372	1744	2115	2487	2859	3231	4228
2500	105	166	189	212	236	283	294	554	0.59	0.93	1.20	1.47	2.02	2.29	2.56	3.10	889	1304	1657	2009	2361	2714	3066	4076
2625	100	159	181	203	225	270	281	528	0.56	0.89	1.15	1.41	1.92	2.18	2.44	2.96	828	1242	1577	1912	2246	2581	2916	3936
2750	96	152	173	194	216	258	269	503	0.54	0.85	1.10	1.34	1.84	2.09	2.33	2.83	791	1186	1504	1823	2142	2460	2779	3809
2875	92	146	167	187	207	247	257	481	0.52	0.82	1.05	1.29	1.76	2.00	2.23	2.71	756	1134	1438	1742	2046	2350	2654	3669
3000	89	141	160	180	199	237	247	461	0.50	0.79	1.01	1.24	1.69	1.92	2.14	2.60	725	1088	1378	1668	1959	2249	2539	3510
3125	86	136	155	173	191	228	238	443	0.48	0.76	0.98	1.19	1.63	1.84	2.06	2.50	696	1045	1323	1601	1879	2157	2435	3366
3250	83	132	149	167	185	220	229	426	0.46	0.73	0.94	1.15	1.57	1.78	1.99	2.40	670	1006	1273	1539	1806	2073	2340	3234
3375	81	128	145	162	179	213	221	411	0.45	0.71	0.91	1.11	1.52	1.72	1.92	2.32	647	970	1227	1483	1740	1997	2253	3113
3500	78	124	140	157	173	206	214	397	0.44	0.69	0.88	1.08	1.47	1.66	1.88	2.24	625	937	1184	1432	1679	1926	2174	3002
3625	76	120	136	152	168	200	207	384	0.42	0.67	0.86	1.05	1.42	1.61	1.80	2.17	605	907	1146	1384	1623	1862	2100	2900
3750	74	117	133	148	163	194	201	372	0.41	0.65	0.83	1.02	1.38	1.56	1.74	2.11	586	879	1110	1340	1571	1802	2033	2806
3875	72	114	129	144	159	188	195	361	0.40	0.63	0.81	0.99	1.34	1.52	1.69	2.05	569	853	1077	1300	1523	1747	1970	2719
4000	71	112	126	140	155	183	191	351	0.39	0.62	0.79	0.96	1.31	1.48	1.65	1.99	553	829	1046	1262	1479	1695	1912	2638
4125	69	109	123	137	151	179	188	341	0.38	0.60	0.77	0.94	1.27	1.44	1.61	1.94	538	807	1017	1227	1437	1647	1857	2562
4250	67	107	120	134	147	174	181	332	0.37	0.59	0.75	0.92	1.24	1.40	1.56	1.89	524	786	990	1194	1398	1602	1806	2490
4375	66	104	118	131	144	170	177	323	0.36	0.58	0.74	0.89	1.21	1.37	1.53	1.84	510	766	954	1162	1360	1559	1757	2423
4500	65	102	115	128	141	166	172	315	0.36	0.57	0.72	0.87	1.18	1.34	1.49	1.80	498	747	939	1132	1325	1518	1711	2359
4625	63	100	113	125	137	162	169	308	0.35	0.55	0.70	0.85	1.15	1.30	1.46	1.76	486	728	916	1104	1291	1479	1666	2297
4750	62	98	110	122	134	159	165	300	0.34	0.54	0.69	0.84	1.13	1.28	1.42	1.72	474	711	893	1076	1259	1441	1624	2238
4875	61	96	108	120	132	155	161	293	0.34	0.53	0.67	0.82	1.10	1.25	1.39	1.68	463	694	872	1049	1227	1405	1583	2180
5000	60	94	106	117	129	152	157	286	0.33	0.52	0.66	0.80	1.08	1.22	1.36	1.64	452	677	850	1023	1196	1369	1542	2125
5125	58	93	104	115	126	148	154	279	0.32	0.51	0.65	0.78	1.05	1.19	1.33	1.60	441	661	830	998	1167	1335	1503	2070
5250	57	91	102	112	123	145	150	272	0.32	0.50	0.63	0.77	1.03	1.16	1.30	1.56	431	648	810	974	1138	1301	1465	2017
5375	56	89	100	110	121	142	147	266	0.31	0.49	0.62	0.75	1.01	1.14	1.27	1.53	420	631	790	950	1109	1269	1428	1966
5500	55	87	98	108	118	139	144	259	0.30	0.48	0.61	0.73	0.99	1.11	1.24	1.49	410	616	771	926	1082	1237	1392	1916
5625	54	86	96	106	116	136	141	253	0.30	0.47	0.59	0.72	0.97	1.09	1.21	1.46	401	601	752	904	1055	1206	1357	1867
5750	53	84	94	104	113	133	138	247	0.29	0.46	0.58	0.70	0.94	1.07	1.19	1.43	391	587	734	882	1029	1176	1323	1820
5875	52	83	92	102	111	130	135	241	0.29	0.45	0.57	0.69	0.92	1.04	1.16	1.40	383	574	717	860	1004	1147	1290	1774
6000	51	81	90	100	109	127	132	236	0.28	0.44	0.56	0.67	0.91	1.02	1.14	1.37	374	561	701	840	980	1120	1259	1731
6125	50	80	89	98	107	125	129	231	0.28	0.44	0.55	0.66	0.89	1.00	1.11	1.34	366	549	685	822	958	1094	1230	1690
6250	50	79	87	96	105	123	127	226	0.27	0.43	0.54	0.65	0.87	0.98	1.09	1.31	359	538	671	804	937	1070	1203	1653
6375	49	77	86	95	103	120	125	222	0.27	0.42	0.53	0.64	0.86	0.96	1.07	1.29	352	528	658	788	919	1049	1179	1619
6500	48	76	85	93	102	119	123	218	0.26	0.42	0.52	0.63	0.84	0.95	1.06	1.27	346	519	647	775	902	1030	1158	1590
6625	48	76	84	92	101	117	121	215	0.26	0.41	0.52	0.62	0.83	0.94	1.04	1.25	341	512	638	738	889	1014	1140	1565
6750	47	75	83	91	100	116	120	213	0.26	0.41	0.51	0.61	0.82	0.93	1.03	1.24	338	507	631	755	879	1003	1127	1546
6875	47	75	83	91	99	115	119	211	0.26	0.40	0.51	0.61	0.82	0.92	1.02	1.23	335	503	626	749	872	995	1118	1534
7000	47	74	83	91	99	115	119	211	0.25	0.40	0.51	0.61	0.82	0.92	1.02	1.23	335	502	625	747	870	992	1115	1531
7125	47	74	82	90	98	115	119	211	0.25	0.40	0.51	0.61	0.81	0.92	1.02	1.22	335	502	624	747	870	992	1115	1530
7250	47	74	82	90	98	115	119	211	0.25	0.40	0.50	0.61	0.81	0.92	1.02	1.22	335	502	624	747	870	992	1115	1530
7375	47	74	82	90	98	115	119	211	0.25	0.40	0.50	0.61	0.81	0.92	1.02	1.22	335	502	624	747	870	992	1115	1530
7500	47	74	82	90	98	115	119	211	0.25	0.40	0.50	0.61	0.81	0.92	1.02	1.22	335	502	624	747	870	992	1115	1530

†For the purpose of applying these standards, the vehicle's LVW shall be rounded to the nearest 125 pound increment listed in this table.

Note: The emission standards decrease with increasing vehicle weight in order to maintain a constant concentration-based standard for all vehicle weights. This effect is a result of conversion of the standards from a mass measurement to a concentration measurement and accounts for increased displacement from larger engines or a higher RPM from the increased load on smaller engines in heavier vehicles.

(c) A gasoline-fueled motor vehicle which is subject to inspection pursuant to N.J.A.C. 7:27-15.5(a) shall, as a condition of compliance with said inspection, have properly functioning and properly maintained emission control apparatus as determined according to the inspection test procedures established at N.J.A.C. 7:27B-4.9, 4.10, 4.11, 4.12 and 4.13.

(d) Except as provided in (e) and (f) below, the applicability of the standards set forth in this subchapter and of the test procedures set forth at N.J.A.C. 7:27B-4.5, 4.6, 4.7, 4.8, 4.9, 4.10, 4.11, 4.12 and 4.13 to a motor vehicle with an engine other than the engine originally installed by the manufacturer shall be based on the chassis type and model year of the motor vehicle, not on the engine model year.

(e) A motor vehicle that is modified to operate solely on a fuel other than that for which the motor vehicle was originally equipped shall be subject to the test procedures and standards applicable to a motor vehicle of the current fuel type. If the motor vehicle's fuel type after modification is one to which this subchapter does not apply (for example, a gasoline engine replaced with a diesel engine), the motor vehicle shall be exempt from this subchapter. If the motor vehicle's fuel type after modification is a fuel type to which this subchapter applies, but is other than gasoline (for example, a gasoline engine modified to operate solely on natural gas), the standards applicable to that motor vehicle shall be those prescribed in the Tables 1, 2, 3 and 4 above for motor vehicles powered by a fuel other than gasoline. Until such time that applicable exhaust emission standards are promulgated for motor vehicles powered by fuels other than gasoline, such vehicles shall be exempt from exhaust emission testing when operating on a fuel other than gasoline.

(f) A motor vehicle that is modified or manufactured to operate on more than one fuel type shall be subject to exhaust emission standards that apply to the motor vehicle for each fuel type for which the motor vehicle is equipped. Such motor vehicle shall be subject to an exhaust emission test for each fuel type on which it operates and shall comply with all applicable standards for each fuel type. Such motor vehicle shall also be subject to an evaporative pressure test and an evaporative purge test when operating on gasoline. If the motor vehicle is capable of simultaneous operation on more than one fuel type (for example, flexible fuel, gasoline-methanol vehicle), the motor vehicle shall be subject to an exhaust emission test using the fuel mixture in the vehicle at the time of inspection and subject to the exhaust emission standards applicable to vehicles powered by gasoline. When operating on a fuel other than gasoline, the exhaust emission standards applied to a motor vehicle shall be those prescribed in the Tables 1, 2, 3 and 4 above for motor vehicles powered by a fuel other than gasoline. Until such time that applicable exhaust emission standards are promulgated for motor vehicles powered by fuels other than gasoline, such vehicles shall be exempt from exhaust emission testing when operating on a fuel other than gasoline.

(g) The provisions of (d), (e), and (f) above shall not be construed to allow any of the following acts, if such act is prohibited by N.J.A.C. 7:27-15.7:

1. The installation of an engine into a motor vehicle other than the engine originally installed by the manufacturer;
2. The operation of a motor vehicle on a fuel other than that for which the motor vehicle was originally equipped; and
3. The modification of a motor vehicle to operate on more than one fuel type.

As amended, R.1975 d.22, eff. January 31, 1975.

See: 7 N.J.R. 102(b).

As amended, R.1975 d.91, eff. October 1, 1975.

See: 6 N.J.R. 173(a), 7 N.J.R. 206(c).

As amended, R.1975 d.92, eff. April 1, 1975.

See: 7 N.J.R. 206(c).

As amended, R.1976 d.12, eff. January 14, 1976.

See: 8 N.J.R. 62(c).

As amended, R.1977 d.1, eff. January 3, 1977.

See: 9 N.J.R. 77(c).

Amended by R.1985 d.1, effective January 21, 1985 (operative July 1, 1985).

See: 16 N.J.R. 2889, 17 N.J.R. 189(b).

Section substantially amended.

Amended by R.1985 d.331, effective July 1, 1985 (operative December 2, 1985).

See: 17 N.J.R. 781(a), 17 N.J.R. 1649(a).

"past-1984 model year" substituted for "light duty." Added text "weighing less than 8501 pounds."

Emergency recodification from 7:27-15.4 and amendment R.1995 d.409, effective June 29, 1995 (expires August 28, 1995).

See: 27 N.J.R. 2752(a).

Adopted Concurrent Proposal, R.1995 d.527, effective August 28, 1995, except changes upon adoption effective October 2, 1995 (operative October 27, 1995).

See: 27 N.J.R. 2752(a), 27 N.J.R. 3806(a).

Amended by R.1997 d.56, effective February 3, 1997 (operative March 8, 1997).

See: 28 N.J.R. 2298(b), 29 N.J.R. 498(a).

In (b), inserted tables, with amended effective dates, under Table 3, amended effective dates for tables under Table 4, and added Table 5; and in (c) and (d), amended N.J.A.C. references.

### 7:27-15.7 Prohibition of tampering with emission control apparatus

(a) No owner or operator of a gasoline-fueled motor vehicle shall cause, suffer, allow or permit any of the following, unless it is performed in accordance with EPA Memorandum 1A or it is exempt from prohibition by CARB executive order (information on devices or modifications approved by CARB executive order may be obtained from Air Resources Board, Haagen-Smit Laboratory, 9528 Tels-tar Avenue, El Monte, CA 91731-2990):

1. The disconnection, detachment, deactivation, or any other alteration or modification from the design of the original vehicle manufacturer of an element of design installed on any motor vehicle with a certified configuration, except temporarily for the purpose of diagnosis, maintenance, repair or replacement;

2. The operation on the public roads, streets or highways of the State or any public or quasi-public property in the State of any motor vehicle with a certified configuration in which any element of design installed on such vehicle has been disconnected, detached, deactivated, or in any other way altered or modified from the design of the original vehicle manufacturer;

3. The sale, lease, or offer for sale or lease, of any motor vehicle with a certified configuration in which any element of design installed on such vehicle has been disconnected, detached, deactivated, or in any other way altered or modified from the design of the original vehicle manufacturer; or

4. The sale, or offer for sale, of any device or component as an element of design intended for use with, or as part of, any motor vehicle or motor vehicle engine with a certified configuration, which is not designed to duplicate the function and performance of any element of design installed by the original vehicle manufacturer.

New Rule, R.1985 d.1, effective January 21, 1985 (operative July 1, 1985).

See: 16 N.J.R. 2889, 17 N.J.R. 189(b).

New rule. Old rule recodified to 15.7.

Emergency recodification from 7:27-15.5 and amendment R.1995 d.409, effective June 29, 1995 (expires August 28, 1995).

See: 27 N.J.R. 2752(a).

Adopted Concurrent Proposal, R.1995 d.527, effective August 28, 1995 (operative October 27, 1995).

See: 27 N.J.R. 2752(a), 27 N.J.R. 3806(a).

#### 7:27-15.8 Idle standard

(a) No person shall cause, suffer, allow, or permit the engine of a gasoline-fueled motor vehicle to idle for more than three consecutive minutes if the vehicle is not in motion.

(b) The provisions of (a) above shall not apply to:

1. Buses while discharging or picking up passengers;

2. Motor vehicles stopped in a line of traffic;

3. Motor vehicles whose primary and/or secondary power source is utilized in whole or in part for necessary and definitively prescribed mechanical operation other than propulsion, passenger compartment heating or air conditioning;

4. Motor vehicles being or waiting to be examined by State or Federal motor vehicle inspectors;

5. Emergency motor vehicles in an emergency situation;

6. Motor vehicles while being repaired;

7. Motor vehicles while engaged in the process of connection, detachment or exchange of trailers; or

8. Motor vehicles manufactured with a sleeper berth while being used, in a non-residentially zoned area, by the vehicle's operator for sleeping or resting.

Amended by R.1985 d.1, effective January 21, 1985 (operative July 1, 1985).

See: 16 N.J.R. 2889, 17 N.J.R. 189(b).

Rule recodified and substantially amended, to 15.8.

New Rule, R.1985 d.610, effective December 2, 1985 (operative May 5, 1986).

See: 16 N.J.R. 2886(a), 17 N.J.R. 2887(a).

Emergency recodification from 7:27-15.6 and amendment R.1995 d.409, effective June 29, 1995 (expires August 28, 1995).

See: 27 N.J.R. 2752(a).

Adopted concurrent proposal, R.1995 d.527, effective August 28, 1995 (operative October 27, 1995).

See: 27 N.J.R. 2752(a), 27 N.J.R. 3806(a).

#### 7:27-15.9 Non-interference with the motor vehicle codes

Nothing in this subchapter is intended to limit or deny the inspection of motor vehicles in accordance with regulations established pursuant to N.J.S.A. 39:8-2, 39:3-70, 39:3-76, and 39:10-26.

Amended by R.1985 d.1, effective January 21, 1985 (operative July 1, 1985).

See: 16 N.J.R. 2889, 17 N.J.R. 189(b).

Recodified from 15.5; Old (a) deleted and (b)-(c) now (a)-(b).

Emergency recodification from 7:27-15.7 and amendment R.1995 d.409, effective June 29, 1995 (expires August 28, 1995).

See: 27 N.J.R. 2752(a).

Adopted Concurrent Proposal, R.1995 d.527, effective August 28, 1995 (operative October 27, 1995).

See: 27 N.J.R. 2752(a), 27 N.J.R. 3806(a).

## SUBCHAPTER 16. CONTROL AND PROHIBITION OF AIR POLLUTION BY VOLATILE ORGANIC COMPOUNDS

### Subchapter Historical Note

Subchapter 16 was adopted as R.1975 d.377, effective March 1, 1976. See: 7 N.J.R. 47(c), 8 N.J.R. 15(b). The subchapter was amended by R.1979 d.414, effective December 17, 1979. See: 10 N.J.R. 477(b), 11 N.J.R. 544(b). Further amendments were filed as R.1982 d.3, effective February 1, 1982 (operative, March 1, 1982). See: 13 N.J.R. 127(a), 14 N.J.R. 145(b). See section annotations for further rulemaking activity.

### 7:27-16.1 Definitions

The following words and terms, when used in this subchapter, have the following meanings, unless the context clearly indicates otherwise.

“Actual emissions” means the rate at which an air contaminant is actually emitted, either directly or indirectly, to the outdoor atmosphere, in units of mass per calendar year, seasonal period, or other time period specified in this subchapter.

“Agitator” means an apparatus with an external seal used to shake, stir, or mix material in an enclosed vessel.