

CHAPTER 62

MOTOR VEHICLE RACE TRACK RULES

Authority

N.J.S.A. 5:7-8 et seq. and Attorney General's Executive Directive 1982-2.

Source and Effective Date

R.2007 d.79, effective February 6, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Chapter Expiration Date

Chapter 62, Motor Vehicle Race Track Rules, expires on February 6, 2012.

Chapter Historical Note

Chapter 62, Motor Vehicle Race Track Rules, was adopted as R.1990 d.175, effective March 19, 1990. See: 21 N.J.R. 3646(a), 22 N.J.R. 965(a).

Pursuant to Executive Order No. 66(1978), Chapter 62, Motor Vehicle Race Track Rules, was readopted as R.1995 d.206, effective March 17, 1995. As a part of R.1995 d.206, Subchapter 3, Construction Requirements, was repealed and existing Subchapters 4, 5, 6, 7, 10, 11, 13 and 14 were replaced with new rules; Subchapters 6A, 6B, 12A, 12B, 15 and 16 were adopted as new rules, effective April 17, 1995. See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).

Pursuant to Executive Order No. 66(1978), the expiration date for Chapter 62, Motor Vehicle Race Track Rules, was extended by gubernatorial directive from March 17, 2000 to September 22, 2000. See: 32 N.J.R. 1244(a).

Pursuant to Executive Order No. 66(1978), the expiration date for Chapter 62, Motor Vehicle Race Track Rules, was extended by gubernatorial directive from September 30, 2000 to September 30, 2001. See: 32 N.J.R. 3869(c).

Chapter 62, Motor Vehicle Race Track Rules, was readopted as R.2001 d.354, effective August 31, 2001. See: 33 N.J.R. 2250(a), 33 N.J.R. 3451(b).

Chapter 62, Motor Vehicle Race Track Rules, was readopted as R.2007 d.79, effective February 6, 2007. As a part of R.2007 d.79, Subchapter 3, Safety Requirements for Vehicles and Personnel: Road Racing and High Performance Driving Schools, and Subchapter 6C, Motorcycle, Quad Vehicle or Snowmobile Hare Scramble Events, were adopted as new rules, and Subchapter 10, Automobile Enduro Events, was renamed Automobile Enduro Events (Other Than at Licensed Road Course Facilities), effective March 5, 2007. See: Source and Effective Date. See, also, section annotations.

CHAPTER TABLE OF CONTENTS

SUBCHAPTER 1. DEFINITIONS

13:62-1.1 Definitions

SUBCHAPTER 2. MOTOR VEHICLE RACE TRACK LICENSE REQUIREMENTS AND LICENSEE RESPONSIBILITIES: ALL RACING EVENTS

13:62-2.1 License application procedure
13:62-2.2 Licensee's responsibility
13:62-2.3 Restrictions upon licensee
13:62-2.4 Procedures for approval of unspecified events
13:62-2.5 Demonstration events
13:62-2.6 Infield pit areas; inspection
13:62-2.7 Alcoholic beverages and drugs
13:62-2.8 Pit credentials

13:62-2.9 Announcements
13:62-2.10 Monthly reports
13:62-2.11 Accident reports and impounding of certain vehicles
13:62-2.12 Report of deaths to local police
13:62-2.13 Inspection of vehicles
13:62-2.14 Braking system and pedal reserve
13:62-2.15 Refueling
13:62-2.16 Water overflow tanks
13:62-2.17 Security personnel
13:62-2.18 Ambulances; first aid attendant
13:62-2.19 Fire fighting equipment
13:62-2.20 Wreckers

SUBCHAPTER 3. SAFETY REQUIREMENTS FOR VEHICLES AND PERSONNEL: ROAD RACING AND HIGH PERFORMANCE DRIVING SCHOOLS

13:62-3.1 Licensed facilities
13:62-3.2 Construction requirements
13:62-3.3 Fences
13:62-3.4 Flag stations and flagmen
13:62-3.5 Maximum protection
13:62-3.6 Helmets and eye protection
13:62-3.7 Safety belts, shoulder harness and crotch belt
13:62-3.8 Seats
13:62-3.9 Inspection of vehicles
13:62-3.10 Speed limits
13:62-3.11 Clothing requirements; other than drivers
13:62-3.12 Number of persons in vehicle
13:62-3.13 Rollover bars
13:62-3.14 Driver requirement for racing

SUBCHAPTER 4. SAFETY REQUIREMENTS FOR VEHICLES AND PERSONNEL: OVAL RACING

13:62-4.1 Construction requirements
13:62-4.2 Fences
13:62-4.3 Red and amber lights
13:62-4.4 Flagmen
13:62-4.5 Starters
13:62-4.6 Maximum protection
13:62-4.7 Safety belts, shoulder harness and crotch belt
13:62-4.8 Inspection of vehicles
13:62-4.9 Number of persons in vehicle
13:62-4.10 Seats
13:62-4.11 Bumpers
13:62-4.12 Rollover bars
13:62-4.13 Nerfing bars
13:62-4.14 Exhaust system
13:62-4.15 Fire wall and flooring
13:62-4.16 Fuel lines and fuel pumps
13:62-4.17 Fuel tanks
13:62-4.18 Fuel supply shutoff valve
13:62-4.19 Refueling
13:62-4.20 Batteries
13:62-4.21 Braking system and pedal reserve
13:62-4.22 Tires
13:62-4.23 Ignition switch
13:62-4.24 Repairs
13:62-4.25 Drivers
13:62-4.26 Helmets, head cushions and head and neck restraints
13:62-4.27 Goggles or face shield
13:62-4.28 Arm restraints; window nets
13:62-4.29 Transmission safety mats
13:62-4.30 Enclosed drive shaft
13:62-4.31 Water overflow tank
13:62-4.32 Speed limits
13:62-4.33 Licensed facilities

SUBCHAPTER 5. SAFETY REQUIREMENTS FOR VEHICLES AND PERSONNEL: DRAG RACING

13:62-5.1 Construction requirements

- 13:62-5.2 Fences
- 13:62-5.3 Starting tree lights
- 13:62-5.4 Starters
- 13:62-5.5 Maximum protection
- 13:62-5.6 Location
- 13:62-5.7 Vehicle equipment
- 13:62-5.8 Inspection of vehicles
- 13:62-5.9 Number of persons in vehicle
- 13:62-5.10 Seats
- 13:62-5.11 Exhaust system
- 13:62-5.12 through 13:62-5.13 (Reserved)
- 13:62-5.14 Fuel tanks
- 13:62-5.15 Refueling
- 13:62-5.16 Batteries
- 13:62-5.17 Braking system and pedal reserve
- 13:62-5.18 Tires
- 13:62-5.19 Ignition switch
- 13:62-5.20 Repairs
- 13:62-5.21 Drivers
- 13:62-5.22 Helmets, head cushions, and head and neck restraints
- 13:62-5.23 Goggles or face shield
- 13:62-5.24 (Reserved)
- 13:62-5.25 Enclosed drive shaft
- 13:62-5.26 Water overflow tank
- 13:62-5.27 Vehicle lighting
- 13:62-5.28 Vehicles equipped with parachutes
- 13:62-5.29 Exceptions
- 13:62-5.30 Spectator protection
- 13:62-5.31 Pit area fences
- 13:62-5.32 Vehicle positioning
- 13:62-5.33 "Burnouts"
- 13:62-5.34 Speed limits
- 13:62-5.35 Minimum age requirement for a street legal car racing events
- 13:62-5.36 Persons permitted in the pit area
- 13:62-5.37 Vehicles allowed in return road
- 13:62-5.38 Licensed facilities
- 13:62-5.39 Exceptions

SUBCHAPTER 6. MOTORCYCLE AND QUAD VEHICLES RACING EVENTS (OVAL RACING)

- 13:62-6.1 Licensed facilities
- 13:62-6.2 Hubrail construction
- 13:62-6.3 Exceptions
- 13:62-6.4 Fences
- 13:62-6.5 Red and amber lights
- 13:62-6.6 Flagmen
- 13:62-6.7 Starters
- 13:62-6.8 Maximum protection
- 13:62-6.9 Eye protection
- 13:62-6.10 Helmets
- 13:62-6.11 Braking system
- 13:62-6.12 Shutoff device
- 13:62-6.13 Minimum age requirements of motorcycle racing events
- 13:62-6.14 Quad vehicle requirements
- 13:62-6.15 Clothing requirements
- 13:62-6.16 Batteries
- 13:62-6.17 Speed limits
- 13:62-6.18 Pit credentials

SUBCHAPTER 6A. MOTOCROSS AND QUAD VEHICLE RACING EVENTS (SERPENTINE RACING)

- 13:62-6A.1 Licensed facilities
- 13:62-6A.2 Construction requirements
- 13:62-6A.3 Fences
- 13:62-6A.4 Flagmen
- 13:62-6A.5 Starters
- 13:62-6A.6 Additional requirements for motocross events
- 13:62-6A.7 Clothing requirements
- 13:62-6A.8 Helmets
- 13:62-6A.9 Goggles or face shield
- 13:62-6A.10 Batteries

- 13:62-6A.11 Quad vehicle requirements
- 13:62-6A.12 Pit area driving prohibition

SUBCHAPTER 6B. MOTOCROSS ENDURO RACING EVENTS

- 13:62-6B.1 Licensed facilities
- 13:62-6B.2 Construction requirements
- 13:62-6B.3 Areas designated as spectator areas and fences
- 13:62-6B.4 Flagmen
- 13:62-6B.5 Starters
- 13:62-6B.6 Additional guidelines for motocross racing enduro events
- 13:62-6B.7 Clothing requirements
- 13:62-6B.8 Helmets
- 13:62-6B.9 Goggles or face shield
- 13:62-6B.10 Batteries
- 13:62-6B.11 Pit area driving prohibition

SUBCHAPTER 6C. MOTORCYCLE, QUAD VEHICLE OR SNOWMOBILE HARE SCRAMBLE EVENTS

- 13:62-6C.1 Licensed facilities
- 13:62-6C.2 Design and construction requirements
- 13:62-6C.3 Spectator area
- 13:62-6C.4 Starters, flagmen and course marshals
- 13:62-6C.5 Participants

SUBCHAPTER 7. SNOWMOBILE EVENTS

- 13:62-7.1 Track construction
- 13:62-7.2 Fences
- 13:62-7.3 Red and amber lights
- 13:62-7.4 Flagmen
- 13:62-7.5 Starters
- 13:62-7.6 Maximum protection
- 13:62-7.7 Safety requirements; vehicles and personnel
- 13:62-7.8 Exhaust system
- 13:62-7.9 Snow flaps
- 13:62-7.10 Shutoff device
- 13:62-7.11 Engine and transmission shielding
- 13:62-7.12 Batteries
- 13:62-7.13 Speed limits
- 13:62-7.14 Licensed facilities

SUBCHAPTER 8. GO-KART EVENTS

- 13:62-8.1 Licensed facilities
- 13:62-8.2 Track construction
- 13:62-8.3 Safety requirements
- 13:62-8.4 Clothing requirements for all go-kart events
- 13:62-8.5 Pit area operation prohibition
- 13:62-8.6 through 13:62-8.7 (Reserved)

SUBCHAPTER 9. DEMOLITION DERBY AND TRACTOR PULLS

- 13:62-9.1 Demolition derby vehicles
- 13:62-9.2 Demolition derby participants
- 13:62-9.3 Goggles or face shield
- 13:62-9.4 Clothing requirements
- 13:62-9.5 Demolition derby exhibition area
- 13:62-9.6 Demolition derby tow vehicles
- 13:62-9.7 Tractor pull age requirement
- 13:62-9.8 Tractor pull kill switch requirement
- 13:62-9.9 Speed limits
- 13:62-9.10 Licensed facilities

SUBCHAPTER 10. AUTOMOBILE ENDURO EVENTS (OTHER THAN AT LICENSED ROAD COURSE FACILITIES)

- 13:62-10.1 Construction requirements
- 13:62-10.2 Fences
- 13:62-10.3 Red and amber lights

- 13:62-10.4 Flagmen
- 13:62-10.5 Starters
- 13:62-10.6 Maximum protection
- 13:62-10.7 Driver and vehicle requirements
- 13:62-10.8 Windshield
- 13:62-10.9 Mirrors
- 13:62-10.10 Vehicle interior and exterior requirements
- 13:62-10.11 Tires
- 13:62-10.12 Fuel tanks
- 13:62-10.13 Fuel lines
- 13:62-10.14 Engine and suspension requirements
- 13:62-10.15 Seat belts
- 13:62-10.16 Bumpers
- 13:62-10.17 Batteries
- 13:62-10.18 Seats
- 13:62-10.19 Rollover cage
- 13:62-10.20 Miscellaneous equipment requirements
- 13:62-10.21 Additional track responsibilities
- 13:62-10.22 Speed limits
- 13:62-10.23 Licensed facilities

SUBCHAPTER 11. MUD HOP

- 13:62-11.1 Construction requirements
- 13:62-11.2 Fences
- 13:62-11.3 Red and amber lights
- 13:62-11.4 Flagmen
- 13:62-11.5 Starters
- 13:62-11.6 Maximum protection
- 13:62-11.7 Licensed facilities
- 13:62-11.8 Alcohol/controlled dangerous substances prohibited
- 13:62-11.9 Driver requirements
- 13:62-11.10 Equipment requirements
- 13:62-11.11 Windows
- 13:62-11.12 Vehicle interior and exterior requirements
- 13:62-11.13 Seat belts
- 13:62-11.14 Rollover cage
- 13:62-11.15 Bumpers
- 13:62-11.16 Batteries
- 13:62-11.17 Miscellaneous equipment requirements
- 13:62-11.18 Braking system and pedal reserve
- 13:62-11.19 Automatic transmission safety mats
- 13:62-11.20 Seats
- 13:62-11.21 Additional track responsibilities
- 13:62-11.22 Speed limits
- 13:62-11.23 Licensed facilities

SUBCHAPTER 12. REACTION POWER VEHICLES, THRILL SHOWS AND GYMKHANAS

- 13:62-12.1 Licensed facilities
- 13:62-12.2 Vehicle equipment

SUBCHAPTER 12A. QUARTER MIDGETS EVENTS

- 13:62-12A.1 Licensed facilities
- 13:62-12A.2 Track construction
- 13:62-12A.3 Safety requirements
- 13:62-12A.4 Speed limits for all quarter midget events; pit area operation prohibition

SUBCHAPTER 12B. JUNIOR DRAG RACING EVENTS

- 13:62-12B.1 Licensed facilities
- 13:62-12B.2 Construction requirements
- 13:62-12B.3 Fences
- 13:62-12B.4 Starting tree lights
- 13:62-12B.5 Starters
- 13:62-12B.6 Maximum protection
- 13:62-12B.7 Location
- 13:62-12B.8 Vehicle equipment and driver requirements
- 13:62-12B.9 Pit area operation

SUBCHAPTER 13. ADVISORY COMMITTEE

- 13:62-13.1 Appointment of advisory committee

SUBCHAPTER 14. SPECIAL AGE PROVISION

- 13:62-14.1 Participant requirements
- 13:62-14.2 Licensee responsibilities

SUBCHAPTER 15. ACTIONS FOR VIOLATION(S)

- 13:62-15.1 Actions for violations

SUBCHAPTER 16. APPEALS OF ADMINISTRATIVE ACTION

- 13:62-16.1 Hearings

SUBCHAPTER 1. DEFINITIONS

13:62-1.1 Definitions

The following words and terms, when used in this chapter, shall have the following meanings, unless the context clearly indicates otherwise.

“Acceleration and performance tests” means a straightaway race against time or another vehicle, including acceleration and deceleration.

“Ambulance” means a motor vehicle certified to provide emergency medical services pursuant to the New Jersey Highway Traffic Safety Act of 1987, N.J.S.A. 27:5F-18 et seq., and the New Jersey Medical Assistance Health Services Act, N.J.S.A. 30:4D-6.2 et seq.

“Driving school” means any instructional program or business for high performance driving or racing offered by an instructor or instructors who are recognized as such by a sanctioning organization or within the racing industry.

“Enduro event” means an oval race in which the winner is determined by the leading car at the expiration of a determined time or number of laps.

“Flag station” means any protected station along a race track from which flagmen can observe track activity and signal other track officials and participants.

“Go-kart” means a small four-wheel vehicle consisting of a frame, seat, one or more engines mounted to the rear or side of the driver’s seat, steering mechanism and a braking system, and having no spring suspension system.

“Go-kart racing event” means a race involving vehicles commonly known as go-karts as defined in this chapter, either on a circular or oval track or on a road course involving curves, chicanes or other track characteristics to simulate varied road conditions.

“Jersey bar” means a vertical component of the roll cage extending from the left side of a quarter midget race car.

“Junior dragster” means a competition vehicle that is scaled down to half the size and is a near replica of a professional dragster utilizing a lawn mower engine. The compet-

itor will utilize $\frac{1}{8}$ of the track surface and driven by children between the ages of 8-17.

“Lapping days” means organized, non-competitive, instructional driving programs where passing is only permitted in designated areas of the race track.

“Motorcycle special events” means motorcrosses, scrambles and other events utilizing open road courses.

“Mud hops” means an event exhibiting driving skill in which the winner is determined by distance or time on a mud obstacle course.

“Pit area” means that portion of a racing location where vehicles are serviced, repaired, or refueled during a racing event.

“Quad” means a four-wheeled version of an all-terrain vehicle (ATV), described as a small open motorized vehicle designed for off-road use. ATVs are also considered off highway vehicles (OHV) or off road vehicles (ORV).

“Quarter midgets” means a competition vehicle scaled down to one-fourth the size of midget racers powered by a lawn mower engine and driven by children ages 5-16.

“Race practice” means any event when the race track is used for the purpose of testing or tuning race vehicles, learning the race track, or practicing for a race, multiple vehicles may occupy the race track at the same time and passing is permitted under the same conditions as a race.

“Racing event” means a motor vehicle race or exhibition of driving skill, including that time period prior to the actual race or exhibition, as well as the time period during the race or exhibition and until the conclusion of the race or exhibition wherein all competing vehicles have been removed from the racing surface.

“Reaction powered vehicles” means vehicles powered by jet or rocket engines.

“Road course” means a race track which incorporates a series of both left- and right-hand turns with or without banking and may also contain changes in elevation.

“Road race” means all motor vehicle racing which occurs on a road course.

“Sanctioning organization” means a regional, national, or international organization, which regularly organizes and operates promotional and touring events, time trials, driving schools, or lapping days. Such organizations have established and accepted guidelines for the operation of these events.

“Snowmobile” means an engine driven motor vehicle designed primarily to travel over ice or snow of a type that uses sled type runners, skis, continuous belt trend, cleats or any combination of these similar means of contact with the surface upon which it is operated.

“Snowmobile racing event” means a race involving vehicles commonly known as snowmobiles as defined in this chapter on a circular or oval track, a road course involving curves, chicanes, or a straightaway race against time or other snowmobiles.

“Staging area” means that portion of a racing location where vehicles are lined up in preparation for entering the acceleration and performance test area.

“Street legal car” means a car intended for the use on public roadways and highways of this State and able to pass all of the requirements for motor vehicle inspection as described under Title 39 of the New Jersey Motor Vehicle and Traffic Laws.

“Superintendent” means the Superintendent of the Division of State Police.

“Thrill shows” means events specifically designed to demonstrate driving skill including, but not limited to, ramp jumps and events requiring the intentional crashing or crushing of participating vehicles.

“Time trials” means events conducted for the purpose of competition through individually timed runs or laps although multiple vehicles may be on the race track at the same time.

“Trained first aid attendant” means a person certified as an emergency medical technician to provide emergency medical services pursuant to the New Jersey Highway Traffic Safety Act of 1987, N.J.S.A. 27:5F-18 et seq. and the New Jersey Medical Assistance Health Services Act, N.J.S.A. 30:4D-6.2 et seq.

Amended by R.1995 d.206, effective April 17, 1995.

See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).

Amended by R.2001 d.354, effective October 1, 2001.

See: 33 N.J.R. 2250(a), 33 N.J.R. 3451(b).

In “Go-karts”, substituted “karts” for “carts” and inserted “or side” following “the rear”; in “Go-kart racing event”, substituted references to karts for references to carts throughout.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Section was “Words and phrases defined”. Added definitions “Driving school”, “Flag Station”, “Jersey bar”, “Lapping days”, “Quad”, “Race practice”, “Road course”, “Road race”, “Sanctioning organization”, and “Time trials”.

SUBCHAPTER 2. MOTOR VEHICLE RACE TRACK LICENSE REQUIREMENTS AND LICENSEE RESPONSIBILITIES: ALL RACING EVENTS

13:62-2.1 License application procedure

(a) A license shall be required for any operation or conduct of motor vehicle races and exhibitions of motor vehicle driving and the tracks or places at which the same are operated and conducted. The application for a motor vehicle race track license must be submitted at least 90 days prior to the first day of racing or exhibition. An application for renewal of a

license shall be submitted within 60 days of the expiration date of the license and is to be accompanied by:

1. An insurance certificate;

i. N.J.S.A. 5:7-13 states that no license shall be issued for the holding of any motor vehicle race or exhibition of motor vehicle driving skill until the person applying for the license shall have filed with the Department evidence satisfactory to it of the issuance of an insurance policy approved by the department and conditioned, in the case of a race or exhibition at a track or other place accommodating less than one thousand people, for the payment of less than \$25,000 to any one person obtaining judgment, and not less than \$50,000 on all judgments recovered, and for the payment of not less than \$50,000 to any one person obtaining judgment, and not less than \$100,000 on all judgments recovered, in the case of all other races or exhibitions, upon a claim or claims arising out of the same transaction, connected with the same subject of action (to be apportioned ratably among judgment creditors according to the amount of their respective judgments) for damages because of bodily injury, including death at any time resulting therefrom, caused to any person or persons, other than the driver, and all pit area personnel as the result of an accident occurring as a result of the conduct of any motor vehicle race or exhibition of motor vehicle driving skill, for which the license is granted, under which policy the liability of the company shall become absolute when loss or damage covered by the policy occurs, and satisfaction by the insured of a final judgment for the loss or damage shall not be a condition precedent to the right or duty of said company to make payment on account of the loss or damage and which policy shall not be cancelable or annulled as to any loss or damage by an agreement between the carrier and the insured after the insured has become responsible for the loss or damage or in any other event, except on 10 days prior notice to the Department;

2. A duplicate of the insurance policy;

i. The policy shall be issued by a company approved by the Superintendent;

ii. The policy and the certificate are to contain a statement to the effect that they are noncancellable except upon 30 days prior written notice to the Superintendent;

3. A certified check or postal money order in the amount prescribed by law as the license fee;

4. A certification from the building inspector of the municipality where the track is located to the effect that he has inspected the spectator seats and found them safe for use. Where the municipality does not have a building inspector, or a building code, a certification from a New Jersey State licensed structural engineer may be accepted; and

5. A sketch or sketches of the track and associated areas, as near to scale as practicable, indicating the location of required safety features such as hub rails, fences, light or flagman positions, spectator seating, entrances and exits, pit facility locations and other physical factors affecting the safety of spectators and participants. This requirement shall not apply to locations licensed prior to January 1, 1963, unless alterations are made to the track and associated areas on or after January 1, 1963.

Amended by R.1995 d.206, effective April 17, 1995.
See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).

13:62-2.2 Licensee's responsibility

The licensee is responsible for any violations of N.J.S.A. 5:7-8 et seq. or any of the provisions of this chapter.

13:62-2.3 Restrictions upon licensee

(a) The Superintendent may impose reasonable restrictions upon any licensee and may waive application of any rules in the interest of safety in his or her discretion, on a case-by-case basis for a specific event or for the facility generally.

(b) The restrictions may include, but shall not be limited to:

1. Requirements for special protective devices for the participants in, or spectators attending, any race or exhibition; and/or

2. Limitations concerning spectator areas; and/or

3. Limitations concerning types of events and classes of vehicles; and/or

4. Requirements for the protection of participants and spectators.

(c) The licensee will comply with any special restriction imposed by the Superintendent after receiving written notice thereof from the Superintendent.

(d) The licensee may refuse participation by any driver, crew member, or spectator for any cause that the licensee deems unsafe to other drivers or spectators or otherwise unsportsmanlike. The licensee shall ensure that all drivers perform in a manner consistent with the necessary skills of their respective division.

1. The licensee may also impose any restrictions reasonably necessary to ensure the safety of the event.

(e) The licensee may refuse entry to any spectator whom the licensee reasonably deems may adversely effect the safe operation of the facility.

(f) The licensee shall maintain evidence proving the age and written consent of a parent or legal guardian of all participating drivers under the age of 18 on premises and available for inspection.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Rewrote (a); and added (d) through (f).

13:62-2.4 Procedures for approval of unspecified events

(a) When a licensee requests for approval to conduct a racing event as defined herein which is not specifically addressed by these rules, the licensee shall apply to the Superintendent for approval for the conduct of said event. Approval shall not be granted unless the Superintendent is satisfied that:

1. The request for an approval was made in writing to the Superintendent at least 20 days prior to the racing event;
2. The request contains a sufficient description of the event; and
3. The approval will not adversely affect the safety of the public or participants at a racing event.

13:62-2.5 Demonstration events

(a) Licensees may apply in writing to the Superintendent for permission to suspend application of a specific rule or rules applicable to an event and to conduct such event under a modified rule or rules for the purpose of evaluation.

(b) The request for modification shall be submitted at least 60 days in advance of the first scheduled event and shall include a complete description of the event or events to be conducted, a citation to the rule or rules for which modification is requested, the modified rule or rules for which approval is requested, a statement of the purpose of the modification, and a schedule of events to be conducted under the modified rule.

(c) The Superintendent shall approve the request as submitted, or approve the request subject to conditions, or deny the request based upon an evaluation of the potential impact of the modification on the safety of spectators and participants. Only the licensee submitting the request shall conduct events in accordance with an approved modified or suspended rule.

(d) A request for approval of a demonstration event may be submitted in connection with a petition for rulemaking pursuant to N.J.S.A. 52:14B-4(f).

New Rule, R.1998 d.354, effective July 20, 1998.

See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

Former N.J.A.C. 13:62-2.5, Infield pit areas; inspection, was recodified to N.J.A.C. 13:62-2.6.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

In (b), substituted "60" for "20".

13:62-2.6 Infield pit areas; inspection

(a) Tracks having the pit area in the infield of a substantially circular or oval track will be subject to special in-

spection to determine whether arrangements are sufficient to provide reasonable protection for pit area personnel.

(b) Such inspection will be made following application to the Superintendent which shall be filed in conjunction with the application for the race track license.

Recodified from N.J.A.C. 13:62-2.5 by R.1998 d.354, effective July 20, 1998.

See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

Former N.J.A.C. 13:62-2.6, Alcoholic beverages and drugs, was recodified to N.J.A.C. 13:62-2.7.

13:62-2.7 Alcoholic beverages and drugs

(a) No alcoholic beverages, nor narcotic, hallucinogenic or habit producing drugs will be permitted on the race track proper, the pit area, or any other area having unrestricted access to the race track proper. No person who has partaken of any alcoholic beverage or narcotic, hallucinogenic or habit producing drug in any amount whatsoever shall participate in any race or exhibition of driving skill, or perform any duties in the pit or pit area.

(b) Any vehicle containing alcoholic beverages or narcotic, hallucinogenic or habit producing drugs, and any person found to have partaken of alcoholic beverages or narcotic, hallucinogenic or habit producing drugs shall be removed from the pit area as soon as is practicable and shall be prohibited from returning to the pit area.

(c) No person who has been convicted of the use or possession of a controlled dangerous substance, as provided in the Comprehensive Drug Reform Act of 1986, N.J.S.A. 2C:35-1 et seq., shall be permitted to enter into a pit area for a period of one year from the date of conviction.

Recodified from N.J.A.C. 13:62-2.6 by R.1998 d.354, effective July 20, 1998.

See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

Former N.J.A.C. 13:62-2.7, Pit credentials, was recodified to N.J.A.C. 13:62-2.8.

13:62-2.8 Pit credentials

(a) During racing events, the track management, or a sanctioning organization, shall be responsible for the issuance of pit credentials. If pit credentials are issued by a sanctioning organization, the design and distribution of the pit credentials must be approved in advance by track management to ensure compliance with this chapter.

(b) Only persons holding pit credentials shall be admitted to the pit area or racing area.

(c) Reporters and photographers of the working press in possession of valid pit credentials shall be limited to safe areas.

(d) The issuance of pit credentials shall be limited to:

1. Participating pit crew members age 16 and above, with a maximum of eight, which includes the driver;

2. Drivers having cars entered in one of the events in the race;

3. Members of the track staff having business in the pit area;

4. Race officials; and

5. Accredited photographers and reporters of the working press.

(e) The track management shall be responsible for the checking of credentials of persons entering the pit area to determine that no person shall enter the pit area or engage in a race or exhibition unless such person shall produce credentials showing age which satisfies the age requirement for a particular event. For 16 year olds, a photo drivers license or other valid photo identification and a copy of the birth certificate shall be produced.

(f) The licensee or the Superintendent may require a person to produce satisfactory evidence attesting to said person's physical and mental well-being as a prerequisite to obtaining permission to enter the pit area. Such evidence shall be on a form signed by a New Jersey licensed physician.

(g) No one is permitted in the staging lanes or track surface without proper credentials.

(h) Flagmen and starters at all racing events shall be at least 17 years of age.

(i) Mechanics must wear pants while working on their respective vehicles.

(j) Drivers are not permitted to wear shorts while competing.

(k) Track staff shall wear pants, at all times, while working in a race or practice event.

(l) Track staff shall wear brightly colored safety vests to be easily identified, or other identifying uniforms, while working a race or practice event.

(m) No one under the age of 17 or without a valid driver's license shall operate any motor vehicle in or on the facility during a racing event, unless otherwise specified in this chapter.

Amended by R.1995 d.206, effective April 17, 1995.

See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).

Recodified from N.J.A.C. 13:62-2.7 by R.1998 d.354, effective July 20, 1998.

See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

Former N.J.A.C. 13:62-2.8, Announcements, was recodified to N.J.A.C. 13:62-2.9.

Amended by R.2001 d.354, effective October 1, 2001.

See: 33 N.J.R. 2250(a), 33 N.J.R. 3451(b).

Rewrote (d)1; in (e), added the last sentence; in (g), substituted "17" for "18".

Amended by R.2003 d.374, effective September 15, 2003.

See: 35 N.J.R. 2569(a), 35 N.J.R. 4294(a).

In (d)1 and (e), substituted "16" for "17"; in (g), substituted "16" for "17" and deleted "pit area" preceding "staging lanes".

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Rewrote (a); in (g), substituted "is" for "under the age of 16 is to be" and inserted "without proper credentials" at the end; in (h), substituted "17" for "18"; in (k), substituted "shall" for "will" and inserted "or practice"; and added (l) and (m).

13:62-2.9 Announcements

(a) The licensee shall be responsible to make a suitable announcement over the public address system in the pit area, advising the public and pit personnel of the following:

1. The minimum age of persons permitted in the pit area;
2. The prohibition against smoking in the area where fuel is stored or refueling of vehicles takes place;
3. The prohibition against the use of alcoholic beverages in the pit area;
4. The prohibition against the use of narcotic, hallucinogenic or habit producing drugs in the pit area; and
5. The speed limit of five miles per hour in the pit area.

(b) The announcement is to be made approximately 15 minutes before the start of the day's program and twice during the program.

(c) The licensee shall post a sign at all entrances to the pit area advising authorized persons in the pit area of the following:

1. The minimum age of persons permitted in the pit area;
2. The prohibition against the possession or use of alcoholic beverages or narcotic, hallucinogenic or habit producing drugs in the pit area; and
3. The prohibition against smoking in areas where fuel is stored or refueling of vehicles takes place; and
4. The speed limit of five miles per hour in the pit area.

Recodified from N.J.A.C. 13:62-2.8 by R.1998 d.354, effective July 20, 1998.

See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

Former N.J.A.C. 13:62-2.9, Monthly reports, was recodified to N.J.A.C. 13:62-2.10.

Amended by R.2001 d.354, effective October 1, 2001.

See: 33 N.J.R. 2250(a), 33 N.J.R. 3451(b).

Added (a)5 and (c)4.

13:62-2.10 Monthly reports

The licensee shall file with the Superintendent a monthly report on the form approved and provided by the Superintendent. This report shall include the date of racing events held in the reported month, the type of event, the attendance, the number of vehicles as well as an account of any other unusual incidents occurring at the track during the reporting period. The report shall further include the monthly schedule of events.

Recodified from N.J.A.C. 13:62-2.9 by R.1998 d.354, effective July 20, 1998.

See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

Former N.J.A.C. 13:62-2.10, Accident reports and impounding of certain vehicles, was recodified to N.J.A.C. 13:62-2.11.

13:62-2.11 Accident reports and impounding of certain vehicles

(a) Accidents involving injury or death must be reported to the office of the Superintendent, by telephone, no later than the first business day following the accident.

(b) Such a report must be followed within 48 hours by a complete written report of the accident.

(c) Any vehicle which is involved in a crash resulting in serious or fatal injuries to a driver or spectators thereof shall be impounded by the licensee and detained until such time as an inspection of the vehicle may be made by a representative of the Superintendent.

Recodified from N.J.A.C. 13:62-2.10 by R.1998 d.354, effective July 20, 1998.

See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

Former N.J.A.C. 13:62-2.11, Report of deaths to local police, was recodified to N.J.A.C. 13:62-2.12.

13:62-2.12 Report of deaths to local police

In addition to the reports to the Superintendent, the licensee shall report any accident resulting in a fatality to the police agency having jurisdiction by the quickest means available.

Recodified from N.J.A.C. 13:62-2.11 by R.1998 d.354, effective July 20, 1998.

See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

Former N.J.A.C. 13:62-2.12, Inspection of vehicles, was recodified to N.J.A.C. 13:62-2.13.

13:62-2.13 Inspection of vehicles

(a) The licensee shall arrange for the inspection of each participating vehicle prior to the event, to determine that it meets the requirements of this chapter. Vehicles not meeting the requirements set forth for the specified event shall be barred by the licensee from participation or practice.

(b) Vehicles which are to be used in automobile races or exhibitions of driving skill are subject to unannounced inspection and approval at any time by the Superintendent or designee.

Recodified from N.J.A.C. 13:62-2.12 by R.1998 d.354, effective July 20, 1998.

See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

Former N.J.A.C. 13:62-2.13, Braking system and pedal reserve, was recodified to N.J.A.C. 13:62-2.14.

13:62-2.14 Braking system and pedal reserve

(a) The licensee will be required to test and approve each race car for pedal reserve before the car leaves the pit area to enter the track.

(b) The licensee shall not permit any vehicle to participate in any race or exhibition if the braking system includes the direct application of pressure to any of the tires or with any apparent deficiency.

Recodified from N.J.A.C. 13:62-2.13 by R.1998 d.354, effective July 20, 1998.

See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

Former N.J.A.C. 13:62-2.14, Refueling, was recodified to N.J.A.C. 13:62-2.15.

13:62-2.15 Refueling

(a) In all instances where refueling is permitted with the engine running, the licensee shall insure that a member of the pit crew equipped with an approved type fire extinguisher be in close proximity to the fill pipe of the fuel tank.

(b) The licensee shall not permit smoking in any area where fuel is being transferred or stored.

(c) The licensee shall not permit the use of welding and acetylene torches in any area where fuel is being transferred or stored unless a fully charged fire extinguisher is in close proximity.

Recodified from N.J.A.C. 13:62-2.14 by R.1998 d.354, effective July 20, 1998.

See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

Former N.J.A.C. 13:62-2.15, Water overflow tanks, was recodified to N.J.A.C. 13:62-2.16.

13:62-2.16 Water overflow tanks

The licensee shall not permit water overflow tanks or reservoirs to be installed inside the driver compartment. Tanks or reservoirs mounted in the roll cage must be fully shielded to protect the driver.

Recodified from N.J.A.C. 13:62-2.15 by R.1998 d.354, effective July 20, 1998.

See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

Former N.J.A.C. 13:62-2.16, Security personnel, was recodified to N.J.A.C. 13:62-2.17.

13:62-2.17 Security personnel

(a) The licensee shall furnish sufficient security protection to maintain peace and good order.

(b) Guard personnel will be furnished by the licensee at each unlocked gateway between the spectator areas and the track and/or pit areas.

(c) Guard personnel will be furnished by the licensee at each unlocked gateway between the pit area and the track area.

Recodified from N.J.A.C. 13:62-2.16 by R.1998 d.354, effective July 20, 1998.

See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

Former N.J.A.C. 13:62-2.17, Ambulances; first aid attendant, was recodified to N.J.A.C. 13:62-2.18.

13:62-2.18 Ambulances; first aid attendant

(a) The licensee shall not permit any race, practice, or exhibition of driving skill unless there is available for immediate use at the licensed location at least one vehicle suitable for ambulance purposes, together with two trained first aid attendants.

(b) The licensee shall ensure that a driver of any racing event involved in an accident which results in considerable damage to the vehicle or any noticeable injury to the driver is checked by the first aid attendant(s) on duty and cleared to participate before he/she returns to the racing event.

1. If the driver refuses medical attention, he or she must sign a waiver stating so.
2. The licensee shall not allow the driver to re-enter the race event if the driver refuses to sign the medical waiver or medical attention is recommended.

Amended by R.1995 d.206, effective April 17, 1995.
 See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).
 Recodified from N.J.A.C. 13:62-2.17 by R.1998 d.354, effective July 20, 1998.
 See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).
 Former N.J.A.C. 13:62-2.18, Fire fighting equipment, was recodified to N.J.A.C. 13:62-2.19.
 Amended by R.2007 d.79, effective March 5, 2007.
 See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).
 In (a), inserted “, practice.”

13:62-2.19 Fire fighting equipment

(a) The licensee shall not permit any race, practice, or exhibition of driving skill to be conducted unless there is available at suitable locations around the track Class B Underwriter labeled approved fire extinguishers.

(b) All extinguishers shall be fully charged at the beginning of each day's activities.

(c) The licensee shall check all extinguishers at least once a year and carry a label to show the date of inspection.

(d) In addition there shall be a reserve consisting of a recognized paid or voluntary fire company with their equipment or at least 350 pounds of dry chemical available to move to the scene of any major fire.

Recodified from N.J.A.C. 13:62-2.18 by R.1998 d.354, effective July 20, 1998.
 See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).
 Former N.J.A.C. 13:62-2.19, Wreckers, was recodified to N.J.A.C. 13:62-2.20.
 Amended by R.2007 d.79, effective March 5, 2007.
 See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).
 In (a), inserted “, practice.”

13:62-2.20 Wreckers

(a) The licensee shall permit only authorized personnel to ride on any wrecker.

(b) No person shall be permitted to ride outside the cab of any wrecker.

(c) Wreckers shall be operated with due care and circumspection.

Recodified from N.J.A.C. 13:62-2.19 by R.1998 d.354, effective July 20, 1998.
 See: 30 N.J.R. 1369(b), 30 N.J.R. 2636(a).

SUBCHAPTER 3. SAFETY REQUIREMENTS FOR VEHICLES AND PERSONNEL: ROAD RACING AND HIGH PERFORMANCE DRIVING SCHOOLS

13:62-3.1 Licensed facilities

Road course-racing, high performance driving schools, and related events shall only take place in licensed facilities. Sanctioned and unsanctioned events shall be conducted in a manner no less restrictive than permitted under the rules in this chapter.

13:62-3.2 Construction requirements

(a) Design and construction of permanent road course race courses must be approved for compliance with this chapter by the Superintendent or his or her designee prior to construction or alteration.

(b) Drawings of the road course track design and associated areas shall be provided as near to scale as practicable and shall indicate the location of required safety features.

(c) Safety features such as flag stations, hubrails, steel armco, tire barriers, and/or concrete walls shall be detailed on the drawings.

(d) Entrance and exit gates to the pits, staging areas, or emergency vehicle service areas, may remain open while cars are on the track and/or staging areas; however, all open gates shall be monitored to allow only authorized vehicles participating in the event and/or approved emergency vehicles.

(e) A pit entry and exit merge lane indicated by a painted solid yellow line shall be provided before the entry to the pits. The length of the lane must allow a vehicle to either obtain race speed before merging with race traffic or to decelerate the vehicle to pit lane speed prior to the entrance to pit lane.

13:62-3.3 Fences

(a) Fences shall be erected around the entire outside of the road course.

(b) If the infield of the road course is accessible by spectators or other non-driving participants, fencing shall also be provided around the entire infield with tunnels and/or bridges to allow emergency entry and egress.

(c) Fences required under this section shall be constructed of welded wire fabric or chain link and shall be at least five

feet in height and so constructed as not to be easily lifted, climbed over, or moved aside.

13:62-3.4 Flag stations and flagmen

(a) Flag stations shall be erected at appropriate locations around a road course to ensure that oncoming vehicles can be provided sufficient advance notice of any obstructions or emergencies that might be on the track surface or in potentially dangerous run off areas. Stations located near corners shall be located so as to have a clear view of the track both forward and rearward and in such a position that vehicles on the track can readily see any displayed warning lights or flags.

(b) Flag stations shall have adequate protection for the flagmen.

(c) Flagmen must be provided at designated flag stations during racing.

(d) Flag control: One flagmen, starter, or experienced event organizing official shall be designated "flag control." Flag control shall be responsible for coordinating communications with all flag stations, initiating emergency response calls, and controlling access to the race track at all times during an event.

(e) Any manned flag station shall be equipped with a two-way radio that is on the same channel as all other flag stations and race control.

(f) Flagmen will only be required during racing or events where more than seven vehicles occupy the track at the same time.

(g) When flagmen are used, all standard motorsport flags shall be used:

1. Yellow flag - caution, no passing;
2. Waving yellow flag - caution immediate danger, slow down, no passing;
3. Red flag procedure may be set by each sanctioning organization. If no procedure is provided to the contrary, all vehicles shall come to a controlled stop, off the race line within site of a flag station. The flagmen shall direct the vehicles when and how to resume. Alternatively the sanctioning body may choose to have the red flag indicate for all vehicles to slowly and proceed immediately into the pits;
4. White flag - slow vehicles on the track and/or last lap of a race;
5. Yellow and red stripe flag - caution, oil, or debris on the track on the race line;
6. Black flag with orange ball - mechanical problem with the vehicle to which the flag is pointed to. Vehicle must pit immediately and go to pit lane;

7. Black flag - vehicle to which the flag is pointed must proceed immediately to pit lane;

8. Green flag - track is clear and vehicles may proceed at race speed; and

9. Checker flag - indicates the finish of a race or the end of a session. Vehicles shall slow to cool down speeds, cease all passing, and proceed to pit lane at the first opportunity.

13:62-3.5 Maximum protection

(a) All safety features such as hubrails, steel armco, tire barriers, safer barriers, concrete walls, and fencing shall be constructed and maintained so as to afford maximum protection for spectators and participants.

(b) Any spectator stand or viewing area shall be at least 25 feet from the designated safety feature unless said feature is a fence.

13:62-3.6 Helmets and eye protection

(a) All drivers shall wear a properly secured helmet, which meets the most recent Snell Memorial Foundation Testing Standards M or SA, incorporated by reference herein, as may be amended and supplemented, which has not reached the expiration date established by the Snell Memorial Foundation at the time of the event. The standards are available from the Snell Memorial Foundation, 3628 Madison Avenue, Suite 11, North Highlands, CA 95660.

(b) "M" (Motorcycle) Snell rated helmets may be used in all motorcycle events and automobile events where fire ratings are not required.

(c) "SA" (Auto Special Application) Snell fire-rated helmets shall be used in all other applications.

(d) Helmets shall not be required under certain instructional and guided tour events where the maximum speed on the track shall not exceed 55 miles per hour.

(e) All helmets used by riders on motorcycles and open air race cars shall be full-faced and shall be worn with the visor in the closed position while on the track, the above rating and standards not withstanding.

(f) Crew members fueling vehicles in pit lane during racing shall wear an SA Fire-rated helmet meeting Snell Memorial Foundation Testing Standards (discussed at (a), (b) and (c) above), National Highway Safety Transportation Association Federal Motor Vehicle Safety Standard 218 (Code of Federal Register, Title 49, Volume 5, Part 571, Section 218, October 2003), or ANSI Z-90.1 standards, incorporated by reference as amended and supplemented, or a fire-resistant balaclava as an alternative. ANSI standards are available from the American National Standards Institute, 25 West 43rd Street, New York, NY 10036. National Highway Transportation Safety Administration standards are available

at <http://www.nhtsa.dot.gov/cars/rules/import/FMVSS/index.html>.

13:62-3.7 Safety belts, shoulder harness and crotch belt

(a) Safety belts are required at all times for any vehicles (except motorcycles), and any occupant of any vehicle, that is allowed on any portion of the race track.

(b) Safety belts for driving schools, time trials, lapping days, and promotional and tour events must meet the standards required by the sanctioning body or event organizer. At a minimum, original vehicle equipment DOT FMVSS 208, incorporated herein by reference and available at <http://www.nhtsa.dot.gov/cars/rules/import/FMVSS/index.html>, seat belts or DOT FMVSS 209, incorporated herein by reference and available at <http://www.nhtsa.dot.gov/cars/rules/import/FMVSS/index.html>, aftermarket seat belts shall be required.

(c) Practice days and road races for any vehicles (except motorcycles) require a minimum of a five-point safety belt for each occupant meeting one of the following standards:

1. SFI 16.1 or SFI 16.5, incorporated herein by reference and available at <http://www.sfifoundation.com>, seat belts shall be valid for two years from the month and year punched or indicated on the SFI tag. There shall be one original tag attached to one of the two shoulder belts, one original tag attached to one of the lap belts, and a third original tag attached to the crotch belt.

2. FIA 8853, incorporated herein by reference and available at <http://www.fia.com/sport/Regulations/standregs.html>, seat belts shall be valid for five years from the year of manufacture. Belts are stamped or printed with an expiration year. FIA seat belts expire on December 31 of the year printed or stamped on the FIA tag. FIA tags are located on each leg of the shoulder belt and lap belt, and on one leg of the crotch strap.

(d) Safety belts must be installed according to the manufacturer's recommendations and to the guidelines of the sanctioning organization.

(e) Four-, five-, and six-point seat belts shall not be used in conjunction with any original equipment vehicle seat that has integrated headrest without a direct pass thru for proper installation of a double shoulder belt.

(f) Crotch straps, in any installation, shall not be routed around the front of a seat.

13:62-3.8 Seats

(a) Vehicles participating in promotional and touring events, drivers schools, time trials, and lapping days, may utilize the original equipment seat provided by the manufacturer provided it has a headrest of sufficient height to provide head support to the driver.

(b) Vehicles participating in a race or race practice shall be fitted with a seat allowing for proper installation of the minimum five- or six-point seat belt. Such seat designs shall be in accordance with the rules of the sanctioning organization.

13:62-3.9 Inspection of vehicles

(a) Vehicles participating in an event by a sanctioning organization must meet all technical guidelines set forth by that organization.

(b) Any vehicles to be used in a race or other type of driving event are subject to unannounced inspection and approval at any time, for compliance with this chapter, by the Superintendent or designee.

13:62-3.10 Speed limits

(a) No vehicles shall be operated in the paddock or staging areas at a speed in excess of five miles per hour.

(b) No vehicles shall be operated in the pit lane in excess of 20 miles per hour during any event, except race and practice sessions.

(c) The pit lane speed limit shall be 50 miles per hour for races and practice sessions only.

13:62-3.11 Clothing requirements; other than drivers

(a) Tank tops, shorts, and any other kind of sandals or open-toed shoes are prohibited from the pit lane or any part of the race track during any part of an event where vehicles are active in the pit lane or on the race track.

(b) During races, crew members working in the hot pit shall wear suits of at least one layer of fire retardant material (two are recommended) to cover the entire torso, arms, and legs.

(c) Any crew member refueling a vehicle shall have a minimum of two layers of fire retardant material fire retardant shoes, gloves, socks, and head sock.

13:62-3.12 Number of persons in vehicle

(a) No vehicle shall carry more than one person at any time during a race or practice session.

(b) Certified instructors are permitted to ride as a passenger in any vehicle driven by a participant during any event, except a race.

(c) Certified instructors are permitted to drive vehicles with multiple passengers providing that each passenger has his or her own seat and seat belt.

(d) Multiple passengers may ride in a vehicle during promotional and touring events, and in other events for the purpose of instruction and/or demonstration providing:

1. All vehicle occupants are wearing a minimum of a factory provided seat belt; and

2. All passengers shall have signed a liability waiver form provided by the licensee or sanctioning organization.

13:62-3.13 Rollover bars

(a) Rollover protection is required for all open cockpit or convertible vehicles.

(b) Factory provided rollover protection (production vehicles) may be used for promotional and touring events, time trials, drivers schools, and lapping days providing that the height of any vehicle occupant (with helmet) is not higher than the highest point of the factory rollover protection structure.

(c) Convertibles and open vehicles (except motorcycles) in races and race practices shall have a roll bar that is a minimum of one inch above the head of any vehicle driver or instructor.

13:62-3.14 Driver requirement for racing

(a) All drivers shall be of the minimum age to meet the standards required by the sanctioning organization or be at least 17 years of age with a valid drivers license, if there is no sanctioning organization.

(b) All drivers of vehicles (other than motorcycles) during a race or race practice shall wear a minimum of two layers of fire-resistant material covering their body, legs, and arms.

(c) It is recommended that all drivers wear fire-resistant gloves, shoes, and socks.

(d) It is recommended that all drivers wear a fire-resistant head sock.

(e) Drivers of street legal cars are not required to wear fire-resistant clothing, but it is recommended.

(f) Motorcycle drivers must wear protective suits; however they need not be fire rated.

(g) Head and neck restraint meeting SFI 38.1 standard is strongly recommended for drivers of vehicles equipped with proper seats, headrests, and seat belts.

(h) Minimum age requirements shall not apply to licensed high performance driving schools or driving schools operated at licensed facilities by driving instructors accepted by their respective sanctioning organizations or industries.

SUBCHAPTER 4. SAFETY REQUIREMENTS FOR VEHICLES AND PERSONNEL: OVAL RACING

13:62-4.1 Construction requirements

(a) Hubrail construction shall comply in all respects with the requirements of this chapter.

(b) The licensee shall provide and maintain hubrails on the outer circumference of the track and around the entire circumference thereof. Where spectators are allowed in the infield or within the inner circumference of the track, the licensee shall provide and ensure a hubrail, as described in this section, around the inner circumference of the track.

(c) The hubrail shall consist of at least two planks of hard wood or other suitable materials, at least 10 inches in width by three inches in thickness.

1. At any oval track modified or built after March 5, 2007, the hubrail shall be constructed of metal or concrete material in accordance with New Jersey Department of Transportation Standard Roadway Construction-Traffic Control-Bridge Construction Details 2001, incorporated herein by reference, as may be amended and supplemented. The standard is available at <http://www.state.nj.us/transportation/eng/CADD/v8/v8RoadwayDetails/pdf/v8eRoadwayDetailsSet.pdf>. Additional state-of-the-art material shall be considered by the Superintendent or designee when documentation of such material has been properly submitted to for review. All material shall be constructed as to afford maximum protection for spectators and participants.

(d) The hubrail shall be supported by posts of similar material of at least six inches in width and six inches in thickness or round posts not less than seven inches in diameter, which are set in the ground at least four feet and shall extend above the ground at least two feet. The post shall be no higher than the hubrail planking and shall be spaced no more than six feet apart.

(e) Two planks of hardwood or other suitable material shall be mounted on the side of the post facing the track and running horizontally and parallel to each other.

(f) On the opposite side of the posts, not more than eight inches from the top thereof, there shall be a ¾ inch steel cable running around the circumference of the track and securely fastened to the post with eye bolts.

(g) The hubrail entrance and exit gates to the pit area shall be closed while vehicles are in motion on the track, unless alternate arrangements have been made by the installation of barriers of a type which will prevent cars out of control from leaving the track and entering the immediate pit working area.

(h) Where the licensee wishes to use methods other than gates, an inspection of such installations by a representative of the Superintendent is required.

(i) The hubrail opening for vehicles shall be so located that a vehicle leaving the track must turn 90 degrees before entering the pit area.

(j) At locations using methods other than gates between the pit area and the track, the licensee shall provide a guard to prevent unauthorized persons from entering the track area.

(k) The use of baled hay or straw or any similar material as a protective device between participating vehicles and spectators is specifically prohibited.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).
Added (c)1.

13:62-4.2 Fences

(a) All fences installed for the purpose of limiting spectator areas shall be constructed of welded wire fabric or chain link and shall be at least six feet in height and so constructed as not to be easily lifted, climbed over or moved aside.

(b) After March 5, 2007, new or existing oval track facilities larger than one-quarter of a mile that, either modify the existing track circumference or change, in any manner, the dimensions of the pit area shall erect a catch fence. The catch fence shall be erected between the track and the entire pit area. The catch fence shall be a minimum of 15 feet above the hubrail and constructed and maintained so as to afford the maximum protection for pit crews.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Inserted designation (a); in (a), deleted “, except at motocross events the fence shall be of the same construction but at least five feet in height” from the end; and added (b).

13:62-4.3 Red and amber lights

(a) Each track used for automotive racing, except those used for acceleration and performance tests, shall be equipped with a system of at least four red lights and four amber lights so arranged that at least one light of each color will be visible to the drivers as they enter each turn.

(b) The lights shall be so arranged as to be controlled by a single switch. The licensee shall provide a responsible person to operate such switch during the entire time of each race.

(c) When the red lights are illuminated, all racing vehicles on the track shall stop as soon as possible and remain stopped until such time as the red lights are turned out.

(d) When the amber lights are illuminated, all racing vehicles on the track shall slow down and maintain their position, unless otherwise directed to change position by a track official.

13:62-4.4 Flagmen

(a) Tracks over one mile in length may use flagmen in lieu of the red and amber lights, provided the assistant flagman in the starter's stand is in constant two-way radio or telephone communication with all flagmen.

(b) On display of the red flag all racing vehicles shall stop as soon as possible and remain stopped until such time as the red flag is removed from display.

(c) On display of the amber flag all racing vehicles shall slow down and maintain their position, unless otherwise directed to change position by a track official.

13:62-4.5 Starters

(a) The licensee shall provide a starter(s) located within a starter's stand with an unobscured view of the entire racing surface from which to control the racing event.

(b) The licensee shall provide an assistant flagman in the starter's stand at all circular or oval tracks, road courses and other locations utilizing the services of flagmen to control the event. The assistant flagmen used to control or start a race shall be in the starter's stand when starting and during the race.

13:62-4.6 Maximum protection

(a) All hubrails, fences, stands and buildings must be constructed and maintained so as to afford maximum protection for spectators.

(b) Any spectator stand erected or relocated on or after April 1, 1960, must be located at least 25 feet from the hubrail.

13:62-4.7 Safety belts, shoulder harness and crotch belt

(a) A quick release type safety belt, shoulder harness and crotch belt in good condition shall be compulsory on all vehicles.

(b) Both ends of the safety belt, shoulder harness and crotch belt must be fastened to the frame of the vehicle.

(c) All fittings and connections of the safety belt, shoulder harness and crotch belt shall be metal.

(d) All safety belts and shoulder harnesses shall be worn properly the entire time the vehicle is being driven in a race.

(e) All safety belts and shoulder harnesses shall bear the date of manufacture and shall not be used for more than two years from that date.

(f) The shoulder harness shall be secured to the frame of the vehicle and come over a round bar at the driver's shoulder height.

(g) No alterations shall be allowed to any manufactured design of seat belts.

Amended by R.2003 d.374, effective September 15, 2003.

See: 35 N.J.R. 2569(a), 35 N.J.R. 4294(a).

In (e), substituted "two" for "five".

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

In (e), substituted "that" for "the" following "from".

13:62-4.8 Inspection of vehicles

(a) The licensee shall arrange for the inspection of each participating vehicle prior to the event, to determine that it meets the requirements of this chapter. The licensee shall prohibit vehicles not meeting the requirements of this chapter from participation or practice.

(b) Vehicles which are to be used in automobile races or exhibitions of driving skill are subject to unannounced inspection and approval at any time by the Superintendent or designee.

13:62-4.9 Number of persons in vehicle

No vehicle shall carry more than one person at any time during a race or warm-up, except that during a bona fide training period an instructor may accompany the trainee.

13:62-4.10 Seats

A metal racing seat, that bears a manufacturer's identification as suitable for use in racing shall be used. The seat shall be set on a steel plate 1/8-inch thick, the size of the base of the seat. The seat shall be attached by six, three-line 5/16-inch bolts. Four bolts shall be installed at the bottom of the seat not more than three inches from the most outside edge. The remaining two bolts shall be installed at the two most practical widely spaced points at the top of the seat back. The two seat back bolts shall be attached to an anchoring position on the vehicle. A washer, larger than the head of the bolt, shall also be installed on each bolt.

Repeal and New Rule, R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Section was "Seats".

13:62-4.11 Bumpers

(a) All vehicles shall be equipped with bumpers on the rear.

(b) The bumper shall be fastened to the frame or structural component of the car.

(c) The height of the bumper shall be as high as the center of the wheel and at least two inches in height.

13:62-4.12 Rollover bars

(a) All vehicles shall be equipped with a rollover bar of a design, construction and quality recognized by industry stan-

dard and maintained with a view toward affording the driver maximum protection against injury.

(b) Rollover bars shall be a minimum of three inches above the driver's head.

(c) Rollover bars shall be bolted or welded to the frame of the vehicle.

13:62-4.13 Nerfing bars

(a) All vehicles shall be equipped with auxiliary bumpers, also known as nerfing bars, of a construction and design to afford the driver maximum protection against injury.

(b) Nerfing bars shall extend within two inches of, but not beyond, the outside edge of the tire.

13:62-4.14 Exhaust system

(a) The outlet for the exhaust system shall be outside of the vehicle and extend at least to the rear of the front firewall.

(b) The exhaust system shall be designed and constructed so as to direct the exhaust flow out and away from the driver.

13:62-4.15 Fire wall and flooring

(a) All vehicles shall have suitable metal flooring from the front firewall to the center of the driver's seat.

(b) All vehicles shall have a permanent fire wall between the fuel supply and the driver, unless the fuel tank consists of a shell with an inner rubber bladder in which case the fire wall is not required.

13:62-4.16 Fuel lines and fuel pumps

(a) A fuel line or fuel pump is prohibited in the driver's compartment unless properly shielded to prevent leakage in the event the line or pump is damaged or broken. This shielding shall consist of the steel braided material.

(b) Fuel lines shall be more than three inches from the headers, unless shielded by metal.

13:62-4.17 Fuel tanks

(a) The use of a commercially manufactured fuel cell is mandatory in all vehicles utilizing a cell size of five gallons or more.

(b) All fuel cells shall be comprised of a steel or aluminum container, bladder, anti-surge baffling and fill plate with check valves (vent check and fill check).

1. The rigid container shall be manufactured of not less than 22 gauge steel or 16 gauge aluminum.

2. No baffling material other than standard foam baffling as provided by the fuel cell manufacturer shall be permitted.

3. Bladders shall be commercially manufactured of either soft rubber (rubberized fabric) or a molded cross linked material.

4. Manufactured check valves shall be installed as a flow control device which closes during a "roll-over" accident to help prevent fuel escaping from the cell.

5. Any vehicle utilizing a tail tank shall use a rear bumper with a hoop plate, and it is recommended that a bladder also be utilized.

6. Fuel tanks shall not be mounted within the driver's compartment.

(c) All commercially manufactured fuel cell systems shall be approved for use by major sanctioning bodies (for example, NASCAR, FIA, SCCA, USAC).

(d) Except as set forth in (e) below, vehicles utilizing an "x" type frame work using a self-contained fuel cell with an inner bladder shall bolt the fuel cell to the frame under the cell. At least three one-inch metal straps one-quarter inch thick, shall be bolted to the frame of the vehicle by at least two $\frac{3}{8}$ inch three line bolts positioned around the cell on all sides, except for the bottom, so as to apply maximum pressure against the tank to the frame.

(e) Vehicles not utilizing an "x" type frame shall have four one inch metal straps, $\frac{1}{4}$ inch thick, bolted to the frame of the vehicle by at least two $\frac{3}{8}$ inch three line bolts positioned around the cell on all sides, except for the bottom, to apply maximum pressure against the tank to the frame.

(f) A reinforcing member of the same kind and size material as that used in the roll cage of the chassis shall be installed to the rear of the fuel tank joining the rearmost portion of the chassis.

(g) A vehicle utilizing a fuel tank mounted to the front of the front fire wall shall have a reinforcing member of the same kind of material as that used in the roll cage or chassis installed to afford maximum protection to the tank.

Amended by R.1997 d.211, effective May 19, 1997.
See: 29 N.J.R. 848(a), 29 N.J.R. 2465(b).

Inserted new (a) and (b); recodified former (a) and (b) as (d) and (e); rewrote (c); in (d), amended subsection reference, deleted "rubber" preceding "bladder", and made a nonsubstantive change; and recodified former (d) and (e) as (f) and (g).

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Added (b)5 and (b)6; in (d), inserted "utilizing an 'x' type frame work", "shall be" and "on all sides," deleted "self-contained" preceding "fuel cell" and "utilizing an 'x' type frame work" preceding "under the cell", and substituted "positioned" for "and angled to that it goes"; and in (e), substituted "Vehicles" for "Units", "an" for "a" and "positioned" for "and angled to go entirely", and inserted "on all sides, except for the bottom,".

13:62-4.18 Fuel supply shutoff valve

(a) All vehicles shall be equipped with a fuel shutoff valve or switch which is easily accessible to the driver.

(b) The fuel shutoff valve or switch shall be conspicuously marked with a brightly colored paint.

13:62-4.19 Refueling

(a) In all instances where refueling is permitted with the engine running, a member of the pit crew, equipped with a 10 BC or greater fire extinguisher, shall be in close proximity to the fill pipe of the fuel tank.

(b) Smoking shall be prohibited in any area where fuel is being transferred or stored.

(c) The driver compartment shall not be occupied when the vehicle is being refueled if the fill pipe is located within 24 inches of the cockpit, except that the driver compartment may be occupied when the vehicle is being refueled from gravity fed fuel containers.

(d) The use of welding and acetylene torches is not permitted in any area where fuel is being transferred or stored unless a fully charged fire extinguisher is in close proximity.

13:62-4.20 Batteries

(a) Batteries, located in the driver compartment, shall be secured and shielded to prevent leakage in the event of damage or turnover.

(b) Batteries located adjacent to the fuel supply of the vehicle it shall be secured in a metal box bolted to the frame of the vehicle by at least four $\frac{3}{8}$ inch three line bolts and in such a manner to apply maximum pressure against the metal box to the frame. The battery shall also have a marine box cover secured to the top of the metal box as to not allow any movement of the battery.

(c) Batteries located in any other area not specified in (a) and (b) above shall be secured and shielded to prevent leakage in the event of damage or turnover.

13:62-4.21 Braking system and pedal reserve

(a) The licensee or designee shall test and approve each race car for brake pedal reserve before the car leaves the pit area to enter the track.

(b) The licensee or designee shall prohibit any vehicle from participating in any event or exhibition if the braking system includes the direct application of pressure to any of the tires or with apparent deficiencies.

13:62-4.22 Tires

(a) No vehicle shall be permitted to participate in any race if the tires are equipped or fitted with any studs, hobs, or other projections.

(b) This section is not intended to prohibit the use of rubber knobbed tires normally used on dirt race tracks.

(c) No vehicle shall be permitted to participate in any race if the tires are in an unsafe condition.

13:62-4.23 Ignition switch

All vehicles shall have an ignition switch which is easily accessible within the driver compartment and conspicuously marked.

13:62-4.24 Repairs

No repairs shall be made on any vehicle during the course of a race unless the vehicle is removed to the pit area.

13:62-4.25 Drivers

(a) All drivers shall be at least 17 years of age, except that:

1. Licensees may permit drivers 16 years of age to operate in events utilizing full-sized vehicles restricted to 400 hp or less, provided they have satisfied the skill and experience requirements of the licensee.

(b) All drivers are required to wear fire resistant underwear and one piece fire resistant clothing covering their body, legs, and arms.

(c) All drivers are required to wear fire resistant gloves.

(d) All drivers shall wear fire resistant shoes and socks.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

In the introductory paragraph of (a), substituted "17" for "18" and "except that:" for the period at the end; added (a)1; and in (d), substituted "shall" for "are required to", deleted "it is recommended that fire resistant" preceding "socks" and deleted "be worn" from the end.

13:62-4.26 Helmets, head cushions and head and neck restraints

(a) All drivers shall wear a properly secured helmet, which meets or exceeds the latest Snell Memorial Foundation Testing Standard SA, incorporated by reference herein, as may be amended and supplemented, which has not reached the expiration date established by the Snell Memorial Foundation at the time of the event. The standards are available from the Snell Memorial Foundation, 3628 Madison Avenue, Suite 11, North Highlands, CA 95660.

(b) All vehicles shall be equipped with a head cushion attached to the roll-on bar or to the back portion of a one-piece seat. The cushion shall be mounted so that it shall be at the approximate height of the center of the driver's helmet.

(c) The head cushion shall be a minimum of 16 square inches in area with at least two inch padding. The minimum length of any side of the head cushion shall be four inches.

(d) A support cushion shall be located behind the rear portion of the seat, attached to the roll cage and at least 1/8 of an inch thick.

(e) All drivers shall wear a properly secured head and neck restraint device/system and/or a neck collar which are commercially-produced and designed for racing.

Amended by R.2003 d.374, effective September 15, 2003.

See: 35 N.J.R. 2569(a), 35 N.J.R. 4294(a).

Rewrote (a).

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Section was "Helmets and head cushions". Rewrote (a); and added (e).

13:62-4.27 Goggles or face shield

The driver of all vehicles not equipped with windshields shall wear windproof, shatterproof goggles or a face shield of the type which meets or exceeds U.S.A. standard Specifications for Head, Eye and Respiratory Protection Z2.1-1959 testing standard.

13:62-4.28 Arm restraints; window nets

All drivers shall use arm restraints or window nets.

13:62-4.29 Transmission safety mats

(a) Any vehicle equipped with an automatic transmission shall have a steel mat, plate, or blanket installed over the transmission so as to protect the driver from injury caused by fragmentation of the automatic transmission upon explosion.

(b) All cooling devices within the driver's compartment shall be shielded from the driver to protect against injuries.

13:62-4.30 Enclosed drive shaft

The drive shaft of a vehicle shall be enclosed or secure, front and rear, by a steel strap 1/4 inch thick by one inch wide, a 1/2 inch steel rod, or one inch steel tubing with .06 wall thickness.

13:62-4.31 Water overflow tank

Water overflow reservoirs shall not be installed inside the driver compartment. Tanks or reservoirs mounted in the roll cage must be fully shielded to protect the driver.

13:62-4.32 Speed limits

(a) Vehicles traveling in the pit area or staging area must obey a five miles per hour speed limit.

(b) Vehicles utilizing a return road will be limited to a 15 miles per hour speed limit.

13:62-4.33 Licensed facilities

Oval racing events shall only take place in licensed facilities.

SUBCHAPTER 5. SAFETY REQUIREMENTS FOR
VEHICLES AND PERSONNEL: DRAG RACING**13:62-5.1 Construction requirements**

(a) Hubrail construction shall comply in all respects with the requirements of this chapter.

(b) The licensee shall provide and maintain hubrails on the outer area of the track and around the entire area thereof. Where spectators are allowed in the return road or within the inner area of the track, the licensee shall provide and maintain a hubrail, as described in this section, around the inner area of the track.

(c) At any facility modified or built after March 5, 2007, the hubrail shall be constructed of metal or concrete material in accordance with New Jersey Department of Transportation Standard Roadway Construction-Traffic Control-Bridge Construction Details 2001, incorporated herein by reference, as may be amended and supplemented, available at <http://www.state.nj.us/transportation/eng/CADD/v8/v8RoadwayDetails/pdf/v8eRoadwayDetailsSet.pdf>, that provides no less protection than two planks of hard wood or other suitable materials, at least 10 inches in width by three inches in thickness. Additional state-of-the-art material shall be considered by the Superintendent or designee when documentation of such material has been properly submitted for review. All material shall be constructed as to afford maximum protection for spectators and participants.

(d) The hubrail shall be supported by posts of similar material of at least six inches in width and six inches in thickness or round posts not less than seven inches in diameter, which are set in the ground at least four feet and shall extend above the ground at least two feet. The post shall be no higher than the hubrail planking and shall be spaced no more than six feet apart.

(e) Two planks of hardwood or other suitable material shall be mounted on the side of the post facing the track and running horizontally and parallel to each other.

(f) On the opposite side of the posts, not more than eight inches from the top thereof, there shall be a ¾ inch steel cable running around the circumference of the track and securely fastened to the post with eye bolts.

(g) All hubrail access gates to and from the track area shall remain secured during racing. These gates shall only be opened by authorized personnel at such times as racing has been suspended.

(h) Where the licensee wishes to use methods other than gates, an inspection of such installations by a representative of the Superintendent is required.

(i) The hubrail opening for vehicles shall be so located that a vehicle leaving the track must turn 90 degrees before entering the pit area.

(j) At locations using methods other than gates between the pit area and the track, the licensee shall provide a guard to prevent unauthorized persons from entering the track area.

(k) The use of baled hay or straw or any similar material as a protective device between participating vehicles and spectators is specifically prohibited.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Rewrote (c) and (g).

13:62-5.2 Fences

All fences installed for the purpose of limiting spectator areas shall be constructed of welded wire fabric or chain link and shall be at least six feet in height and so constructed as not to be easily lifted, climbed over or moved aside.

13:62-5.3 Starting tree lights

(a) Strips used for acceleration and performance tests need be equipped with only one red light on the starting tree.

(b) The lights shall be controlled by a single switch. The licensee shall provide a responsible person to operate such switch during the entire time of each race.

(c) When the red lights are illuminated, all racing vehicles on the track shall stop as soon as possible and remain stopped until such time as the red lights are turned out.

13:62-5.4 Starters

The licensee shall provide a Starter(s) located within a starter's area with an unobscured view of the entire racing surface from which to control the racing event.

13:62-5.5 Maximum protection

(a) All hubrails, fences, stands and buildings shall be constructed and maintained so as to afford maximum protection for spectators.

(b) Any spectator stand erected or relocated on or after April 1, 1960, shall be located at least 25 feet from the hubrail.

13:62-5.6 Location

(a) A location approved for acceleration and performance tests shall provide for a stopping distance at least equal to the acceleration and timing distance.

(b) The acceleration area shall not exceed 1,386 feet.

(c) The entire racing strip, including the deceleration area, shall be paved.

(d) The end of the acceleration area may be marked by an overhead banner, provided the supports are of such construction that they will not present a hazard to the vehicles. The

height of the banner shall be at least 14 feet above the surface of the strip.

13:62-5.7 Vehicle equipment

(a) Safety belts, shoulder harness and crotch belt shall be provided in accordance with Section 16 of the National Hot Rod Association's rules, incorporated by reference at N.J.A.C. 13:62-5.39.

1. A quick release type safety belt, shoulder harness and crotch belt in good condition shall be compulsory on all vehicles.

2. Both ends of the safety belt, shoulder harness and crotch belt shall be fastened to the frame of the vehicle.

3. All fittings and connections of the safety belt, shoulder harness and crotch belt shall be metal.

4. All safety belts and shoulder harnesses shall be worn properly the entire time the vehicle is being driven in a race.

5. All five- and six-point harnesses shall bear the date of manufacture and shall not be used more than two years from that date.

6. The shoulder harness shall be secured to the frame of the vehicle and come over a round bar at the driver's shoulder height.

7. No alterations shall be allowed to any manufactured design of seat belts.

8. The exception to this section is for street legal cars. These vehicles shall be equipped with the safety belt(s) that was provided by the manufacturer.

Amended by R.2003 d.374, effective September 15, 2003.

See: 35 N.J.R. 2569(a), 35 N.J.R. 4294(a).

In (a)5, substituted "two" for "five".

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Rewrote (a); and in (a)5, substituted "five- and six-point" for "safety belts and shoulder" and "that" for "the".

13:62-5.8 Inspection of vehicles

(a) The licensee shall arrange for the inspection of each participating vehicle prior to the event, to determine that it meets the requirements of this chapter. The licensee shall prohibit vehicles not meeting the requirements of this chapter from participation or practice.

(b) Vehicles which are to be used in automobile races or exhibitions of driving skill are subject to unannounced inspection and approval at any time by the Superintendent or designee.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

In (a), deleted "shall be barred by the licensee" preceding "from".

13:62-5.9 Number of persons in vehicle

No vehicle shall carry more than one person at any time during a race or warm-up, except during a bona fide training period an instructor may accompany the trainee.

13:62-5.10 Seats

All seats shall be constructed, located, and mounted, in accordance with Section 16.6:2 of the National Hot Rod Association's rules relative to class of competition, incorporated by reference at N.J.A.C. 13:62-5.39.

Repeal and New Rule, R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Section was "Seats".

13:62-5.11 Exhaust system

The exhaust system shall be designed and constructed so as to direct the exhaust flow out and away from the driver.

13:62-5.12 (Reserved)

Repealed by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Section was "Fire wall and flooring".

13:62-5.13 (Reserved)

Repealed by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Section was "Fuel lines and fuel pumps".

13:62-5.14 Fuel tanks

All fuel tanks shall be constructed, fastened, located, and reinforced as per NHRA rules, based on class of competition, incorporated by reference at N.J.A.C. 13:62-5.39.

Repeal and New Rule, R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Section was "Fuel tanks".

13:62-5.15 Refueling

(a) In all instances where refueling is permitted with the engine running, a member of the pit crew, equipped with a 10 BC or greater fire extinguisher, shall be in close proximity to the fill pipe of the fuel tank.

(b) Smoking shall be prohibited in any area where fuel is being transferred or stored.

(c) The driver compartment shall not be occupied when the vehicle is being refueled if the fill pipe is located within 24 inches of the cockpit, except that the driver compartment may be occupied when the vehicle is being refueled from gravity fed fuel containers.

(d) The use of welding and acetylene torches is not permitted in any area where fuel is being transferred or stored unless a fully charged fire extinguisher is in close proximity.

13:62-5.16 Batteries

(a) Batteries, located in the driver compartment, shall be secured and shielded to prevent leakage in the event of damage or turnover.

(b) Batteries located adjacent to the fuel supply of the vehicle it shall be secured in a metal box bolted to the frame of the vehicle by at least four 3/8 inch three line bolts and in such a manner to apply maximum pressure against the metal box to the frame. The battery shall also have a marine box cover secured to the top of the metal box as to not allow any movement of the battery.

(c) Batteries located in any other area not specified in (a) and (b) above shall be secured and shielded to prevent leakage in the event of damage or turnover.

13:62-5.17 Braking system and pedal reserve

(a) The licensee or designee shall test and approve each race car for brake pedal reserve before the car leaves the pit area to enter the track.

(b) The licensee or designee shall prohibit any vehicle from participating in any event or exhibition if the braking system includes the direct application of pressure to any of the tires or with apparent deficiencies.

13:62-5.18 Tires

(a) No vehicle shall be permitted to participate in any race if the tires are equipped or fitted with any studs, hobs, or other projections.

(b) No vehicle shall be permitted to participate in any race if the tires are in an unsafe condition.

13:62-5.19 Ignition switch

(a) All vehicles shall have an ignition switch which is easily accessible within the driver compartment and conspicuously marked.

(b) All motorcycles shall be equipped with a functional tether mechanical kill device so that the ignition is shut off if the rider separates from the vehicle.

13:62-5.20 Repairs

No repairs shall be made on any vehicle during the course of a race unless the vehicle is removed to the pit area.

13:62-5.21 Drivers

(a) All drivers shall be at least 17 years of age.

(b) It is recommended that all drivers wear fire resistant underwear and one piece fire resistant clothing covering their body, legs, and arms.

(c) It is recommended that all drivers wear fire resistant gloves.

(d) It is recommended that all drivers wear fire resistant shoes and socks.

(e) Drivers of motorcycles and street legal cars are not required to wear fire resistant clothing, but it is recommended.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

In (a), substituted "17" for "18"; and in (d), deleted "it is recommended that fire resistant" preceding "socks" and "be worn" from the end.

13:62-5.22 Helmets, head cushions, and head and neck restraints

(a) All drivers shall wear a properly secured helmet which meets or exceeds the Snell Memorial Foundation Testing Standards for special application (SA) or motorcycle (M) use, respectively, incorporated herein by reference, as may be amended and supplemented, which has not reached the expiration date established by the Snell Memorial Foundation at the time of the event. The standards are available from the Snell Memorial Foundation, 3628 Madison Avenue, Suite 11, North Highlands, CA 95660.

(b) Where required under NHRA rules, incorporated by reference at N.J.A.C. 13:62-5.39, all drivers shall wear a properly secured head and neck restraint device/system or neck collar which is commercially-produced and designed for racing.

Amended by R.2003 d.374, effective September 15, 2003.

See: 35 N.J.R. 2569(a), 35 N.J.R. 4294(a).

Substituted "Snell Memorial Foundation Testing Standard K, M or SA, incorporated herein by reference, as may be amended or supplemented" for "American National Standard Institute (A.N.S.I.) Z-90.1 testing standard".

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Section was "Helmets and head cushions". Inserted designation (a); rewrote (a); and added (b).

13:62-5.23 Goggles or face shield

The driver of all vehicles not equipped with windshields shall wear windproof, shatterproof goggles or a face shield of the type which meets or exceeds U.S.A. standard Specifications for Head, Eye and Respiratory Protection Z2.1-1959 testing standard.

13:62-5.24 (Reserved)

Repealed by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Section was "Transmission safety mats".

13:62-5.25 Enclosed drive shaft

The drive shaft of a vehicle running 13.99 or quicker elapsed time shall be enclosed or secured in the front by a steel strap 1/4 inch thick by one inch wide, a one-half inch

steel rod or one one inch steel tubing with .06 wall thickness. This is not required for vehicles with an elapsed time of 14.00 and slower equipped with street tires.

13:62-5.26 Water overflow tank

Water overflow reservoirs shall not be installed inside the driver compartment. Tanks or reservoirs mounted in the roll cage must be fully shielded to protect the driver.

13:62-5.27 Vehicle lighting

All vehicles shall be equipped with a functioning taillight so that the starter is able to see the competing vehicles during night racing.

13:62-5.28 Vehicles equipped with parachutes

(a) All vehicles equipped with parachutes shall have a red streamer attached to the safety pin. The safety pin shall be removed from the parachutes before the starting lights are activated.

(b) All vehicles utilizing two or more parachutes shall have at least two anchoring points for each parachute, each separate from the other.

13:62-5.29 Exceptions

(a) Cars need not have rollover bars or door fastening, provided there has been no modification of either body or engine.

(b) Street legal cars are exempt from having an enclosed drive shaft provided that no modifications have been done to the vehicle.

13:62-5.30 Spectator protection

The licensee shall provide spectator protection by a standard hubrail and six-foot high welded wire fabric or chain link fence so constructed as not to be easily lifted, climbed over or moved aside.

13:62-5.31 Pit area fences

The pit area, if located behind the starting line, shall be separated from the track by a six-foot high welded fabric or chain link fence so constructed as not to be easily lifted, climbed over or moved aside.

13:62-5.32 Vehicle positioning

Racing vehicles may line up a safe distance behind the starting line. Only drivers, officials, and authorized persons are permitted in this area.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Inserted "a safe distance" and ", and authorized persons" and substituted a comma for "and" following "drivers".

13:62-5.33 "Burnouts"

No "burnouts" shall be made unless the driver is secured in the vehicle and the doors are firmly closed.

13:62-5.34 Speed limits

(a) All vehicles returning after a race event, using the return road, either under their own power or being towed shall obey a 15 miles per hour speed limit until the vehicle has been returned to the staging lanes or pits.

(b) All vehicles traveling in the pit area or staging area shall obey a five miles per hour speed limit.

13:62-5.35 Minimum age requirement for a street legal car racing events

No persons will be permitted to participate in a street legal car racing event unless that person is 17 years of age and possesses a valid driver's license from his/her state of residence.

13:62-5.36 Persons permitted in the pit area

(a) All persons with pit credentials are to be permitted in the pit area. Persons under the age of 17 are to be permitted in the pit area as long as the individual has the proper pit credentials and is accompanied by an adult.

(b) No one under the age of 17 will be permitted in the staging area under any circumstance unless otherwise specified.

13:62-5.37 Vehicles allowed in return road

(a) Only official vehicles are permitted to travel the return road while a racing event is in progress. An official vehicle means a vehicle displaying the competitor's vehicle number and shall be limited to one official vehicle per competition vehicle.

(b) All official vehicles shall obey the following speed limits:

1. All vehicles returning after a race event, using the return road, either under their own power or being towed shall obey a 15 miles per hour speed limit until the vehicle has been returned to the staging lanes or pits.

2. All vehicles traveling in the pit area or staging area shall obey a five miles per hour speed limit.

(c) All official vehicles shall wait outside the return road until the competition vehicle has entered the burn out area and is preparing to compete.

13:62-5.38 Licensed facilities

Drag racing events shall only take place in licensed facilities.

13:62-5.39 Exceptions

Except as specifically set forth within this subchapter, all licensees, participants, and participating vehicles shall adhere to the 2006 National Hot Rod Association (NHRA) Rulebook, incorporated herein by reference, as may be amended and supplemented. Copies of the rulebook are available from the NHRA at National Hot Rod Association, 2035 Financial Way, Glendora, CA 91741 or at www.nhra.com.

New Rule, R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

—————

SUBCHAPTER 6. MOTORCYCLE AND QUAD
VEHICLES RACING EVENTS (OVAL RACING)

13:62-6.1 Licensed facilities

Motorcycle and quad vehicle oval racing events shall only take place in licensed facilities.

13:62-6.2 Hubrail construction

(a) Hubrail construction shall comply in all respects with the requirements of this chapter.

(b) The licensee shall provide and maintain hubrails on the outer circumference of the track and around the entire circumference thereof. Where spectators are allowed in the infield or within the inner circumference of the track, the licensee shall provide and maintain a hubrail, as described in this section, around the inner circumference of the track.

(c) The hubrail shall consist of at least two planks of hardwood or other suitable materials, at least 10 inches in width by three inches in thickness.

1. At any facility modified or built after March 5, 2007, the hubrail shall be constructed of metal or concrete material in accordance with New Jersey Department of Transportation Standard Roadway Construction-Traffic Control-Bridge Construction Details 2001, incorporated herein by reference, as may be amended and supplemented, available at <http://www.state.nj.us/transportation/eng/CADD/v8/v8RoadwayDetails/pdf/v8eRoadwayDetailsSet.pdf>, which provides no less protection than two planks of hard wood or other suitable materials, at least 10 inches in width by three inches in thickness. Additional state-of-the-art material shall be considered by the Superintendent or designee when documentation of such material has been properly submitted for review. All material shall be constructed as to afford maximum protection for spectators and participants.

(d) The hubrail shall be supported by posts of similar material of at least six inches in width and six inches in thickness or round posts not less than seven inches in diameter, which are set in the ground at least four feet and shall extend above the ground at least two feet. The post shall be no higher than

the hubrail planking and shall be spaced no more than six feet apart.

(e) Two planks of hardwood or other suitable material shall be mounted on the side of the post facing the track and running horizontally and parallel to each other.

(f) On the opposite side of the posts, not more than eight inches from the top thereof, there shall be a ¾ inch steel cable running around the circumference of the track and securely fastened to the post with eye bolts.

(g) The hubrail entrance and exit gates to the pit area shall be closed while vehicles are in motion on the track, unless alternate arrangements have been made by the installation of barriers of a type which will prevent cars out of control from leaving the track and entering the immediate pit working area.

(h) Where the licensee wishes to use methods other than gates, an inspection of such installations by a representative of the Superintendent is required.

(i) The hubrail opening for vehicles shall be so located that a vehicle leaving the track must turn 90 degrees before entering the pit area.

(j) At locations using methods other than gates between the pit area and the track, the licensee shall provide a guard to prevent unauthorized persons from entering the track area.

(k) The use of baled hay or straw or any similar material as a protective device between participating vehicles and spectators is specifically prohibited.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).
Added (c)1.

13:62-6.3 Exceptions

(a) Hubrail posts constructed for use on motorcycle tracks shall be no higher than the hubrail planking.

(b) Hubrails constructed for use on motorcycle tracks shall consist of safety rails two feet high, constructed of two two-inch by 12-inch planks, on four-inch by four-inch stanchions spaced not more than six feet apart, and so embedded in the ground that they will not pull out if struck.

(c) As an alternative to the two-inch by 12-inch planks, two planks made of marine plywood, ¾ inches thick and 12 inches wide may be used on motorcycle tracks. These rails shall be backed up either by a wire cable similar to the wire cable used on automobile hubrails, except that it need not exceed ½ inch in diameter, or in the alternative, a mound of packed earth shall be constructed in the back of the safety rail at least 18 inches high, and tapering to the ground level between the rail and the spectators.

13:62-6.4 Fences

All fences installed for the purpose of limiting spectator areas shall be constructed of welded wire fabric or chain link and shall be at least six feet in height and so constructed as not to be easily lifted, climbed over or moved aside.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Deleted “, except at motocross events the fence shall be of the same construction but at least five feet in height” from the end.

13:62-6.5 Red and amber lights

(a) Each track used for motorcycle racing, except those used for acceleration and performance tests, shall be equipped with a system of at least four red lights and four amber lights so arranged that at least one light of each color will be visible to the drivers as they enter each turn.

(b) The lights shall be controlled by a single switch. The licensee shall provide responsible person to operate such switch during the entire time of each race.

(c) When the red lights are illuminated, all racing vehicles on the track shall stop as soon as possible and remain stopped until such time as the red lights are turned out.

(d) When the amber lights are illuminated, all racing vehicles on the track shall slow down and maintain their position unless otherwise directed to change position by a track official.

13:62-6.6 Flagmen

(a) Tracks over one mile in length may use flagmen in lieu of the red and amber lights, provided the assistant flagman in the starter’s stand is in constant two-way radio or telephone communication with all flagmen.

(b) Flagmen shall be positioned so as to be visible to drivers entering each turn on the track or course.

(c) On display of the red flag all racing vehicles shall stop as soon as possible and remain stopped until such time as the red flag is removed from display.

(d) On display of the amber flag all racing vehicles shall slow down and maintain their position unless directed to change position by a track official.

(e) Flagmen at all racing events shall be at least 16 years of age.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Added (e).

13:62-6.7 Starters

(a) The licensee shall provide starter(s) located within a starter’s stand with an unobscured view of the entire racing surface from which to control the racing event.

(b) All circular or oval tracks utilizing the services of flagmen to control the event shall also have an assistant flagman in the starter’s stand. The assistant flagmen used to control or start a race shall be in the starter’s stand when starting and during the race.

(c) Starters at all racing events shall be at least 16 years of age.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Added (c).

13:62-6.8 Maximum protection

(a) All hubrails, fences, stands and buildings must be constructed and maintained so as to afford maximum protection for spectators.

(b) Any spectator stand erected or relocated on or after April 1, 1960, must be located at least 25 feet from the hub-rail.

13:62-6.9 Eye protection

All drivers shall wear windproof, shatterproof goggles or face shield of the type, which meets or exceeds U.S.A. standard Specifications for Head, Eye and Respiratory Protection Z2.1-1959 testing standard unless excessively muddy conditions would create a view obstruction on those devices.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Inserted “unless excessively muddy conditions would create a view obstruction on those devices”.

13:62-6.10 Helmets

All drivers shall wear a properly secured helmet which meets or exceeds the latest Snell Memorial Foundation Testing Standard K, M or SA, incorporated herein by reference, as may be supplemented or amended, which has not reached the expiration date established by the Snell Memorial Foundation at the time of the event. The Standards are available from the Snell Memorial Foundation, 3628 Madison Avenue, Suite 11, North Highlands, CA 95660.

Amended by R.2003 d.374, effective September 15, 2003.

See: 35 N.J.R. 2569(a), 35 N.J.R. 4294(a).

Substituted “Snell Memorial Foundation Testing Standard K, M or SA, incorporated herein by reference, as may be amended or supplemented” for “American National Standard Institute (A.N.S.I.) Z-90.1 testing standard”.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Rewrote the section.

13:62-6.11 Braking system

(a) A representative of the track licensee will be required to test front and rear brake application before the vehicle leaves the area to enter the track.

(b) This section is not to be construed to require brakes on racing motorcycles with a compression ratio higher than 10 to one or with a compression ratio which, in the opinion of the Superintendent, is sufficiently high to bring the motorcycle to a stop when the ignition is cut off.

13:62-6.12 Shutoff device

(a) A "shutoff" device shall be affixed to the handlebars on all competing motorcycles.

(b) A "shutoff" device shall be of a type which is designed, constructed and maintained to stop the motor of the motorcycle immediately upon releasing or pressing the said device.

13:62-6.13 Minimum age requirements of motorcycle racing events

(a) All drivers participating in a motorcycle or quad racing event (oval) shall be at least 17 years of age.

(b) All participants shall possess and display, upon request, a valid motorcycle license or endorsement.

(c) All persons participating in an event shall have proper documentary evidence to substantiate proof of age.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).
Rewrote (a).

13:62-6.14 Quad vehicle requirements

(a) Quad vehicles shall be equipped with a functional tether type mechanical kill device, so that the ignition is shut off upon the driver's separation from the vehicle.

(b) Quad vehicle engines shall be fitted with a guard completely enclosing the primary drive.

(c) Rear chain guards, roll bars and seat belts are not required.

(d) Vehicles designed to operate with three wheels (tricycles) are prohibited from participation.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).
Added (d).

13:62-6.15 Clothing requirements

(a) Drivers shall wear safety clothing to afford maximum protection to the driver according to industry standards. It is recommended that this clothing be of a fire retardant material.

(b) Mechanics shall wear pants while working on their respective vehicles.

(c) Drivers are not permitted to wear shorts while competing.

(d) Track staff shall wear pants at all times while working in a race or practice event.

(e) Staff personnel shall wear brightly colored safety vests to be easily identified or other identifying uniforms while working a race or practice event.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).
Inserted designation (a); and added (b) through (e).

13:62-6.16 Batteries

Batteries shall be secured and shielded to prevent leakage in the event of damage or turnover.

13:62-6.17 Speed limits

All vehicles traveling in the pit area or staging area shall obey a five miles per hour speed limit.

13:62-6.18 Pit credentials

(a) The track management shall be responsible for the issuance of pit credentials and only those credentials issued by the track management shall be recognized as valid.

(b) Only persons holding pit credentials shall be admitted to the pit area or racing area.

(c) Reporters and photographers of the working press in possession of valid pit credentials shall be limited to safe areas.

(d) The issuance of pit credentials shall be limited to:

1. Pit crew members age 16 and above, with a maximum of eight, which includes the rider.
2. Riders having motorcycles or quads entered in one of the events in the race;
3. Members of the track staff having business in the pit area;
4. Race officials; and
5. Accredited photographers and reporters of the working press.

(e) The track management shall be responsible for the checking of credentials of persons entering the pit area to determine that no person shall enter the pit area or engage in a race or exhibition unless such person shall produce credentials showing age which satisfies the age requirement for a particular event. For 16-year olds, valid photo identification and a copy of the birth certificate shall be produced.

New Rule, R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

**SUBCHAPTER 6A. MOTOCROSS AND QUAD
VEHICLE RACING EVENTS (SERPENTINE
RACING)**

13:62-6A.1 Licensed facilities

Motocross and quad vehicle serpentine racing events shall only take place in licensed facilities.

13:62-6A.2 Construction requirements

(a) Design and construction of motocross and quad vehicle race courses must be approved by the Superintendent or his or her designee prior to the racing event.

(b) A sketch or sketches of the track and associated areas shall be provided as near to scale as practicable indicating the location of required safety features.

(c) Safety features such as hubrails, fences, crash protection for participants, light or flagmen positions, spectator seating, entrances and exits, pit facility locations and other physical factors affecting the safety of spectators and participants may be required for approval depending on the terrain and location of the race course. This requirement shall not apply to locations licensed prior to January 1, 1963, unless alterations are made to the track and associated areas on or after January 1, 1963.

13:62-6A.3 Fences

All fences installed for the purpose of limiting spectator areas shall be constructed of welded wire fabric or chain link and shall be at least six feet in height and so constructed as not to be easily lifted, climbed over or moved aside, except at motocross events the fence shall be of the same construction but at least five feet in height.

13:62-6A.4 Flagmen

(a) Licensees may use flagmen provided an assistant flagman is in the starter's area and is in constant two-way radio or telephone communication with all flagmen.

(b) Flagmen shall be positioned so as to be visible to drivers entering each turn on the track or course.

(c) All working personnel and officials having access to the pit area or racing surface shall be at least 16 years of age.

(d) On display of the red flag, all racing vehicles shall stop as soon as possible and remain stopped until such time as the red flag is removed from display.

(e) On display of the amber flag all racing vehicles are to slow down and maintain their position.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).
Deleted (c)1.

13:62-6A.5 Starters

Starter(s) shall be located within a starter's area with an unobscured view of the entire racing surface from which to control the racing event.

13:62-6A.6 Additional requirements for motocross events

(a) Except as provided in this chapter and in (a)1 and 2 below, all motocross practice, racing, and exhibition events shall be in accordance with the 2006 American Motorcyclist Association (AMA) rules and regulations, which are incorporated by reference, as may be amended and supplemented. AMA rules may be obtained from the American Motorcyclist Association, 13515 Yarmouth Drive, Pickerington, OH 43147 or at www.AMADirectlink.com:

1. The designation "cc" shall be conspicuously marked on the racing vehicle; and
2. Hubrail construction does not pertain to motocross events which utilize jumps and serpentine type racing.

Amended by R.2001 d.354, effective October 1, 2001.
See: 33 N.J.R. 2250(a), 33 N.J.R. 3451(b).

In (a), substituted "requirements" for "guidelines" in the introductory paragraph, inserted a new 1 and recodified former 1 through 6 as 2 through 7.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Rewrote (a).

13:62-6A.7 Clothing requirements

Drivers shall wear safety clothing to afford maximum protection to the driver according to industry standards. It is recommended that this clothing be of a fire retardant material.

13:62-6A.8 Helmets

All drivers shall wear a properly secured helmet which meets or exceeds the Snell Memorial Foundation Testing Standard K, M or SA, incorporated herein by reference, as may be amended or supplemented, which has not reached the expiration date, established by the Snell Memorial Foundation at the time of the event. The Standards are available from the Snell Memorial Foundation, 3628 Madison Avenue, Suite 11, North Highlands, CA 95660.

Amended by R.2003 d.374, effective September 15, 2003.
See: 35 N.J.R. 2569(a), 35 N.J.R. 4294(a).

Substituted "Snell Memorial Foundation Testing Standard K, M or SA, incorporated herein by reference, as may be amended or supplemented" for "American National Standard Institute (A.N.S.I.) Z-90.1 testing standard."

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Rewrote the section.

13:62-6A.9 Goggles or face shield

All drivers shall wear windproof, shatterproof goggles or a face shield of the type which meets or exceeds U.S.A. standard Specifications for Head, Eye and Respiratory Protection

Z2.1-1959 testing standard, unless excessively muddy conditions would create a view obstruction on those devices.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Inserted “, unless excessively muddy conditions would create a view obstruction on those devices”.

13:62-6A.10 Batteries

Batteries shall be secured and shielded to prevent leakage in the event of damage or turnover.

13:62-6A.11 Quad vehicle requirements

(a) Quad vehicles shall be equipped with a functional tether type mechanical kill device, so that the ignition is shut off upon the driver's separation from the vehicle.

(b) Quad vehicle engines shall be fitted with a guard completely enclosing the primary drive.

(c) Rear chain guards, roll bars and seat belts are not required.

(d) Quad vehicles shall be equipped with additional nerfing bars to the front of the rear wheels in order to prevent injury to the driver.

(e) All working personnel and officials having access to the track shall be at least 16 years of age.

(f) Vehicles designed to operate with three wheels (tricycles) are prohibited from participation.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Rewrote (e); and added (f).

13:62-6A.12 Pit area driving prohibition

No motorcycle or quad vehicle is to be driven, under power, in the pit area.

SUBCHAPTER 6B. MOTOCROSS ENDURO RACING EVENTS

13:62-6B.1 Licensed facilities

Motocross enduro racing events shall only take place in licensed facilities.

13:62-6B.2 Construction requirements

(a) Design and construction of motocross and quad vehicle race courses must be approved by the Superintendent or his or her designee prior to the racing event.

(b) A sketch or sketches of the track and associated areas shall be provided as near to scale as practicable indicating the location of required safety features.

(c) Safety features such as hubrails, fences, crash protection for participants, light or flagmen positions, spectator seating, entrances and exits, pit facility locations and other physical factors affecting the safety of spectators and participants may be required for approval depending on the terrain and location of the race course. This requirement shall not apply to locations licensed prior to January 1, 1963, unless alterations are made to the track and associated areas on or after January 1, 1963.

13:62-6B.3 Areas designated as spectator areas and fences

(a) The licensee shall designate spectator areas throughout the race course and provide security to prevent spectators from entering the race course.

(b) Fences used to prevent spectators from entering the race course shall be constructed of welded wire fabric or chain link and shall be at least six feet in height and so constructed as not to be easily lifted, climbed over or moved aside.

13:62-6B.4 Flagmen

(a) Licensees may use flagmen provided an assistant flagman is in the starter's area and is in constant two-way radio or telephone communication with all flagmen.

(b) Flagmen shall be positioned so as to be visible to drivers entering each turn on the track or course.

(c) All working personnel and officials having access to the pit area or racing surface shall be at least 18 years of age.

(d) On display of the red flag, all racing vehicles shall stop as soon as possible and remain stopped until such time as the red flag is removed from display.

(e) On display of the amber flag, all racing vehicles shall slow down and maintain their position.

13:62-6B.5 Starters

The licensee shall provide a starter(s) located within a starter's area with an unobscured view of the starting line from which to control the start of the racing event.

13:62-6B.6 Additional guidelines for motocross racing enduro events

(a) All participants shall be 18 years of age and be in possession of a valid motorcycle driver's license from his or her state of residence.

(b) All participating motorcycles must be able to pass all of the motor vehicle regulations governing motorcycles under Title 39 of the New Jersey Motor Vehicle Laws.

(c) In the event that the race course includes local roadway or highways, the participants shall adhere to all of the motor vehicle regulations for that roadway.

13:62-6B.7 Clothing requirements

Drivers shall wear safety clothing to afford maximum protection to the driver according to industry standards. It is recommended that this clothing be of a fire retardant material.

13:62-6B.8 Helmets

All drivers shall wear a properly secured helmet which meets or exceeds the Snell Memorial Foundation Testing Standard K, M or SA, incorporated herein by reference, as may be amended or supplemented, which has not reached the expiration date established by the Snell Memorial Foundation at the time of the event. The standards are available from the Snell Memorial Foundation, 3628 Madison Avenue, Suite 11, North Highlands, CA 95660.

Amended by R.2003 d.374, effective September 15, 2003.
See: 35 N.J.R. 2569(a), 35 N.J.R. 4294(a).

Substituted "Snell Memorial Foundation Testing Standard K, M or SA, incorporated herein by reference, as may be amended or supplemented" for "American National Standard Institute (A.N.S.I.) Z-90.1 testing standard".

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Rewrote the section.

13:62-6B.9 Goggles or face shield

All drivers shall wear windproof, shatterproof goggles or a face shield of the type which meets or exceeds U.S.A. standard Specifications for Head, Eye and Respiratory Protection Z2.1-1959 testing standard, unless excessively muddy conditions would create a view obstruction on those devices.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Inserted " , unless excessively muddy conditions would create a view obstruction on those devices".

13:62-6B.10 Batteries

Batteries shall be secured and shielded to prevent leakage in the event of damage or turnover.

13:62-6B.11 Pit area driving prohibition

No motorcycle is to be driven under power in the pit area.

SUBCHAPTER 6C. MOTORCYCLE, QUAD VEHICLE OR SNOWMOBILE HARE SCRAMBLE EVENTS

13:62-6C.1 Licensed facilities

Motorcycle, quad vehicle, or snowmobile hare scramble events shall only take place in facilities approved for compliance with this chapter and licensed by the Superintendent.

13:62-6C.2 Design and construction requirements

(a) Design and construction of motorcycle, quad vehicle, or snowmobile hare scramble courses and facilities must be approved for compliance with this chapter by the Superintendent or designee prior to the racing event.

(b) A sketch of the entire facility including the race course, spectator area(s), pits area(s) and parking area(s), as close as practicable to scale, with an accompanying written description of the facility shall be provided.

(c) Specific safety features such as hubrails, fences, crash protection, lights and flagmen, and other physical factors affecting the safety of workers, spectators, and participants may be required for approval depending on the terrain and location of the facility.

(d) The race course shall be clearly defined to participants.

(e) All obvious hazards near the race course shall be clearly defined and fitted with a cushion or protected by a barrier, where applicable.

(f) The race course shall be equipped with clearly marked and numbered delineators so as to provide timely response by emergency personnel.

13:62-6C.3 Spectator area

(a) The licensee shall designate and clearly define spectator areas which are physically separated from the race course utilizing fencing so constructed as to not be easily lifted, climbed over, or moved aside.

(b) The licensee shall provide ample security to prevent spectators from entering the race course, pits, or prohibited areas.

(c) Spectator areas shall be so designed and located so as to provide maximum protection for spectators.

13:62-6C.4 Starters, flagmen and course marshals

(a) The licensee shall utilize flagmen and/or course marshals strategically located throughout the race course who are in visual or electronic contact with the starter or race control officials.

(b) All working personnel, officials, flagmen, and course marshals shall be at least 16 years of age and be documented as such by the licensee.

(c) All working personnel, officials, flagmen, and course marshals shall wear brightly colored safety vests to be easily identified or other easily identifiable uniforms while working at a race, practice event or exhibition.

(d) The licensee shall perform sweeps of the race course between each race and division.

(b) The licensee shall erect, along any part of the track where spectators are permitted, whether outside of the track or in the infield, in addition to the hubrail, a four-foot high fence positioned not less than four feet from the edge of the track.

Amended by R.1995 d.206, effective April 17, 1995.
See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).
Amended by R.2001 d.354, effective October 1, 2001.
See: 33 N.J.R. 2250(a), 33 N.J.R. 3451(b).

Rewrote (a); in (b), added the last sentence.
Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

In (a), substituted "2006" for "2001", inserted "or her" preceding "designee" and substituted "NC" for "N.C."; deleted (b); recodified former (c) as (b); and in (b), inserted "four-foot high" and substituted "positioned" for "six feet in height and located".

13:62-8.3 Safety requirements

Go-karts and personnel participating in races, practices, or exhibitions of driving skill on any track or facility licensed by the Superintendent shall comply with the World Karting Association Technical Manual, incorporated by reference at N.J.A.C. 13:62-8.2(a).

Amended by R.1995 d.206, effective April 17, 1995.
See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).
Amended by R.1997 d.211, effective May 19, 1997.
See: 29 N.J.R. 848(a), 29 N.J.R. 2465(b).

Deleted (a)14, prohibiting equipping a go-kart with a gear or sprocket ratio changing device; and recodified former (a)15 through 23 as (a)14 through 22.

Amended by R.2001 d.354, effective October 1, 2001.
See: 33 N.J.R. 2250(a), 33 N.J.R. 3451(b).

Rewrote the section.
Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).
Rewrote the section.

13:62-8.4 Clothing requirements for all go-kart events

All participants shall wear safety clothing and a helmet and neck support in compliance with Section 115 of the World Karting Association Technical Manual incorporated by reference at N.J.A.C. 13:62-8.2(a).

New Rule, R.1995 d.206, effective April 17, 1995.
See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).
Recodified from N.J.A.C. 13:62-8.6 by R.2001 d.354, effective October 1, 2001.

See: 33 N.J.R. 2250(a), 33 N.J.R. 3451(b).
Former N.J.A.C. 13:62-8.4, Serpentine go-kart road course, was repealed.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Rewrote the section.

13:62-8.5 Pit area operation prohibition

No go-karts shall be driven, under power, in the pit area.

New Rule, R.1995 d.206, effective April 17, 1995.
See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).
Recodified from N.J.A.C. 13:62-8.7 by R.2001 d.354, effective October 1, 2001.

See: 33 N.J.R. 2250(a), 33 N.J.R. 3451(b).
Former N.J.A.C. 13:62-8.5, Track construction, was repealed.
Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Substituted "driven," for "operated" and inserted a comma following "power".

13:62-8.6 (Reserved)

Recodified to N.J.A.C. 13:62-8.4 by R.2001 d.354, effective October 1, 2001.

See: 33 N.J.R. 2250(a), 33 N.J.R. 3451(b).
Section was "Clothing requirements for all go-kart events".

13:62-8.7 (Reserved)

Recodified to N.J.A.C. 13:62-8.5 by R.2001 d.354, effective October 1, 2001.

See: 33 N.J.R. 2250(a), 33 N.J.R. 3451(b).
Section was "Pit area operation prohibition".

SUBCHAPTER 9. DEMOLITION DERBY AND TRACTOR PULLS

13:62-9.1 Demolition derby vehicles

(a) In a demolition derby event, any stock, American made, hardtop automobile may be used.

(b) In a demolition derby event, jeeps, carryalls, station wagons, ambulances, and other vehicles utilizing a truck chassis are not permitted. American made and foreign made, stock, hardtop vehicles may participate together in a compact car class with the following guidelines:

1. Vehicles must have four cylinder engines;
2. A maximum wheelbase of 104 inches measured from center of front wheel to center of rear wheel;
3. Vehicles shall not have more than five lug nuts per wheel;
4. Wheel size not to exceed 15 inches;
5. No full framed vehicles allowed; and
6. Compact cars shall not compete with any other class.

(c) All glass, including rear windows, headlights, tail lights, and parking lights, must be removed with the exception of the windshield. If the windshield is removed it must be replaced with heavy mesh screening with a center post or plexiglass.

(d) All chrome strips must be removed from a participating vehicle.

(e) Gas tanks may be moved to a different position within the driving compartment. Tanks relocated into the driver compartment must be placed in the vehicle where the back seat normally would be located, on the right side, behind the front passenger seat. All tanks shall be constructed of steel (22 gauge minimum) or aluminum (16 gauge minimum). Tanks shall be restricted to a maximum capacity of five gallons. Tanks shall be encased in a metal box that is bolted to

the floor of the vehicle. The box shall have a metal lid that is fastened to the container. A metal fire wall must be between the driver and the gas tank.

(f) Fuel lines and pumps will not be allowed in the driving compartment.

(g) All doors must be securely fastened by either welding, metal strips or chains.

(h) Doors opening during an event will automatically disqualify that automobile.

(i) Batteries located within the driver compartment must have a suitable cover and be securely fastened.

(j) All vehicles must be equipped with a securely installed safety belt.

(k) Rear seats must be removed from a participating vehicle.

(l) No vehicle emitting heavy smoke will be allowed to participate. A vehicle discharging heavy smoke after an event has started must be disqualified.

Amended by R.2001 d.354, effective October 1, 2001.
See: 33 N.J.R. 2250(a), 33 N.J.R. 3451(b).

Rewrote (e).

Amended by R.2003 d.374, effective September 15, 2003.
See: 35 N.J.R. 2569(a), 35 N.J.R. 4294(a).

Rewrote (b).

13:62-9.2 Demolition derby participants

(a) Participants in a demolition derby event shall be 17 years of age or older.

(b) A participant must remain in the vehicle until the event has been completed.

(c) All drivers shall wear a properly secured helmet which meets or exceeds the Snell Memorial Foundation Testing Standard K, M or SA, incorporated herein by reference, as may be amended or supplemented, which has not reached the expiration date established by the Snell Memorial Foundation at the time of the event. The standards are available from the Snell Memorial Foundation, 3628 Madison Avenue, Suite 11, North Highlands, CA 95660.

(d) All demolition derby participants shall wear a properly secured head and neck restraint device/system and/or a neck collar which are commercially-produced and designed for racing.

Amended by R.1995 d.206, effective April 17, 1995.

See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).

Amended by R.2003 d.374, effective September 15, 2003.

See: 35 N.J.R. 2569(a), 35 N.J.R. 4294(a).

In (c), substituted "Snell Memorial Foundation Testing Standard K, M or SA, incorporated herein by reference, as may be amended or supplemented" for "American National Standard Institute (A.N.S.I.) Z-90.1 testing standard".

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

In (a), substituted "17" for "18"; rewrote (c); and added (d).

13:62-9.3 Goggles or face shield

The driver of all vehicles not equipped with windshields shall wear windproof, of the type which meets or exceeds U.S.A. standard Specifications for Head, Eye and Respiratory Protection Z2.1-1959 testing standard.

Repeal and New Rule, R.1995 d.206, effective April 17, 1995.

See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).

Formerly "Demolition derby exhibition area".

13:62-9.4 Clothing requirements

Drivers shall wear safety clothing to afford maximum protection to the driver according to industry standards. It is recommended that this clothing be of a fire retardant material.

Repeal and New Rule, R.1995 d.206, effective April 17, 1995.

See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).

Formerly "Demolition derby tow vehicles".

13:62-9.5 Demolition derby exhibition area

(a) The demolition derby exhibition area shall be no more than 250 feet and of 100 feet deep.

(b) The outer edge of the exhibition area shall be marked with poles or similar devices so as to contain the participating vehicles.

(c) No one shall be allowed within this area except track officials and participants.

(d) If mechanics or members of the press are allowed in the infield portion, a suitable fence shall be erected 50 feet from the outer edge of the exhibition area.

(e) Spectators are prohibited within infield portions of the exhibition area unless protected by a fence of at least six feet in height erected no closer than 50 feet from the outer edge of the exhibition area.

Repeal and New Rule, R.1995 d.206, effective April 17, 1995.

See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).

Formerly "Tractor pull age requirement".

13:62-9.6 Demolition derby tow vehicles

(a) Tow vehicles shall be permitted to enter the demolition derby exhibition area for vehicle removal.

(b) There shall be no more than two persons per tow vehicle.

(c) No riders shall be permitted on the outside of the tow vehicle.

Repeal and New Rule, R.1995 d.206, effective April 17, 1995.

See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).

Formerly "Tractor pull kill switch requirement".

13:62-9.7 Tractor pull age requirement

(a) All competitors shall be at least 17 years of age.

(b) All working personnel, officials, and persons having access to the track surface shall be at least 16 years of age.

New Rule, R.1995 d.206, effective April 17, 1995.

See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Inserted designation (a); rewrote(a); and added (b).

13:62-9.8 Tractor pull kill switch requirement

All vehicles competing in a tractor pull event shall be equipped with a kill switch in operating order.

New Rule, R.1995 d.206, effective April 17, 1995.

See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).

13:62-9.9 Speed limits

All vehicles traveling in the pit area or staging area shall obey a five miles per hour speed limit.

New Rule, R.1995 d.206, effective April 17, 1995.

See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).

13:62-9.10 Licensed facilities

Demolition derby and tractor pull events shall only take place in licensed facilities.

New Rule, R.1995 d.206, effective April 17, 1995.

See: 27 N.J.R. 445(a), 27 N.J.R. 1622(a).

—————

SUBCHAPTER 10. AUTOMOBILE ENDURO EVENTS
(OTHER THAN AT LICENSED ROAD COURSE
FACILITIES)

13:62-10.1 Construction requirements

(a) Hubrail construction shall comply in all respects with the requirements of this chapter.

(b) The licensee shall provide and maintain hubrails on the outer circumference of the track and around the entire circumference thereof. Where spectators are allowed in the infield or within the inner circumference of the track, the licensee shall provide and maintain a hubrail, as described in this section, around the inner circumference of the track.

(c) The hubrail shall consist of at least two planks of hard wood or other suitable materials, at least 10 inches in width by three inches in thickness.

1. At any oval track modified or built after March 5, 2007, the hubrail shall be constructed of metal or concrete material in accordance with New Jersey Department of Transportation Standard Roadway Construction-Traffic Control-Bridge Construction Details 2001, incorporated

herein by reference, as may be amended and supplemented, available at <http://www.state.nj.us/transportation/eng/CADD/v8/v8RoadwayDetails/pdf/v8eRoadwayDetailsSet.pdf>. Additional state-of-the-art material shall be considered by the Superintendent or his designee when documentation of such material has been properly submitted to his office for review. All material shall be constructed as to afford maximum protection for spectators and participants.

(d) The hubrail shall be supported by posts of similar material of at least six inches in width and six inches in thickness or round posts not less than seven inches in diameter, which are set in the ground at least four feet and shall extend above the ground at least two feet. The post shall be no higher than the hubrail planking and shall be spaced no more than six feet apart.

(e) Two planks of hardwood or other suitable material shall be mounted on the side of the post facing the track and running horizontally and parallel to each other.

(f) On the opposite side of the posts, not more than eight inches from the top thereof, there shall be a ¾ inch steel cable running around the circumference of the track and securely fastened to the post with eye bolts.

(g) The hubrail entrance and exit gates to the pit area shall be closed while vehicles are in motion on the track, unless alternate arrangements have been made by the installation of barriers of a type which will prevent cars out of control from leaving the track and entering the immediate pit working area.

(h) Where the licensee wishes to use methods other than gates, an inspection of such installations by a representative of the Superintendent is required.

(i) The hubrail opening for vehicles shall be so located that a vehicle leaving the track must turn 90 degrees before entering the pit area.

(j) At locations using methods other than gates between the pit area and the track, the licensee shall provide a guard to prevent unauthorized persons from entering the track area.

(k) The use of baled hay or straw or any similar material as a protective device between participating vehicles and spectators is specifically prohibited.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Added (c)1.

13:62-10.2 Fences

All fences installed for the purpose of limiting spectator areas shall be constructed of welded wire fabric or chain link and shall be at least six feet in height and so constructed as not to be easily lifted, climbed, or moved aside.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Deleted “, except at motocross events the fence shall be of the same construction but at least five feet in height” from the end.

13:62-10.3 Red and amber lights

(a) Each track used for automotive racing, except those used for acceleration and performance tests, shall be equipped with a system of at least four red lights and four amber lights so arranged that at least one light of each color will be visible to the drivers as they enter each turn.

(b) The lights shall be controlled by a single switch. The licensee shall provide a responsible person to operate such switch during the entire time of each race.

(c) When the red lights are illuminated, all racing vehicles on the track shall stop as soon as possible and remain stopped until such time as the red lights are turned out.

(d) When the amber lights are illuminated, all racing vehicles on the track shall slow down and maintain their position unless otherwise directed to change position by a track official.

13:62-10.4 Flagmen

(a) On tracks over one mile in length, licensees may use flagmen in lieu of the red and amber lights, provided the assistant flagman in the starter's stand is in constant two-way radio or telephone communication with all flagmen.

(b) On display of the red flag, all racing vehicles shall stop as soon as possible and remain stopped until such time as the red flag is removed from display.

(c) On display of the amber flag, all racing vehicles shall slow down and maintain their position unless directed to change their position by a track official.

13:62-10.5 Starters

(a) The licensee shall provide starter(s) located within a starter's stand with an unobscured view of the entire racing surface from which to control the racing event.

(b) All circular or oval tracks, road courses and other locations utilizing the services of flagmen to control the event shall also have an assistant flagman in the starter's stand. The assistant flagman used to control or start a race shall be in the starter's stand when starting and during the race.

13:62-10.6 Maximum protection

(a) All hubrails, fences, stands and buildings shall be constructed and maintained so as to afford maximum protection for spectators.

(b) Any spectator stand erected or relocated on or after April 1, 1960, must be located at least 25 feet from the hubrail.

13:62-10.7 Driver and vehicle requirements

(a) All drivers in enduro events shall be at least 18 years of age and possess a driver's license. The licensee shall check the license for validity.

(b) All drivers shall wear a properly secured helmet which meets or exceeds the Snell Memorial Foundation Testing Standard K, M or SA, incorporated herein by reference, as may be amended and supplemented, which has not reached the expiration date established by the Snell Memorial Foundation at the time of the event. The standards are available from the Snell Memorial Foundation, 3628 Madison Avenue, Suite 11, North Highlands, CA 95660.

(c) The driver of all vehicles shall wear windproof, shatter-proof goggles or a face shield of the type which meets or exceeds U.S.A. standard Specifications for Head, Eye and Respiratory Protection Z2.1-1959 testing standard.

(d) All drivers shall wear fire retardant suits, fire retardant underwear and a properly secured head and neck restraint device/system and or a neck collar, which are commercially-produced and designed for racing.

(e) All drivers are required to wear fire resistant gloves.

(f) All drivers are required to wear fire resistant shoes and it is recommended that fire resistant socks be worn.

(g) No driver shall compete with head or arm extended outside of the doors or windows.

(h) A driver shall remain with the vehicle if it is disabled during the race, except that:

1. During a red light or red flag, the driver may exit the vehicle and return to the pit area at direction of track personnel.

2. Racing should be stopped (red flagged) at 15-minute intervals to allow drivers to exit to pit area. The time intervals may be extended if no disabled vehicles are located on the track.

(i) Each vehicle shall have a minimum 104-inch wheel-base.

(j) Convertibles, pickup trucks, station wagons, or vans are prohibited in enduro events.

Amended by R.2003 d.374, effective September 15, 2003.
See: 35 N.J.R. 2569(a), 35 N.J.R. 4294(a).

In (b), substituted "Snell Memorial Foundation Testing Standard K, M or SA, incorporated herein by reference, as may be amended or supplemented" for "American National Standard Institute (A.N.S.I.) Z-90.1 testing standard".

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Rewrote (b) and (d).

13:62-10.8 Windshield

(a) The originally installed windshield may remain but all other glass must be completely removed from a participating vehicle.

(b) Window net or screen shall be securely installed on the driver's side.

13:62-10.9 Mirrors

Inside rear view mirrors are permitted. Outside view mirrors are prohibited.

13:62-10.10 Vehicle interior and exterior requirements

(a) Chrome and nonmetallic trim shall be removed from sides of the vehicle.

(b) Passenger seats shall be removed from the interior of the vehicle.

(c) A safety hub or reinforced wheel is required on the vehicle's right front wheel.

(d) All doors shall be bolted, chained or welded closed. Any door opening during an event shall constitute automatic disqualification.

(e) The exterior of the driver's side door shall have at least one metal brace at bumper height.

(f) All vehicles shall retain stock appearance with no alterations to fenders or wheel wells.

13:62-10.11 Tires

(a) Passenger tires with United States Department of Transportation numbers shall be allowed with a maximum tread width of seven inches.

(b) Studs or "cheater-slicks" are prohibited.

(c) Wheel rim width shall not exceed seven inches.

13:62-10.12 Fuel tanks

(a) Except as set forth in (b) below, vehicles using a self-contained fuel cell with an inner rubber bladder shall bolt the self-contained fuel cell to the frame of the vehicle utilizing an "x" type frame work under the cell. At least three one inch metal straps ¼ inch thick shall be bolted to the frame of the vehicle by at least two ¾ inch three line bolts and angled to go around the cell, except for the bottom, to apply maximum pressure against the tank to the frame.

(b) Vehicles with limited space shall have the fuel cell secured by four one inch metal straps, ¼ inch thick, bolted to the frame of the vehicle by at least two ¾ inch three line bolts and angled to go entirely around the cell to apply maximum pressure against the fuel tank.

(c) A conventional type fuel tank shall be bolted within the frame of the vehicle.

(d) A reinforcing member of the same kind and size material as that used in the roll cage of the chassis shall be installed to the rear of the fuel tank joining the rearmost portion of the chassis.

(e) A vehicle utilizing a fuel tank mounted to the front of the front fire wall shall have a reinforcing member of the same kind of material as that used in the roll cage or chassis, installed in such a manner as to afford maximum protection to the tank.

(f) A metal fire wall shall be installed between the fuel tank and driver's compartment to afford the driver maximum protection.

13:62-10.13 Fuel lines

Fuel lines shall not pass through the passenger compartment of the vehicle.

13:62-10.14 Engine and suspension requirements

(a) The engine shall remain stock with a factory installed carburetor and manifold.

(b) Altering of suspension or torching of springs is prohibited.

13:62-10.15 Seat belts

(a) A shoulder harness and four point racing lap belt in good working condition shall be installed and properly worn during the event.

(b) A lap belt and shoulder harness installed in a position other than manufacturer's shall be affixed to the outer floor utilizing four inch by four inch steel plate and bolts of adequate tempered steel strength.

(c) All safety belts and shoulder harnesses shall bear the date of manufacture and shall not be used for more than two years from that date.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Added (c).

13:62-10.16 Bumpers

All vehicles shall be equipped with stock bumpers securely fastened on the front and rear. Outside bracing of bumpers is prohibited.

13:62-10.17 Batteries

(a) Batteries shall be properly secured as follows:

1. Batteries located in the driver compartment shall be shielded to prevent leakage in the event of damage or turnover.

2. Batteries located adjacent to the fuel supply of the vehicle shall be secured in a metal box bolted to the frame of the vehicle by at least four $\frac{3}{8}$ inch three line bolts and in such a manner to apply maximum pressure against the metal box to the frame. The battery shall also have a marine box cover secured to the top of the metal box as to not allow any movement of the battery.

3. Batteries located in any other area not specified in (a)1 and 2 above shall be shielded to prevent leakage in the event of damage or turnover.

13:62-10.18 Seats

(a) A factory installed front seat shall be utilized provided it is equipped with a headrest.

(b) Seats shall be attached to the main frame of the vehicle, the frame of the roll cage or to a substantial metal plate utilizing a minimum of six, three line, $\frac{5}{16}$ inch bolts.

(c) The base of the seat shall be installed with four $\frac{5}{16}$ inch bolts not more than three inches from the outer edge at the four most practical points.

(d) Two bolts shall be installed at the two most practical points at the top of the back of the seat and a metal strap of at least two inches in width and $\frac{3}{8}$ inch thick shall connect every two bolts.

13:62-10.19 Rollover cage

(a) All race cars shall be equipped with a rollover cage surrounding the driver of a design, construction and quality affording the driver maximum protection against injury.

(b) Rollover bars installed in vehicle shall be a minimum of three inches above and six inches behind the driver's head.

(c) The outside diameter of the rollover bars shall be a minimum of one and three-quarters inch and wall thickness a minimum of .09 inch.

(d) Rollover bars welded, bolted or fastened to the flooring shall utilize a six inch by six inch by one-quarter inch base plate.

(e) Vehicles having uni-body construction may install a rollover bar welded to the frame of the vehicle utilizing six inch by six inch by one-quarter inch base plate affixed to outer flooring.

(f) Rollover bars shall be plainly visible with the exception of built-in or integral rollover bars.

(g) Vehicles with built-in or integral rollover bars shall maintain and provide upon request by the Superintendent or

designee the manufacturer's detailed drawing establishing the dimensions and material utilized.

13:62-10.20 Miscellaneous equipment requirements

(a) Two drive shaft loops shall be installed not more than 24 inches from the front and rear yokes of the vehicle.

(b) All vehicles shall have an opening in the hood to properly expose the carburetor.

(c) The radiator shall remain in the manufacturer's position. Any movement of the radiator is prohibited.

(d) The front and rear trunk lid shall remain securely fastened with cable or chain throughout the entire event. Any incidental opening shall disqualify the vehicle from the event.

(e) Outer decorations on the vehicle utilizing poles, flags, staffs or other hazardous protuberances are prohibited.

(f) Transmission and radiator cooling cores located inside the vehicle are prohibited.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

In (a), substituted "Two" for "The" and "loops" for "loop".

13:62-10.21 Additional track responsibilities

(a) The licensee shall maintain safe conditions during all pit stops.

(b) The licensee shall insure that disabled vehicles are left at the point of disablement.

(c) The licensee shall maintain adequate fire apparatus on location during the event, including:

1. A fire vehicle with a minimum of 300 pounds of dry chemical then meets the National Fire Protection Association standards of a mini pumper;

2. Twenty-pound fire extinguishers, at a minimum, with a minimum of 10 B.C. rating shall be maintained on location during an event; and

3. A minimum of two sets of protective turn-out gear shall be available to track personnel.

13:62-10.22 Speed limits

All vehicles traveling in the pit area or staging area must obey a five miles per hour speed limit.

13:62-10.23 Licensed facilities

Automobile enduro events shall only take place in licensed facilities.

SUBCHAPTER 11. MUD HOP

13:62-11.1 Construction requirements

(a) Hubrail construction shall comply in all respects with the requirements of this chapter.

(b) The licensee shall provide and maintain hubrails on the outer circumference of the track and around the entire circumference thereof. Where spectators are allowed in the infield or within the inner circumference of the track, the licensee shall provide and maintain a hubrail, as described in this section, around the inner circumference of the track.

(c) The hubrail shall consist of at least two planks of hard wood or other suitable materials, at least 10 inches in width by three inches in thickness.

(d) The hubrail shall be supported by posts of similar material of at least six inches in width and six inches in thickness or round posts not less than seven inches in diameter, which are set in the ground at least four feet and shall extend above the ground at least two feet. The post shall be no higher than the hubrail planking and shall be spaced no more than six feet apart.

(e) Two planks of hardwood or other suitable material shall be mounted on the side of the post facing the track and running horizontally and parallel to each other.

(f) On the opposite side of the posts, not more than eight inches from the top thereof, there shall be a $\frac{3}{4}$ inch steel cable running around the circumference of the track and securely fastened to the post with eye bolts.

(g) The hubrail entrance and exit gates to the pit area shall be closed while vehicles are in motion on the track, unless alternate arrangements have been made by the installation of barriers of a type which will prevent cars out of control from leaving the track and entering the immediate pit working area.

(h) Where the licensee wishes to use methods other than gates, an inspection of such installations by a representative of the Superintendent is required.

(i) The hubrail opening for vehicles shall be so located that a vehicle leaving the track must turn 90 degrees before entering the pit area.

(j) At locations using methods other than gates between the pit area and the track, the licensee shall provide a guard to prevent unauthorized persons from entering the track area.

(k) The use of baled hay or straw or any similar material as a protective device between participating vehicles and spectators is specifically prohibited.

13:62-11.2 Fences

All fences installed for the purpose of limiting spectator areas shall be constructed of welded wire fabric or chain link

and shall be at least six feet in height and so constructed as not to be easily lifted, climbed, or moved aside.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Deleted “, except at motocross events the fence shall be of the same construction but at least five feet in height” from the end.

13:62-11.3 Red and amber lights

(a) Each track used for automotive racing, except those used for acceleration and performance tests, shall be equipped with a system of at least four red lights and four amber lights so arranged that at least one light of each color will be visible to the drivers as they enter each turn.

(b) The lights shall be controlled by a single switch. The licensee shall provide a responsible person to operate such switch during the entire time of each race.

(c) When the red lights are illuminated, all racing vehicles on the track shall stop as soon as possible and remain stopped until such time as the red lights are turned out.

(d) When the amber lights are illuminated, all racing vehicles on the track shall slow down and maintain their position unless otherwise directed to change position by a track official.

13:62-11.4 Flagmen

(a) Licensees of tracks over one mile in length may use flagmen in lieu of the red and amber lights, provided the assistant flagman in the starter's stand is in constant two-way radio or telephone communication with all flagmen.

(b) On display of the red flag, all racing vehicles shall stop as soon as possible and remain stopped until such time as the red flag is removed from display.

(c) On display of the amber flag all racing vehicles shall slow down and maintain their position unless directed to change position by a track official.

13:62-11.5 Starters

(a) The licensee shall provide a starter(s) located within a starter's stand with an unobscured view of the entire racing surface from which to control the racing event.

(b) At all circular or oval tracks, road courses and other locations utilizing the services of flagmen to control the event, the licensee shall also have an assistant flagman in the starter's stand. The assistant flagman used to control or start a race shall be in the starter's stand when starting and during the race.

13:62-11.6 Maximum protection

(a) All hubrails, fences, stands and buildings shall be constructed and maintained so as to afford maximum protection for spectators.

(b) Any spectator stand erected or relocated on or after April 1, 1960, must be located at least 25 feet from the hub-rail.

13:62-11.7 Licensed facilities

Mud hop events shall only be conducted at licensed facilities.

13:62-11.8 Alcohol/controlled dangerous substances prohibited

No alcohol or controlled dangerous substances shall be permitted within the pit area. Anyone departing the pit area shall be prohibited from returning during the duration of the event if the individual has consumed alcohol or a controlled dangerous substance.

13:62-11.9 Driver requirements

(a) Mud hop drivers shall be a minimum of 17 years of age and possess a valid driver's license from the driver's state of residence.

(b) The driver's license number shall be recorded on an entry form and checked by the licensee for validity.

(c) The driver shall remain with a disabled vehicle until properly escorted from the racing track.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).
In (a), substituted "of 17" for "18".

13:62-11.10 Equipment requirements

(a) All drivers shall wear a properly secured helmet which meets or exceeds Snell Memorial Foundation Testing Standard SA, incorporated by reference herein, as may be amended or supplemented, which has not reached the expiration date established by the Snell Memorial Foundation at the time of the event. The standards are available from the Snell Memorial Foundation, 3628 Madison Avenue, Suite 11, North Highlands, CA 95660.

(b) The driver of all vehicles shall wear windproof, shatterproof goggles or a face shield of the type which meets or exceeds U.S.A. standard Specifications for Head, Eye and Respiratory Protection Z2.1-1959 testing standard.

(c) Drivers shall be attired in a shirt, long pants and shoes, at a minimum. It is recommended that this clothing be of a fire retardant material.

(d) The extension of the driver's head or arm outside the vehicle is prohibited.

(e) All drivers shall wear a properly secured head and neck restraint device/system and/or a neck collar, which are commercially-produced and designed for racing.

Amended by R.2003 d.374, effective September 15, 2003.

See: 35 N.J.R. 2569(a), 35 N.J.R. 4294(a).

In (a), substituted "Snell Memorial Foundation Testing Standard K, M or SA, incorporated herein by reference, as may be amended or supplemented" for "American National Standard Institute (A.N.S.I.) Z-90.1 testing standard".

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Rewrote (a); and added (e).

13:62-11.11 Windows

(a) The windshield of the participating vehicle may remain as originally installed.

(b) Heavy mesh screening with a metal post covering the entire opening or plexiglass with a center post shall be utilized where the original windshield is removed.

13:62-11.12 Vehicle interior and exterior requirements

(a) Sharp edges created by accidental vehicle contact shall be folded over to render the vehicle safe.

(b) Alterations to the fenders or wheel wells are prohibited on stock vehicles.

(c) All doors of participating vehicles shall remain closed during an event. Any opening shall constitute automatic disqualification.

13:62-11.13 Seat belts

(a) Seat belts are required and shall be properly worn during the event.

(b) A racing lap belt and shoulder harness shall be installed and utilized on any modified vehicle, provided it is:

1. Approved through the licensee's technical inspection and found to be in good condition; and
2. Securely affixed to the outer flooring and reinforced by a four inch by four inch steel plate and bolts of adequate tempered steel strength.

(c) Cable, chain or straps securing devices for seat belts are prohibited.

13:62-11.14 Rollover cage

(a) Open cab vehicles shall be equipped with rollover cage surrounding the driver of a design, construction and quality affording the driver maximum protection against injury.

(b) Rollover bars installed in vehicle shall be a minimum of three inches above and six inches behind the driver's head.

(c) Rollover bars shall be a minimum of 1¾ inch outside diameter with a wall thickness of a minimum of .09 inch.

(d) Rollover bars welded, bolted or fastened to the flooring shall utilize a six inch by six inch by ¼ inch base plate.

(e) Vehicles having uni-body construction may have a roll-over bar welded to the frame of the vehicle utilizing six inch by six inch by ¼ inch base plate affixed to the outer flooring.

(f) Rollover bars shall be plainly visible with the exception of built-in or integral rollover bars.

(g) Owners of vehicles with built-in or integral rollover bars shall maintain and provide upon request by the Superintendent or designee the manufacturer's detail drawing establishing the dimensions and material utilized.

13:62-11.15 Bumpers

All vehicles shall be equipped with bumpers securely fastened on the front and rear. Outside bracing of bumpers shall be prohibited.

13:62-11.16 Batteries

(a) Batteries shall be properly secured as follows:

1. Batteries located in the driver compartment shall be shielded to prevent leakage in the event of damage or turnover.

2. Batteries located adjacent to the fuel supply of the vehicle must be secured in a metal box bolted to the frame of the vehicle by at least four ⅜ inch three line bolts to apply maximum pressure against the metal box to the frame. The battery shall also have a marine box cover secured to the top of the metal box as to not allow any movement of the battery.

3. Batteries shall not be located within the driver's compartment.

4. Batteries located in any other area not specified in (a)1 and 2 above shall be shielded to prevent leakage in the event of damage or turnover.

13:62-11.17 Miscellaneous equipment requirements

(a) The drive shaft loop shall be installed not more than 24 inches from the front and rear yokes of modified vehicles.

(b) The radiator, if moved from the manufacturer's position, shall be shielded from the driver by a firewall.

(c) The front and rear trunk lid shall remain securely fastened with cable or chain throughout the entire event. Any incidental opening shall disqualify the vehicle from the event.

(d) Outer decorations on the vehicle utilizing poles, flags, staffs or other hazardous protuberances are prohibited.

(e) Transmission and radiator cooling lines or cooling cores shall be equipped with a metal fire wall separating the driver for maximum security.

(f) Tow hooks or tow bars shall be installed and secured to the frame of the vehicle.

(g) No vehicle shall transport more than one person at any time during an event or warm-up.

13:62-11.18 Braking system and pedal reserve

(a) The licensee shall test and approve each vehicle for break pedal reserve prior to the vehicle departing the pit area.

(b) No vehicle shall be permitted to participate in any event if the braking system includes a direct application of pressure to any of the tires or any apparent deficiencies.

13:62-11.19 Automatic transmission safety mats

(a) Any modified vehicle with an automatic transmission shall have a steel mat, plate, or blanket installed over the transmission so as to protect the driver from injury caused by the fragmentation of the automatic transmission upon explosion.

(b) Two drive shaft loops shall be installed not more than 24 inches from the front and rear yokes of the vehicle.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Inserted designation (a); and added (b).

13:62-11.20 Seats

(a) A factory installed front seat may be utilized provided it is equipped with a headrest.

(b) Seats shall be attached to the main frame of the vehicle, the frame of the roll cage or to a substantial metal plate utilizing a minimum of six, three line, five-sixteenths inch bolts.

(c) The base of the seat shall be installed with four five-sixteenths inch bolts not more than three inches from the outside edge of the four most practical points.

(d) Two bolts shall be installed at the two most practical points at the top of the back of the seat and a metal strap of at least two inches in width and one-eighth inch in thickness shall connect every two bolts.

13:62-11.21 Additional track responsibilities

(a) The licensee shall maintain safe conditions during all pit stops.

(b) The licensee shall maintain adequate fire apparatus on location during the event, including:

1. A fire vehicle that meets the National Fire Protection Associations standards of a mini pumper;

2. Twenty-pound fire extinguishers, at a minimum, with a minimum of 10 B.C. rating on location during an event; and

3. A minimum of two protective turn out gear shall be available to track personnel.

13:62-11.22 Speed limits

All vehicles traveling in the pit area or staging area must obey a five miles per hour speed limit.

13:62-11.23 Licensed facilities

Mud hop events shall only take place in licensed facilities.

**SUBCHAPTER 12. REACTION POWER VEHICLES,
THRILL SHOWS AND GYMKHANAS**
13:62-12.1 Licensed facilities

(a) Reaction powered vehicles and thrill shows are prohibited from non-licensed facilities.

(b) Applications shall be forwarded to the Superintendent for approval in accordance with standards set forth in this chapter at least 60 days prior to any proposed event. Applications shall include a full description of the proposed event.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).
Rewrote (b).

13:62-12.2 Vehicle equipment

(a) All vehicles equipped with parachute(s) shall have a red streamer attached to the safety pin(s). The safety pin shall be removed from the parachute prior to the starting lights being activated.

(b) All vehicles utilizing two or more parachutes shall have at least two anchoring points for each parachute, each point separate from the other.

SUBCHAPTER 12A. QUARTER MIDGETS EVENTS
13:62-12A.1 Licensed facilities

Quarter midget events shall only take place in licensed facilities. Except as specifically set forth in this chapter, all facilities, participants and vehicles shall comply with the 2006 rules, requirements and specifications of the Quarter Midgets of America relative to the class or division of competition, incorporated herein by reference, as amended and supplemented. A copy of these rules can be obtained by contacting the Quarter Midgets of America, 6118 E. 19th Street, Tulsa, OK 74112.

Amended by R.2007 d.79, effective March 5, 2007.
See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).
Inserted the last two sentences.

13:62-12A.2 Track construction

(a) Construction of hubrails, fences and other safety devices for quarter midget events shall comply in all respects with provisions of this subchapter.

(b) The hubrail construction for quarter midget events shall be the same as the hubrail construction used for go-kart and motorcycle events in that planks made of marine plywood three-quarter inches thick and 12 inches wide may be used.

(c) The licensee shall erect along any part of the track where spectators are permitted, in addition to the hubrail, a fence six feet in height and located not less than four feet from the edge of the track.

13:62-12A.3 Safety requirements

(a) Quarter midgets and persons participating in races or exhibitions of driving skill on any track or facility licensed by the Superintendent shall comply with the following requirements:

1. No person under the age of five years of age may operate a quarter midget in any race or exhibition of driving skills.

2. All quarter midget facilities, participants and vehicles shall comply with the rules, requirements and specifications of the Quarter Midgets of America relative to the class or division of competition, which are incorporated by reference at N.J.A.C. 13:62-12A.2.

i. On written request of a licensee, the Superintendent may approve any revisions or amendments by the Quarter Midgets of America. Approval of such request shall be reflected in a proposed amendment to this chapter.

3. No repairs shall be made on any quarter midget during the course of a race unless the vehicle is removed to the pit area.

4. A starting apron shall be provided where the quarter midgets are to be started. Persons shall not enter the race course to push a quarter midget. A quarter midget which has not been started on the starting apron shall not be pushed on to the track proper but shall return to the pit area or to the rear of the starting apron. No person shall enter the race course for the purpose of starting a stalled quarter midget while any race or exhibition is in progress.

5. All drivers shall wear a properly secured helmet, which meets or exceeds the Snell Memorial Foundation Testing Standard SA, incorporated herein by reference, as may be amended or supplemented, which has not reached the expiration date established by the Foundation at the time of the event. The standards are available from the Snell Memorial Foundation, 3628 Madison Avenue, Suite 11, North Highlands, CA 95660. All drivers shall also wear a properly secured head and neck restraint device/system

and/or a neck collar which are commercially produced and designed for racing.

6. The driver of all vehicles shall wear windproof, shatterproof goggles or a face shield of the type which meets or exceeds U.S.A. standard Specifications for Head, Eye and Respiratory Protection Z2.1-1959 testing standard.

7. All participants shall remain inside the cockpit of the vehicle while the vehicle is on the track with the engine running. The participant shall not be permitted to race (black flagged) if the participant leans outside of the vehicle, in such a manner that his or her helmet is positioned more than halfway past the outer edge of the Jersey bar.

8. All novice class quarter midget vehicles shall be equipped with an additional external engine shut off switch placed on the top of the roll bar to shut off the vehicles engine in case of emergency.

9. All fuel lines, which pass through the driver compartment shall be shielded utilizing a steel braided material.

10. Fuel lines shall have automotive fittings or positive clamps.

11. Rigid fuel lines are prohibited.

Amended by R.1997 d.211, effective May 19, 1997.

See: 29 N.J.R. 848(a), 29 N.J.R. 2465(b).

Added (a)9 through 11.

Amended by R.2003 d.374, effective September 15, 2003.

See: 35 N.J.R. 2569(a), 35 N.J.R. 4294(a).

In (a), substituted "Snell Memorial Foundation Testing Standard K, M or SA, incorporated herein by reference, as may be amended or supplemented" for "American National Standard Institute (A.N.S.I.) Z-90.1 testing standard" in 5.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Rewrote the introductory paragraph of (a)2, and rewrote (a)5 and (a)7; and in (a)9, inserted " , which pass through the driver compartment".

13:62-12A.4 Speed limits for all quarter midget events; pit area operation prohibition

No quarter midget race car shall be driven, under power, in the pit area.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Deleted (a); deleted designation (b); inserted "race car", substituted "driven," for "operated", and inserted a comma following "power".

SUBCHAPTER 12B. JUNIOR DRAG RACING EVENTS

13:62-12B.1 Licensed facilities

Except as specifically set forth in this subchapter, all licensed facilities, participants, and participating vehicles shall comply with the requirements and specifications of the 2006 National Hot Rod Association Junior Drag Racing League Rulebook, relative to class of competition, incorporated herein by reference, as may be amended and supplemented. A copy of these rules may be obtained by contacting the NHRA

at National Hot Rod Association Technical Department, 2035 Financial Way, Glendora, CA 91740.

Repeal and New Rule, R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Section was "Licensed facilities".

13:62-12B.2 Construction requirements

(a) Hubrail construction shall comply in all respects with the requirements of this subchapter.

(b) The licensee shall provide and maintain hubrails on the outer area of the track and around the entire area thereof. Where spectators are allowed in the return road or within the inner area of the track, the licensee shall provide and maintain a hubrail, as described in this section, around the inner area of the track.

(c) The hubrail shall consist of at least two planks of hard wood or other suitable materials, at least 10 inches in width by three inches in thickness.

1. At any oval track modified or built after March 5, 2007, the hubrail shall be constructed of metal or concrete material in accordance with New Jersey Department of Transportation Standard Roadway Construction-Traffic Control-Bridge Construction Details 2001, incorporated herein by reference, as may be amended and supplemented. The standard is available at <http://www.state.nj.us/transportation/eng/CADD/v8/v8RoadwayDetails/pdf/v8eRoadwayDetailsSet.pdf>. Additional state-of-the-art material shall be considered by the Superintendent or designee when documentation of such material has been properly submitted to for review. All material shall be constructed as to afford maximum protection for spectators and participants.

(d) The hubrail shall be supported by posts of similar material of at least six inches in width and six inches in thickness or round posts not less than seven inches in diameter, which are set in the ground at least four feet and shall extend above the ground at least two feet. The post shall be no higher than the hubrail planking and shall be spaced no more than six feet apart.

(e) Two planks of hardwood or other suitable material shall be mounted on the side of the post facing the track and running horizontally and parallel to each other.

(f) On the opposite side of the posts, not more than eight inches from the top thereof, there shall be a ¾ inch steel cable running around the circumference of the track and securely fastened to the post with eye bolts.

(g) The hubrail entrance and exit gates to the pit area shall be closed while vehicles are in motion on the track, unless alternate arrangements have been made by the installation of barriers of a type which will prevent cars out of control from leaving the track and entering the immediate pit working area.

(h) Where the licensee wishes to use methods other than gates, an inspection of such installations by a representative of the Superintendent is required.

(i) The hubrail opening for vehicles shall be so located that a vehicle leaving the track must turn 90 degrees before entering the pit area.

(j) At locations using methods other than gates between the pit area and the track, the licensee shall provide a guard to prevent unauthorized persons from entering the track area.

(k) The use of baled hay or straw or any similar material as a protective device between participating vehicles and spectators is specifically prohibited.

Amended by R.2007 d.79, effective March 5, 2007.

See: 38 N.J.R. 4806(a), 39 N.J.R. 790(a).

Added (c)1.

13:62-12B.3 Fences

All fences installed for the purpose of limiting spectator areas shall be constructed of welded wire fabric or chain link and shall be at least six feet in height and so constructed as not to be easily lifted, climbed over or moved aside, except at motocross events the fence shall be of the same construction but at least five feet in height.

13:62-12B.4 Starting tree lights

(a) Strips used for acceleration and performance tests need be equipped with only one red light on the starting tree.

(b) The lights shall be controlled by a single switch. The licensee shall provide a responsible person to operate such switch during the entire time of each race.

13:62-12B.5 Starters

(a) The licensee shall provide starter(s) located within a starter's area with an unobscured view of the entire racing surface from which to control the racing event.

13:62-12B.6 Maximum protection

(a) All hubrails, fences, stands and buildings shall be constructed and maintained so as to afford maximum protection for spectators.

(b) Any spectator stand erected or relocated on or after April 1, 1960, must be located at least 25 feet from the hubrail.

13:62-12B.7 Location

(a) A location approved for acceleration and performance tests shall provide for a stopping distance at least equal to the acceleration and timing distance.

(b) The acceleration area shall not exceed 660 feet.

(c) The entire racing strip, including the deceleration area, shall be paved.

(d) The end of the acceleration area may be marked by an overhead banner, provided the supports are of such construction that they will not present a hazard to the vehicles. The height of the banner shall be at least 14 feet above the surface of the strip.

(e) All junior dragsters shall only compete utilizing the 1/8 of a mile track surface.

13:62-12B.8 Vehicle equipment and driver requirements

(a) Junior drag racers and personnel participating in races or exhibitions of driving skill on any track or facility licensed by the Superintendent shall comply with the following requirements:

1. No person under the age of eight years of age may operate a junior dragster in any race or exhibition of driving skill.

2. All junior dragster vehicles shall adhere to the rules and regulations governing junior drag racing vehicles in the National Hot Rod Association (NHRA) Junior Dragracing League Rulebook incorporated by reference at N.J.A.C. 13:62-12B.1.

3. No repairs shall be made on any junior drag racer during the course of a race unless the vehicle is removed to the pit area.

4. Persons shall not enter the race course to push a junior drag vehicle. A junior drag vehicle which has not been started on the starting area shall not be pushed on to the track proper but must return to the pit area or to the rear of the starting line. No person shall enter the race course for the purpose of starting a stalled junior drag vehicle while any race or exhibition is in progress.

5. All drivers shall wear a properly secured helmet which meets or exceeds the Snell Memorial Foundation Testing Standard SA, incorporated herein by reference as may be amended and supplemented, which has not reached the expiration date established by the Snell Memorial Foundation at the time of the event. The standards are available from the Snell Memorial Foundation, 3628 Madison Avenue, Suite 11, North Highlands, CA 95660.

6. The driver of all vehicles shall wear windproof, shatterproof goggles or a face shield of the type which meets or exceeds U.S.A. standard Specifications for Head, Eye and Respiratory Protection Z2.1-1959 testing standard.

7. All participants shall remain inside the cockpit of the junior dragster while the vehicle's engine is running.

8. All junior dragster vehicles shall be equipped with an additional external engine shut off switch on top of the